

## Coaxial PCB Connector 2x8A\_82\_MXPM-S50-0-1

### Description

Straight PCB jack

Interface Standards

HUBER+SUHNER MXPM STD (Patent US 8,360,807 / Patent pend.)



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	70 GHz

#### Mechanical Data

Board mounting type	pin-in-hole / SMT
Weight	0.01 kg

#### Environmental Data

Operating temperature	0 °C to 85 °C
2011/65/EC (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact		
Outer contact	Brass	SUCOPRO / Gold Plating
Body	Brass	SUCOPRO / Gold Plating

### Related Documents

Outline drawing	DOU-00332824
Catalogue drawing	DCA-00364569

### Ordering Information

Single package	2x8A_82_MXPM-S50-0-1/-11_NE
Tape and Reel package	2x8A_82_MXPM-S50-0-1/-11_NM

### Remarks

Multicoax socket, 2x8 ganged, keyed

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[2x8A\\_82\\_MXPM-S50-0-1/-11\\_NM](#) [2x8A\\_82\\_MXPM-S50-0-1/-11\\_NE](#)