

# Multranol<sup>®</sup> 3900

## Characterization

Multranol 3900 polyether polyol is a 4,800-molecular-weight polyoxypropylene triol specially modified with ethylene oxide.

### Characteristic data

Property	Value	Unit of measurement	Method
Hydroxyl number	33.8 - 37.2	mg KOH/g	
Water	max. 0.05	Wt. %	
Acid number	max. 0.015	mg KOH/g	
Color	max. 50	Pt•Co	

### Other data\*

Property	Value	Unit of measurement	Method
Appearance	Clear, viscous liquid		
Specific gravity at 25°C	1.02		
Viscosity at 25°C	820	cps	
Flash point PMCC	184	°C	
Bulk density	8.56	lb/gal	

\*These values provide general information and are not part of the product specification.

## Properties / Applications

Multranol 3900 polyether polyol is a 4,800-molecular-weight polyoxypropylene triol specially modified with ethylene oxide. The terminal end-groups have a high percentage of primary hydroxyl end-groups, giving it a relatively high rate of reactivity with isocyanates. It is compatible with most polyether polyols and can be blended with other diols, triols, and polymer polyols to achieve desirable modifications of product properties.

Multranol 3900 polyol is used in a broad range of urethane foam and other applications, including sealants, caulks, deck coatings, elastomers, tire fill, and reaction injection molding (RIM). As with any product, the use of Multranol 3900 polyol in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability.

## Storage

Multranol 3900 polyol is slightly hygroscopic and may absorb water. Containers should be kept tightly closed and protected from contamination with moisture and foreign materials, which can adversely affect product quality. This polyol can become quite viscous at low temperatures. For ease of handling,



# Multranol<sup>®</sup> 3900

storage temperatures between ambient room temperature and 15°C (59°F) are recommended.

---

## Health and Safety Information

Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling this product. Before working with this product, you must read and become familiar with the available information on its risks, proper use, and handling. This cannot be overemphasized. Information is available in several forms, e.g., safety data sheets and product labels. For further information contact your Covestro LLC representative or the Product Safety and Regulatory Affairs Department in Pittsburgh, PA.

---

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether our products, technical assistance and information are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent.

---

Editor: Covestro LLC  
1 Covestro Circle  
Pittsburgh, Pennsylvania 15205  
United States  
[www.covestro.com](http://www.covestro.com)

**Contact:**  
CAS Single Point of Contact Office  
Tel. 412-413-3983