

Multranol[®] 4011

Characterization

Multranol 4011 is a 300-molecular-weight polypropylene oxide-based triol.

Characte	ristic	data
----------	--------	------

Property	Value	Unit of measurement Method
Hydroxyl number	530 - 570	mg KOH/g
Water	0.10	Wt. %
Acid number	0.20	mg KOH/g
Color APHA	100	
Viscosity at 25°C	1,400 - 1,900	mPa•s

Other data*

Property	Value	Unit of measurement	Method
Appearance	Clear, viscous liquid		
Specific gravity at 25°C	1.02		
Flash point PMCC	180	°C	
Bulk density	8.51	lb/gal	

^{*}These values provide general information and are not part of the product specification.

Properties / Applications

Multranol 4011 is a 300-molecular-weight polypropylene oxide-based triol. It is typically used in the production of solid and microcellular urethane elastomers and rigid foams. As with any product, use of Multranol 4011 polyol in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability.

Storage

Multranol 4011 polyol is slightly hygroscopic and may absorb water. Containers should be kept tightly closed and protected from contamination with moisture and foreign materials, which can adversely affect processing. This product can become quite viscous at low temperatures. For ease of handling, storage temperatures between 15°C (59°F) and 48°C (118°F) are recommended.

Health and Safety Information

Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling this product. Before working with this product, you must read and become familiar with the available information on its risks, proper use, and handling. This cannot be overemphasized. Information is available in several forms, e.g., safety data sheets and product labels. For further





Edition 2007-05-31

Product Datasheet



Multranol[®] 4011

information contact your Covestro LLC representative or the Product Safety and Regulatory Affairs Department in Pittsburgh, PA.

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether our products, technical assistance and information are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent.

Editor: Covestro LLC
1 Covestro Circle
Pittsburgh, Pennsylvania 15205
United States
www.covestro.com

Contact: CAS Single Point of Contact Office Tel. 412-413-3983

page 2 of 2

Document contains important information and must be read in its entirety.



Edition 2007-05-31