Core Sea Bluetooth Scale Cloud Edition Communication Protocol

Communication protocol

1.1 Unlocked data

Service UUID: 0xFFF0

Charateristic UUID: 0xFFF1 notify

Charateristic UUID: 0xFFF2 write

The data format is the same as the 1.2 lock data format

1.2 Locking data

Service UUID: 0x181B

Charateristic UUID: 0x2A9C read,indicate

Byte	definition	Value	Description
0-1	Flags	16bit	
2-3	time	Uint16	year
4		Uint8	Month 1~12
5		Uint8	Day 1~31
6		Uint8	0~23
7		Uint8	0~59
8		Uint8	Seconds 0~59
9-10		Unt16	First electrode resistance, accuracy 0.1
11-12		Unt16	body weight
13-14		Unt16	Second electrode resistance (if any), accuracy 0.1
15		Uint8	Message properties, see Table 1.
16-19		--	Reserved

Eg: weight scale: resistance is 0 flags 0x0002 byte0:02 byte1:00

Eg: body fat scale (one resistor): flags 0x0306 byte0:06 byte1:03

Eg: body fat scale (two resistors): flags 0x2306 byte0:06 byte1:23

Note: When uint16 data is sent, the low bit is first and the high bit is after.

1.3 Historical data

Service UUID: 0x181B

Charateristic UUID: 0xFA9C (custom)

Indicate

The data format is the same as the 1.2 measurement data format. After the FA9C is indicated, the historical data is spit out and the data is spit out.

Between

Increase the time interval from 0 to 200ms.

1.4 Battery power

Service UUID : 0x180F

Charateristic UUID : 0x2A19 read,notify

Consistent with the gatt standard, the power data is 0~100.

1.5 time

Service UUID: 0x1805

Charateristic UUID: 0x2A08 read,write,notify

Byte	Value	Description
0-1	Uint16	year
2	Uint8	Month 1~12
3	Uint8	Day 1~31
4	Uint8	Time 1~31
5	Uint8	0~59
6	Uint8	Seconds 0~59

1.6 OTA

Service UUID: 0xFAA0

Charateristic UUID: 0xFAA1 notify

Charateristic UUID: 0xFAA2 write

1.7 Synchronous APP unit

Ervice UUID: 0xFFF0

Charateristic UUID: 0xFFF2

Byte	Value	Description
0	Uint8	Message type 01: Unit switching
1	Uint8	Unit value: 00:kg 01: LB 02: Jin 03:stb

2. Broadcast package specification

To access the OKOK Bluetooth device, the broadcast package must meet the specifications to access, and the broadcast package contains the manufacturer.

Data, format requirements are as follows:

Byte	Description
0-1	FFF0 (core sea logo)
2	Broadcast version number (current 02)
3	Message properties, see Table 1.
4~5	body weight
6~9	Product ID
10~11	Bluetooth version
12~13	Scale algorithm version
14-19	Mac address

note:

All data is little endian

Table I

Message body	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Attributes	Reserved			Unit selection		Decimal point		Reserved

Bit4-3 unit selection

00 = KG (default)

01 = kg

10 = LB

11 = ST: LB

Bit2-1 decimal number selection

00 = 2 decimal places (default)

01 = 0 decimal place

10 = 1 decimal place

If you keep 1 decimal place, the uploaded weight value is 10 times the actual value. If you keep 2 decimal places, the uploaded weight value is actually 100 times the value, and so on.

Note: 1.ST: LB unit default convention: ST bytes are fixed to integers, and LB bytes are fixed to 1 decimal place. Decimal point at this time

The selection bits represent the decimal places after conversion to other units.

2. Business specifications

If the device takes time, synchronize the time each time the app connects to the device, do not use the device relative time.

The device needs to clear the data after the historical data on the device is read.

When the device broadcasts, the duration is no less than 45 seconds.

When Bluetooth is not connected, the weight is sent in broadcast format; when Bluetooth is connected, the unlocked data is unlocked.

For the data channel, the locked data uses the locked data channel and stops the non-locked data channel transmission.

Some devices (with scales, blood glucose meters, blood pressure monitors), after the panel light is off, at least 60 seconds of connection is required.