COMP 3331/9331: Computer Networks and Applications

Week 5

Transport Layer (Continued)

Reading Guide: Chapter 3, Sections: 3.5

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

Pipelined protocols

3.5 connection-oriented transport: TCP

- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

rdt3.0: channels with errors *and* loss (RECAP)

new assumption: underlying channel can also lose packets (data, ACKs)

- checksum, seq. #, ACKs, retransmissions will be of help … but not enough

approach: sender waits "reasonable" amount of time for ACK

- retransmits if no ACK received in this time
- if pkt (or ACK) just delayed (not lost):
  - retransmission will be duplicate, but seq. #'s already handles this
  - receiver must specify seq # of pkt being ACKed
- requires countdown timer

rdt3.0 in action (RECAP)



(a) no loss



(b) packet loss

rdt3.0 in action (RECAP)



(c) ACK loss



(d) premature timeout/ delayed ACK

rdt3.0: stop-and-wait operation



$$U_{sender} = \frac{L / R}{RTT + L / R}$$

Pipelined protocols

pipelining: sender allows multiple, "in-flight", yet-to-be-acknowledged pkts

- range of sequence numbers must be increased
- buffering at sender and/or receiver



(a) a stop-and-wait protocol in operation (b) a pipelined protocol in operation

- two generic forms of pipelined (sliding window) protocols: *go-Back-N, selective repeat*

Pipelining: increased utilization



3-packet pipelining increases utilization by a factor of 3!

$$U_{sender} = \frac{3L / R}{RTT + L / R}$$

Go-Back-N: sender

- k-bit seq # in pkt header
- "window" of up to N, consecutive unack'ed pkts allowed



- ACK(n): ACKs all pkts up to, including seq # n - *"cumulative ACK"*
  - may receive duplicate ACKs (see receiver)
- timer for oldest in-flight pkt
- *timeout(n):* retransmit packet n and all higher seq # pkts in window

Applets: http://media.pearsoncmg.com/aw/aw_kurose_network_2/applets/go-back-n/go-back-n.html
http://www.ccs-labs.org/teaching/rn/animations/gbn_sr/

GBN: sender extended FSM



GBN: receiver extended FSM



ACK-only: always send ACK for correctly-received pkt with highest *in-order* seq #
- may generate duplicate ACKs
- need only remember **`expectedseqnum`**

❖ out-of-order pkt:
- discard (don't buffer): *no receiver buffering!*
- re-ACK pkt with highest in-order seq #

GBN in action



Selective repeat

- receiver *individually* acknowledges all correctly received pkts
  - buffers pkts, as needed, for eventual in-order delivery to upper layer
- sender only resends pkts for which ACK not received
  - sender timer for each unACKed pkt
- sender window
  - *N* consecutive seq #'s
  - limits seq #s of sent, unACKed pkts

Applet: http://media.pearsoncmg.com/aw/aw_kurose_network_3/applets/SelectRepeat/SR.html

Selective repeat: sender, receiver windows



Selective repeat

sender

data from above:

- if next available seq # in window, send pkt

timeout(n):

- resend pkt n, restart timer

ACK(n) in [sendbase,sendbase+N]:

- mark pkt n as received
- if n smallest unACKed pkt, advance window base to next unACKed seq #

receiver

pkt n in [rcvbase, rcvbase+N-1]

- send ACK(n)
- out-of-order: buffer
- in-order: deliver (also deliver buffered, in-order pkts), advance window to next not-yet-received pkt

pkt n in [rcvbase-N,rcvbase-1]

- ACK(n)

otherwise:

- ignore

Selective repeat in action



Selective repeat: dilemma

example:

- seq #'s: 0, 1, 2, 3
- window size=3
- receiver sees no difference in two scenarios!
- duplicate data accepted as new in (b)

Q: what relationship between seq # size and window size to avoid problem in (b)?



Recap: components of a solution

- Checksums (for error detection)
- Timers (for loss detection)
- Acknowledgments
  - cumulative
  - selective
- Sequence numbers (duplicates, windows)
- Sliding Windows (for efficiency)

- Reliability protocols use the above to decide when and what to retransmit or acknowledge

There are a number of self-check questions and problems on GBN & SR on OpenLearning. Please complete them. This is a rather important topic.

In-class Activity: Past Exam Question

Consider the rdt 3.0 protocol. Draw a timing diagram showing that if the network connection between the sender and receiver can reorder messages (that is, that two messages propagating in the medium between the sender and receiver can be reordered), then the rdt 3.0 protocol will not work correctly (make sure you clearly identify the sense in which it will not work correctly). Your diagram should have the sender on the left and the receiver on the right, with the time axis running down the page, showing data (D) and acknowledgment (A) message exchange. Make sure you indicate the sequence number associated with any data or acknowledgment segment.

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Practical Reliability Questions

- How do the sender and receiver keep track of outstanding pipelined segments?
- How many segments should be pipelined?
- How do we choose sequence numbers?
- What does connection establishment and teardown look like?
- How should we choose timeout values?

TCP: Overview RFCs: 793,1122,1323, 2018, 2581

- point-to-point:
  - one sender, one receiver
- reliable, in-order *byte steam:*
  - no "message boundaries"
- pipelined:
  - TCP congestion and flow control set window size
- send and receive buffers



- full duplex data:
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- connection-oriented:
  - handshaking (exchange of control msgs) inits sender, receiver state before data exchange
- flow controlled:
  - sender will not overwhelm receiver

TCP segment structure



TCP segment structure

20 Bytes

(UDP was 8)



Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Recall: Components of a solution for reliable transport

- Checksums (for error detection)
- Timers (for loss detection)
- Acknowledgments
  - cumulative
  - selective
- Sequence numbers (duplicates, windows)
- Sliding Windows (for efficiency)
  - Go-Back-N (GBN)
  - Selective Replay (SR)

What does TCP do?

Many of our previous ideas, but some key differences

- Checksum

TCP Header



Source port
Destination port
Sequence number
Acknowledgment
HdrLen
0
Flags
Advertised window
Checksum
Urgent pointer
Options (variable)
Data
Computed over header and data

What does TCP do?

Many of our previous ideas, but some key differences

- Checksum
- **Sequence numbers are byte offsets**

TCP "Stream of Bytes" Service ..

Application @ Host A



Application @ Host B

.. Provided Using TCP "Segments"



Segment sent when:

1. Segment full (Max Segment Size),
2. Not full, but times out

TCP Segment Size



- IP packet
  - No bigger than Maximum Transmission Unit (MTU)
  - E.g., up to 1500 bytes with Ethernet
- TCP packet
  - IP packet with a TCP header and data inside
  - TCP header ≥ 20 bytes long
- TCP **segment**
  - No more than Maximum Segment Size (MSS) bytes
  - E.g., up to 1460 consecutive bytes from the stream
  - MSS = MTU – (IP header) – (TCP header)

Sequence Numbers



Sequence & Ack Numbers



What does TCP do?

Most of our previous tricks, but a few differences

- Checksum
- Sequence numbers are byte offsets
- Receiver sends cumulative acknowledgements (like GBN)

ACKing and Sequence Numbers

- Sender sends packet
  - Data starts with sequence number X
  - Packet contains B bytes [X, X+1, X+2, ….X+B-1]

- Upon receipt of packet, receiver sends an ACK
  - If all data prior to X already received:
    - ACK acknowledges X+B (because that is next expected byte)
  - If highest in-order byte received is Y s.t. (Y+1) < X
    - ACK acknowledges Y+1
    - Even if this has been ACKed before

Normal Pattern

- Sender: seqno=X, length=B
- Receiver: ACK=X+B
- Sender: seqno=X+B, length=B
- Receiver: ACK=X+2B
- Sender: seqno=X+2B, length=B

- Seqno of next packet is same as last ACK field

Packet Loss

- Sender: seqno=X, length=B
- Receiver: ACK=X+B
- Sender: ~~seqno=X+B, length=B~~ LOST

- Sender: seqno=X+2B, length=B
- Receiver: ACK = X+B

TCP Header

Acknowledgment gives seqno just beyond highest seqno received **in order**

("What Byte is Next")



TCP seq. numbers, ACKs

sequence numbers:

- byte stream "number" of first byte in segment's data

acknowledgements:

- seq # of next byte expected from other side
- cumulative ACK



Piggybacking

- So far, we've assumed distinct "sender" and "receiver" roles
- In reality, usually both sides of a connection send some data



Without Piggybacking



With Piggybacking

Quiz


Seq = 101, 2 KBytes of data
ACK = ?
Seq = 1024, 1 KByte of data
Seq = ?, 2 KBytes of data
ACK = ?

What does TCP do?

Most of our previous tricks, but a few differences

- Checksum
- Sequence numbers are byte offsets
- Receiver sends cumulative acknowledgements (like GBN)
- Receivers can buffer out-of-sequence packets (like SR)

Loss with cumulative ACKs

- Sender sends packets with 100Bytes and sequence numbers:
  - 100, 200, 300, 400, 500, 600, 700, 800, 900, …
- Assume the fifth packet (seq. no. 500) is lost, but no others
- Stream of ACKs will be:
  - 200, 300, 400, 500, 500, 500, 500,…

What does TCP do?

Most of our previous tricks, but a few differences

- Checksum
- Sequence numbers are byte offsets
- Receiver sends cumulative acknowledgements (like GBN)
- Receivers do not drop out-of-sequence packets (like SR)
- Sender maintains a single retransmission timer (like GBN) and retransmits on timeout

TCP round trip time, timeout

Q: how to set TCP timeout value?

- longer than RTT
  - but RTT varies
- *too short:* premature timeout, unnecessary retransmissions
- *too long:* slow reaction to segment loss and connection has lower throughput

Q: how to estimate RTT?

- **`SampleRTT`**: measured time from segment transmission until ACK receipt
  - ignore retransmissions
- **`SampleRTT`** will vary, want estimated RTT "smoother"
  - average several *recent* measurements, not just current **`SampleRTT`**

TCP round trip time, timeout

EstimatedRTT = (1- α)*EstimatedRTT + α*SampleRTT

- exponential weighted moving average
- influence of past sample decreases exponentially fast
- typical value: α = 0.125



TCP round trip time, timeout

- timeout interval: **`EstimatedRTT`** plus "safety margin"
  - large variation in **`EstimatedRTT`** -> larger safety margin
- estimate SampleRTT deviation from EstimatedRTT:

```
DevRTT = (1-β)*DevRTT +
              β*|SampleRTT-EstimatedRTT|

              (typically, β = 0.25)
```

```
TimeoutInterval = EstimatedRTT + 4*DevRTT
```

estimated RTT (EstimatedRTT) — "safety margin" (4*DevRTT)

Practice Problem:
http://wps.pearsoned.com/ecs_kurose_compnetw_6/216/55463/14198700.cw/index.html

Why exclude retransmissions in RTT computation?

- How do we differentiate between the real ACK, and ACK of the retransmitted packet?



TCP sender events:

PUTTING IT TOGETHER

data rcvd from app:

- create segment with seq #
- seq # is byte-stream number of first data byte in segment
- start timer if not already running
  - think of timer as for oldest unacked segment
  - expiration interval: `TimeOutInterval`

timeout:

- retransmit segment that caused timeout
- restart timer

ack rcvd:

- if ack acknowledges previously unacked segments
  - update what is known to be ACKed
  - start timer if there are still unacked segments

TCP sender (simplified)

PUTTING IT TOGETHER



Λ
____
NextSeqNum = InitialSeqNum
SendBase = InitialSeqNum

data received from application above
____
create segment, seq. #: NextSeqNum
pass segment to IP (i.e., "send")
NextSeqNum = NextSeqNum + length(data)
if (timer currently not running)
    start timer

timeout
____
retransmit not-yet-acked segment
    with smallest seq. #
start timer

ACK received, with ACK field value y
____

```
if (y > SendBase) {
   SendBase = y
   /* SendBase–1: last cumulatively ACKed byte */
   if (there are currently not-yet-acked segments)
       start timer
     else stop timer
 }
```

TCP: retransmission scenarios



lost ACK scenario



premature timeout

TCP: retransmission scenarios



cumulative ACK

TCP ACK generation [RFC 1122, RFC 2581]

event at receiver	*TCP receiver action*
arrival of in-order segment with expected seq #. All data up to expected seq # already ACKed	delayed ACK. Wait up to 500ms for next segment. If no next segment, send ACK
arrival of in-order segment with expected seq #. One other segment has ACK pending	immediately send single cumulative ACK, ACKing both in-order segments
arrival of out-of-order segment higher-than-expect seq. # . Gap detected	immediately send *duplicate ACK,* indicating seq. # of next expected byte
arrival of segment that partially or completely fills gap	immediate send ACK, provided that segment starts at lower end of gap

What does TCP do?

Most of our previous tricks, but a few differences

- Checksum
- Sequence numbers are byte offsets
- Receiver sends cumulative acknowledgements (like GBN)
- Receivers may not drop out-of-sequence packets (like SR)
- Sender maintains a single retransmission timer (like GBN) and retransmits on timeout
- Introduces fast retransmit: optimisation that uses duplicate ACKs to trigger early retransmission

Quiz

Suppose host A sends two TCP segments back to back to Host B over a TCP connection. The first segment has sequence number 90; the second has sequence number 110.

- Q1: How much data is in the first segment ?

- Q2: Suppose that the first segment is lost but not that the second segment arrives at B. In the acknowledgement that Host B sends to Host A, what will be the acknowledgement number?

TCP fast retransmit

- time-out period often relatively long:
  - long delay before resending lost packet
- "Duplicate ACKs" are a sign of an <u>isolated</u> loss
  - The lack of ACK progress means that packet hasn't been delivered
  - Stream of ACKs means some packets are being delivered
  - Could trigger resend on receiving "k" duplicate ACKs (TCP uses k = 3)

TCP fast retransmit

if sender receives 3 duplicate ACKs for same data

("triple duplicate ACKs"), resend unacked segment with smallest seq #

- likely that unacked segment is lost, so don't wait for timeout

TCP fast retransmit



fast retransmit after sender receipt of triple duplicate ACK

What does TCP do?

Most of our previous ideas, but some key differences

- Checksum
- Sequence numbers are byte offsets
- Receiver sends cumulative acknowledgements (like GBN)
- Receivers do not drop out-of-sequence packets (like SR)
- Sender maintains a single retransmission timer (like GBN) and retransmits on timeout
- Introduces fast retransmit: optimization that uses duplicate ACKs to trigger early retransmission

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

TCP flow control



receiver protocol stack

flow control

receiver controls sender, so sender won't overflow receiver's buffer by transmitting too much, too fast

TCP flow control

- receiver "advertises" free buffer space by including **rwnd** value in TCP header of receiver-to-sender segments
  - **RcvBuffer** size set via socket options (typical default is 4096 bytes)
  - many operating systems autoadjust **RcvBuffer**
- sender limits amount of unacked ("in-flight") data to receiver's **rwnd** value
- guarantees receive buffer will not overflow



receiver-side buffering

http://media.pearsoncmg.com/aw/aw_kurose_network_4/applets/flow/FlowControl.htm

Transport Layer Outline

3.1 transport-layer services

3.2 multiplexing and demultiplexing

3.3 connectionless transport: UDP

3.4 principles of reliable data transfer

3.5 connection-oriented transport: TCP
- segment structure
- reliable data transfer
- flow control
- connection management

3.6 principles of congestion control

3.7 TCP congestion control

Connection Management

before exchanging data, sender/receiver "handshake":

- agree to establish connection (each knowing the other willing to establish connection)
- agree on connection parameters




```
Socket clientSocket =
  newSocket("hostname","port
   number");
```

```
Socket connectionSocket =
   welcomeSocket.accept();
```

Initial Sequence Number (ISN)

- Sequence number for the very first byte
- Why not just use ISN = 0?
- Practical issue
  - IP addresses and port #s uniquely identify a connection
  - Eventually, though, these port #s do get used again
  - … small chance an old packet is still in flight
  - Easy to hijack a TCP connection (security threat)
- TCP therefore requires changing ISN
- Hosts exchange ISNs when they establish a connection

Agreeing to establish a connection

2-way handshake:





Q: will 2-way handshake always work in network?

- variable delays
- retransmitted messages (e.g. req_conn(x)) due to message loss
- message reordering
- can't "see" other side

Agreeing to establish a connection

2-way handshake failure scenarios:



TCP 3-way handshake



Step 1: A's Initial SYN Packet



A tells B it wants to open a connection…

Step 2: B's SYN-ACK Packet



B tells A it accepts, and is ready to hear the next byte…

… upon receiving this packet, A can start sending data

Step 3: A's ACK of the SYN-ACK



A tells B it's likewise okay to start sending

… upon receiving this packet, B can start sending data

TCP 3-way handshake: FSM



What if the SYN Packet Gets Lost?

- Suppose the SYN packet gets lost
  - Packet is lost inside the network, or:
  - Server discards the packet (e.g., it's too busy)
- Eventually, no SYN-ACK arrives
  - Sender sets a timer and waits for the SYN-ACK
  - … and retransmits the SYN if needed
- How should the TCP sender set the timer?
  - Sender has no idea how far away the receiver is
  - Hard to guess a reasonable length of time to wait
  - **SHOULD** (RFCs 1122 & 2988) use default of 3 seconds
    - Some implementations instead use 6 seconds

SYN Loss and Web Downloads

- User clicks on a hypertext link
  - Browser creates a socket and does a "connect"
  - The "connect" triggers the OS to transmit a SYN
- If the SYN is lost…
  - 3-6 seconds of delay: can be very long
  - User may become impatient
  - … and click the hyperlink again, or click "reload"
- User triggers an "abort" of the "connect"
  - Browser creates a new socket and another "connect"
  - Essentially, forces a faster send of a new SYN packet!
  - Sometimes very effective, and the page comes quickly

TCP: closing a connection

- client, server each close their side of connection
  - send TCP segment with FIN bit = 1
- respond to received FIN with ACK
  - on receiving FIN, ACK can be combined with own FIN
- simultaneous FIN exchanges can be handled

Normal Termination, One at a Time



TIMED_WAIT: Can retransmit ACK if ACK is lost

Normal Termination, Both Together



Abrupt Termination



- A sends a RESET (**RST**) to B
  - E.g., because application process on A crashed
- That's it
  - B does not ack the **RST**
  - Thus, **RST** is not delivered reliably
  - And: any data in flight is lost
  - But: if B sends anything more, will elicit another **RST**

TCP Finite State Machine



TCP Connection Management (cont)



TCP client
lifecycle

TCP server
lifecycle



Quiz

Assume there is no documentation of the TCP finite state machine, so there's no supporting textual description which defines other state transitions



Suppose we start in the CLOSED state, then call listen, then receive a SYN, then call close. What state will we be in:

(a) CLOSED
(b) SYN SENT
(c) SYN RECEIVED
(d) ESTABLISHED
(e) Undefined state

TCP SYN Attack (SYN flooding)

- Miscreant creates a fake SYN packet
  - Destination is IP address of victim host (usually some server)
  - Source is some spoofed IP address
- Victim host on receiving creates a TCP connection state i.e allocates buffers, creates variables, etc and sends SYN ACK to the spoofed address (half-open connection)
- ACK never comes back
- After a timeout connection state is freed
- However for this duration the connection state is unnecessarily created
- Further miscreant sends large number of fake SYNs
  - Can easily overwhelm the victim
- Solutions:
  - Increase size of connection queue
  - Decrease timeout wait for the 3-way handshake
  - Firewalls: list of known bad source IP addresses
  - TCP SYN Cookies (explained on next slide)

TCP SYN Cookie

- On receipt of SYN, server does not create connection state
- It creates an initial sequence number (*init_seq*) that is a hash of source & dest IP address and port number of SYN packet (secret key used for hash)
  - Replies back with SYN ACK containing *init_seq*
  - Server does not need to store this sequence number
- If original SYN is genuine, an ACK will come back
  - Same hash function run on the same header fields to get the initial sequence number (*init_seq*)
  - Checks if the ACK is equal to (*init_seq*+1)
  - Only create connection state if above is true
- If fake SYN, no harm done since no state was created

http://etherealmind.com/tcp-syn-cookies-ddos-defence/

Transport: summary (so far)

- principles behind transport layer services:
  - multiplexing, demultiplexing
  - reliable data transfer
  - flow control
  - **congestion control (next week)**
- instantiation, implementation in the Internet
  - UDP
  - TCP

next:

- leaving the network "edge" (application, transport layers)
- into the network "core"