

PRELIMINARY PROPOSAL - NOT AS-BUILT

Motor model	OrbiDrive OD-96M-4
Motor rating	96 kW at 1468 rpm
Gearbox model	TransAxis TA-92-22.10
Gearbox ratio	22.10:1
Agitator shaft diameter	108 mm
Coupling	GridFlex GF-260
Coupling spacer	174 mm
Lubricant	Mineral EP ISO VG 150
Shaft seal	Double lip seal with grease barrier

This preliminary schedule predates the 2026 gearbox, coupling, bearing, seal, and lubricant service.

PRELIMINARY PROPOSAL - NOT AS-BUILT

Motor-bearing vibration	6.8 mm/s RMS maximum	Generic vendor screening value
Gearbox bearing temperature rise	38 C maximum	Generic vendor screening value
Coupling guard clearance	9 mm minimum	Preliminary arrangement
Gearbox oil water	900 ppm maximum	Preliminary mineral-oil context
Alignment offset	0.12 mm maximum	Preliminary installation value
Soft foot	0.07 mm maximum	Preliminary installation value

These screening values are not current AG-512B installed-condition acceptance criteria.

Preliminary Fastener and Seal Options

PRELIMINARY PROPOSAL - NOT AS-BUILT

Option	Description	Preliminary value
A	Coupling bolt M20 grade 8.8	485 N*m
B	Guard fastener M8 zinc-plated	28 N*m
C	Double lip seal NBR	108 mm shaft

Lower-half table obscured by diagonal fold damage, toner loss, and handwritten overwriting.