

☐ Translate Text

OK

Cancel

Default

1:1 Mapping

Emulation - Text Attributes...

Text Attributes:

Plain

Style

Black

ANSI Black

Bold

Style

Magenta

ANSI Magenta

Blank/Dim

Style

Cyan

ANSI Cyan

Underline

Style

Red

ANSI Red

Blink

Style

Green

ANSI Green

Reverse

Style

Blue

ANSI Blue

Background Color:

Black

White

☐ HiLite Color Cursor

☐ ANSI Color/Graphics

Text Character Sets:

Set:

☒ 60

☐ 61

☐ 62

☐ 63

Font:

☒ ASCII

☐ DEC

☐ Other

☐ Soft

Text Font Size:

☐ 6

☐ 9

☒ 12

☐ 15

☐ 18

OK

Cancel

Defaults

Settings - Kermit Options...

Kermit Options:

Start of Packet Char

End of Packet Char

Pad Char

Padding

Timeout (seconds)

Packet Length

Receive

Send

^A

^M

^@

00

14

2048

^A

^M

^@

00

20

2048

Transfer Mode:

File Fork:

Handshake:

☒ Text

☐ Binary

☐ MacBinary

☒ Data

☐ Resource

☐ None

☐ ^Q

Block Check Type:

Options:

☒ 1 - 6 bit/sum

☐ 2 - 12 bit/sum

☐ 3 - 16 bit/CRC

☒ Use Long Packets

☒ Use Compression

☐ Use Server Mode

☒ Always Quote Binary

☐ Literal Filenames

OK

Cancel

Settings - Config

Connection Settings

Method:

Serial Tool

Port Settings

Baud Rate:

9600

Parity:

None

Data Bits:

8

Stop Bits:

1

Handshake:

None

Current Port

Modem Port

Printer Port

When Closing Document

☐ Hold Connection

☐ Remind to Disconnect

OK

Cancel