

[https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc753551\(v=ws.10\)?redirectedfrom=MSDN](https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc753551(v=ws.10)?redirectedfrom=MSDN)

# Forfiles

04/18/2012 • 3 minutes to read

## In this article

[Syntax](#)

[Parameters](#)

[Remarks](#)

[Examples](#)

[Additional references](#)

Applies To: Windows Server 2008, Windows Vista

Selects and executes a command on a file or set of files. This command is useful for batch processing.

For examples of how to use this command, see Examples.

## Syntax



```
forfiles [/p <Path>] [/m <SearchMask>] [/s] [/c "<Command>"] [/d [{+|-}][{<Date>|<Days>}]]
```

## Parameters

**Parameter**

**Description**

Parameter	Description
/p <Path>	Specifies the path from which to start the search. By default, searching starts in the current working directory.
/m <SearchMask>	Searches files according to the specified search mask. The default search mask is *.*.
/s	Instructs the <b>forfiles</b> command to search into subdirectories recursively.
/c "<Command>"	Runs the specified command on each file. Command strings should be enclosed in quotation marks. The default command is " <b>cmd /c echo @file</b> ".
/d [{+ -}][<Date> <Days>]	Selects files with a last modified date within the specified time frame. <ul style="list-style-type: none"><li>• Selects files with a last modified date later than or equal to (+) or earlier than or equal to (-) the specified date, where <i>Date</i> is in the format MM/DD/YYYY.</li><li>• Selects files with a last modified date later than or equal to (+) the current date plus the number of days specified, or earlier than or equal to (-) the current date minus the number of days specified.</li><li>• Valid values for <i>Days</i> include any number in the range 0–32,768. If no sign is specified, + is used by default.</li></ul>
/?	Displays help at the command prompt.

## Remarks

- **Forfiles** is most commonly used in batch files.
- **Forfiles /s** is similar to **dir /s**.

- You can use the following variables in the command string as specified by the **/c** command-line option.


Variable	Description
@FILE	File name.
@FNAME	File name without extension.
@EXT	File name extension.
@PATH	Full path of the file.
@RELPATH	Relative path of the file.
@ISDIR	Evaluates to TRUE if a file type is a directory. Otherwise, this variable evaluates to FALSE.
@FSIZE	File size, in bytes.
@FDATE	Last modified date stamp on the file.
@FTIME	Last modified time stamp on the file.

- With **forfiles**, you can run a command on or pass arguments to multiple files. For example, you could run the **type** command on all files in a tree with the .txt file name extension. Or you could execute every batch file (\*.bat) on drive C, with the file name "Myinput.txt" as the first argument.
- With **forfiles**, you can do any of the following:
  - Select files by an absolute date or a relative date by using the **/d** parameter.
  - Build an archive tree of files by using variables such as @FSIZEand @FDATE.


- Differentiate files from directories by using the @ISDIRvariable.
- Include special characters in the command line by using the hexadecimal code for the character, in 0xHH format (for example, 0x09 for a tab).
- **Forfiles** works by implementing the **recurse subdirectories** flag on tools that are designed to process only a single file.

## Examples


To list all of the batch files on drive C, type:

	 Copy
<pre>forfiles /p c:\ /s /m *.bat /c "cmd /c echo @file is a batch file"</pre>	

To list all of the directories on drive C, type:

	 Copy
<pre>forfiles /p c:\ /s /m *.* /c "cmd /c if @isdir==true echo @file is a directory"</pre>	

To list all of the files in the current directory that are at least one year old, type:

	 Copy
<pre>forfiles /s /m *.* /d -365 /c "cmd /c echo @file is at least one year old."</pre>	

To display the text "*File is outdated*" for each of the files in the current directory that are older than January 1, 2007, type:



```
forfiles /s /m *.* /d -01/01/2007 /c "cmd /c echo @file is outdated."
```

To list the file name extensions of all the files in the current directory in column format, and add a tab before the extension, type:



```
forfiles /s /m *.* /c "cmd /c echo The extension of @file is 0x09@ext"
```

## Additional references

[Command-Line Syntax Key](#)