API DOCUMENT

PROJECT: Biller Integration API Guide

Version 1.0

Date: 27-Feb-2025

Author: Paul Kimani, Win Kimathi

Reviewer: John Kagwima

HEAD OFFICE
Equity Centre,
Hospital Road, Upper Hill.
Address: P.O. Box 75104-00200,
Nairobi, Kenya
Email: info@equitybank.co.ke
Website: www.equitybank.co.ke



1. Authentication **2**
JWT Authentication 2
How it works step by step: 2
2. Biller Validation **3**
Request 3
Headers 3
Request Parameters 3
Example Request 4
Response Parameters 4
Response 5
3. Biller Notification **5**
Request 5
Headers 5
Request Parameters 6
Example Request 6
Response 7
Response Parameters 7
Example Success Response 7
Example Failure Response 7

1. **Authentication**

JWT Authentication

How it works step by step:

1. User requests a token:

- The client (user, mobile app, or frontend) sends their **username and password** to the server.
- This usually happens via a **login endpoint** (like /api/token/).

2. Server verifies credentials:

- The server checks if the credentials are correct by validating them against the user database.
- If valid, the server generates two tokens:
- **Access Token:** short-lived, used for authentication in every request.
- **Refresh Token:** long-lived, used to get a new access token without re-logging in.

3. Server responds with tokens:

- The server returns a **response** containing both tokens:

```
{
  "access": "your-access-token",
  "refresh": "your-refresh-token"
}
```

4. Client uses the access token (Bearer token):

- For every **subsequent API request** to a protected route, the client includes the access token in the Authorization header as per the sample below.

Sample

POST /notification

Authorization: Bearer <your-token>

2. Biller Validation

This API is used to validate a customer identifier(invoice/BillNumber/BillRef/CustomerCode) on the system i.e ERP.

Request

HTTP Version	HTTP/1.1
API TYPE	REST
HTTP Method	POST
End-Point	To be shared with Equity by the customer or their solution provider(vendor)

Headers

Key	Required	Value	Description
Content-Type	Yes	application/json	Content-Type

Request Parameters

Parameter	Data-Type	Required	Description
billNumber	String	Yes	Biller Reference.
amount	String	**NB: If not available set to zero(0). This might be mandatory for**	Transaction amount.

		some billers, especially for invoice based payments.	

Example Request

POST /validation HTTP/1.1

Content-Type: application/json

```
{
  "billNumber": "123456",
//invoice/BillNumber/BillRef/CustomerCode->Customer identifier on third party or ERP system
  "amount": "10" //This field is optional
}
```

Response Parameters

Parameter	Data-Type	Mandatory	Description
billNumber	String	Yes	Bill reference number
customerName	String	Yes	Customer name
amount	String	No	billAmount
description	string	Yes	Validation response description

Response

```
{
  "customerName": "Jane Josh", //Customer Name as maintained on ERP
  "billNumber": "123456",
//Invoice/BillNumber/BillRef/CustomerCode->Return this value only when validation is successful
  "amount": "10", // Due amount->For invoice based return the invoice, Default amount is 0
  "description": "Success" //Response description
}
```

3. Biller Notification

This API is used to send a notification request to the customer system i.e ERP.

Request

HTTP Version	HTTP/1.1
API TYPE	REST
HTTP Method	POST
End-Point	To be shared with Equity by the customer or their solution provider(vendor)

Headers

Key	Required	Value	Description
Content-Type	Yes	application/json	Content-Type

Request Parameters

Parameter	Data-Type	Required	Description
billNumber	String	Yes	Bill reference number
amount	String	Yes	Bill Amount
bankReference	String	Yes	Transaction ID from Equity
transactionDate	String	Yes	Date of the transaction

Example Request

POST /notification HTTP/1.1

Content-Type: application/json

```
{
  "billNumber": "123456",
//Invoice/BillNumber/BillRef/CustomerCode->Customer identifier on third party or ERP system
  "amount": "10", //This field is mandatory
  "bankReference": "EQB293293829", //Transaction Id from Equity
  "transactionDate": "2025-01-09 12:23:23" //Transaction Date
}
```

Response

HTTP Version	HTTP/1.1
HTTP Response Code	200

Response Parameters

Parameter	**Data-Type**	**Mandatory**	**Description**
responseCode	String	Yes	Response code(200)
responseMessage	String	Yes	description(Success)

Example Success Response

POST /notification HTTP/1.1

Content-Type: application/json

```
{
  "responseCode": "200", //Response Code(You can opt to use http codes)
  "responseMessage": "Success" //Response Message
}
```

Example Failure Response

POST /notification HTTP/1.1

Content-Type: application/json

```
{
  "responseCode": "400", //Response Code(You can opt to use http codes)
  "responseMessage": "Duplicate transaction" //Response Message
}
```