



TECHNICAL SPECIFICATION

PARAMETER	SPECIFICATION
MODEL NAME	NITROJET 1000 LCV
POWER SUPPLY	110 - 240VAC AT 50HZ
SYSTEM	MICRO - CONTROLLER BASED
OPERATION	AUTO SENSING SYSTEM
INLET PRESSURE RANGE	90 - 180 PSI
NITROGEN PURITY	95 - 99 %
WORKING PRESSURE	0 - 100 PSI
DISPLAY	2 X 1" LCD WITH BACK LIGHT
DISPLAY RESOLUTION	1.0 PSI
ACCURACY	± 1 PSI / 0.07 BAR
MEASURING RESOLUTION	0.1 PSI
INDICATIONS	LED , DISPLAY AND BUZZER
SWITCHES	MEMBRANE KEYS
POWER CONSUMPTION	45 VA
OUTPUT HOSE	10 METER PU SPIRAL
DIMENSIONS(LxWxH)IN MM	(550x590x1400)
FILTER	MOISTURE / OIL REMOVAL
APPLICATION	TWO WHEELERS, CARS, SUV

NITROJET 1000 LCV (H)

WHY USE NITROGEN IN TYRES?

- SAVES MONEY & ENVIRONMENT
- INCREASED FUEL MILEAGE
- INCREASED TREAD LIFE
- TYRE RUNS COOLER
- HELPS PREVENT UNEVEN WEAR & TEAR
- VERY LESS PRESSURE LOSS
- REDUCED WHEEL CORROSION
- NO NEED TO CHECK PRESSURE FREQUENTLY
- NO RUST FORMATION

*The above mentioned specifications are subjected to change without prior notice

MANUFACTURED BY:

ICON EMBEDDED CONTROLS

374/2, JOTHINAGAR 2ND STREET,
RAMANUJAM NAGAR EXTN,
UPPILIPALAYAM POST,
COIMBATORE, TAMILNADU - 641015
PHONE: 0422 -2596032
E-MAIL : INFO@ICONEMBEDDEDCONTROLS.COM
WEBSITE: WWW.ICONEMBEDDEDCONTROLS.COM

MARKETED AND SERVICED BY:

