



DIGITAL NITROGEN TYRE INFLATOR WITH FOUR HOSE PLUS SYSTEM

SALIENT FEATURES

- CAN INFLATE FROM 1 TO 5 TYRES SIMULTANEOUSLY
- EASY SWITCHING FOR AIR OR NITROGEN SELECTION
- BALL VALVE PROTECTION FOR EACH OUTPUT HOSE
- 10 METER SPIRAL HOSE CAN BE USED FOR REGULAR SINGLE TYRE MODE
- DOUBLE TIME FASTER THAN SINGLE HOSE MODEL



TECHNICAL SPECIFICATION

PARAMETER	SPECIFICATION
MODEL NAME	NITROJET 6000 LCV 4H
POWER SUPPLY	110 - 240VAC AT 50HZ
SYSTEM	MICRO - CONTROLLER BASED
OPERATION	AUTO SENSING SYSTEM
INLET PRESSURE RANGE	90 - 180 PSI
NITROGEN PURITY	95 - 99 %
WORKING PRESSURE	0 - 100 PSI
DISPLAY	2 X 1" LCD WITH BACK LIGHT
DISPLAY RESOLUTION	1.0 PSI
ACCURACY	± 1 PSI / 0.07 BAR
MEASURING RESOLUTION	0.1 PSI
INDICATIONS	LED , DISPLAY AND BUZZER
SWITCHES	MEMBRANE KEYS
POWER CONSUMPTION	45 VA
OUTPUT HOSE	4 X 8 METER BRAIDED HOSE
DIMENSIONS(LxWxH)IN MM	(450x680x1400)
FILTER	MOISTURE / OIL REMOVAL
APPLICATION	TWO WHEELERS, CARS, SUV

WHY USE NITROGEN IN TYRES?

- SAVES MONEY & ENVIRONMENT
- INCREASED FUEL MILEAGE
- INCREASED TREAD LIFE
- TYRE RUNS COOLER
- HELPS PREVENT UNEVEN WEAR & TEAR
- VERY LESS PRESSURE LOSS
- REDUCED WHEEL CORROSION
- NO NEED TO CHECK PRESSURE FREQUENTLY
- NO RUST FORMATION

*The above mentioned specifications are subjected to change without prior notice

MANUFACTURED BY:
ICON EMBEDDED CONTROLS
374/2, JOTHINAGAR 2ND STREET,
RAMANUJAM NAGAR EXTN,
UPPILIPALAYAM POST,
GOIMBATORE, TAMILNADU - 641015

CONTACT DETAILS:

PHONE : +91422-2596032
MOBILE : +91-9751456032

E-MAIL : info@iconembeddedcontrols.com
WEBSITE: www.iconembeddedcontrols.com