Configuring a corporate proxy

When JHipster is used in a company, you probably will need to configure all tools to bypass the corporate proxy.

You can try to configure the HTTP_PROXY and HTTPS_PROXY environment variables or use a tool like Cntlm (http://cntlm.sourceforge.net/).

But this probably won't be enough, so you will need to configure separately all the tools that are used with JHipster.

Introduction

Supposing your proxy is defined with:

- username
- password
- host
- nort

The resulting configuration is: http://username:password@host:port

If your use Cntlm (http://cntlm.sourceforge.net/), then your configuration would be: 127.0.0.1:3128. Otherwise, follow the next steps to configure each tool individually.

Yarn configuration

Use these commands:

```
yarn config set proxy http://username:password@host:port
yarn config set https-proxy http://username:password@host:port
```

NPM configuration

Use these commands:

```
npm config set proxy http://username:password@host:port
npm config set https-proxy http://username:password@host:port
```

Or you can edit directly your ~/.npmrc file:

```
proxy=http://username:password@host:port
https-proxy=http://username:password@host:port
https_proxy=http://username:password@host:port
```

Git configuration

Use these commands:

```
git config --global http.proxy http://username:password@host:port
git config --global https.proxy http://username:password@host:port
```

Or you can edit directly your ~/.gitconfig file:

```
[http]
     proxy = http://username:password@host:port
[https]
     proxy = http://username:password@host:port
```

Bower configuration

Edit your ~/.bowerrc file:

```
{
    "proxy":"http://username:password@host:port",
    "https-proxy":"http://username:password@host:port"
}
```

Maven configuration

Edit the proxies session in your ~/.m2/settings.xml file



Maven Wrapper

Create a new file .mvn/jvm.config inside the project folder and set the properties accordingly:

```
-Dhttp.proxyHost=host
-Dhttp.proxyHost=host
-Dhttps.proxyHost=host
-Dhttps.proxyPort=port
-Dhttp.proxyUser=username
-Dhttp.proxyPassword=password
```

Gradle configuration

Add the below in your gradle.properties file and in your gradle/wrapper/gradle-wrapper.properties file if you are downloading the wrapper over a proxy

If you want to set these properties globally then add it in USER_HOME/.gradle/gradle.properties file

```
## Proxy setup
systemProp.proxySet="true"
systemProp.http.keepAlive="true"
systemProp.http.proxyHost=host
systemProp.http.proxyPort=port
systemProp.http.proxyUser=username
systemProp.http.nonProxyHosts=local.net|some.host.com

systemProp.https.keepAlive="true"
systemProp.https.proxyHost=host
systemProp.https.proxyHost=host
systemProp.https.proxyUser=username
systemProp.https.proxyUser=username
systemProp.https.proxyUser=username
systemProp.https.proxyHosts=local.net|some.host.com
## end of proxy setup
```

Docker

Native Docker

Depending on your OS, you have to edit a specific file (/etc/sysconfig/docker Or /etc/default/docker).

Then, you have to restart the docker service with: sudo service docker restart.

It will not apply to systemd. See this page from docker (https://docs.docker.com/engine/admin/systemd/#http-proxy) to configure the proxy.

Docker with docker-machine

You can create your docker-machine with:

```
docker-machine create -d virtualbox \
    --engine-env HTTP_PROXY=http://username:password@host:port \
    --engine-env HTTPS_PROXY=http://username:password@host:port \
    default
```

- Team (http://www.jhipster.tech/team/)
- Artwork (http://www.jhipster.tech/artwork)
- ♣ Policies (http://www.jhipster.tech/policies/)
- Thanks (http://www.jhipster.tech/thanks/)
- Meetups (http://www.jhipster.tech/meetups/)
- Archives (http://www.jhipster.tech/documentation-archive/)



()	

(https://dpittpusb/./cpitte/jhirp/steip/stein/egenterator-

(https://jtwipitste.mjbiposjtævaa_hipster)

Custom	n s	Search

Copyright © JHipster 2016 | Theme based on Freelancer (https://github.com/IronSummitMedia/startbootstrap-freelancer) and Flat admin (https://github.com/tui2tone/flat-admin-bootstrap-templates)