

LabRoboticsProject

Generated by Doxygen 1.8.14

Contents

1	Class Index	1
1.1	Class List	1
2	File Index	3
2.1	File List	3
3	Class Documentation	5
3.1	Settings Class Reference	5
3.1.1	Member Enumeration Documentation	7
3.1.1.1	InputType	7
3.1.1.2	Pattern	7
3.1.2	Constructor & Destructor Documentation	7
3.1.2.1	Settings()	7
3.1.3	Member Function Documentation	7
3.1.3.1	isListOfImages()	7
3.1.3.2	nextImage()	8
3.1.3.3	read()	8
3.1.3.4	readStringList()	8
3.1.3.5	validate()	9
3.1.3.6	write()	9
3.1.4	Member Data Documentation	10
3.1.4.1	aspectRatio	10
3.1.4.2	atImageList	10
3.1.4.3	boardSize	10

3.1.4.4	calibFixPrincipalPoint	10
3.1.4.5	calibrationPattern	10
3.1.4.6	calibZeroTangentDist	11
3.1.4.7	cameraID	11
3.1.4.8	delay	11
3.1.4.9	fixK1	11
3.1.4.10	fixK2	11
3.1.4.11	fixK3	11
3.1.4.12	fixK4	12
3.1.4.13	fixK5	12
3.1.4.14	flag	12
3.1.4.15	flipVertical	12
3.1.4.16	goodInput	12
3.1.4.17	imageList	12
3.1.4.18	input	12
3.1.4.19	inputCapture	13
3.1.4.20	inputType	13
3.1.4.21	nrFrames	13
3.1.4.22	outputFileName	13
3.1.4.23	showUndistorsed	13
3.1.4.24	squareSize	13
3.1.4.25	useFisheye	14
3.1.4.26	writeExtrinsics	14
3.1.4.27	writePoints	14

4	File Documentation	15
4.1	src/calibration.cc File Reference	15
4.1.1	Function Documentation	16
4.1.1.1	calcBoardCornerPositions()	16
4.1.1.2	calibration()	16
4.1.1.3	computeReprojectionErrors()	16
4.1.1.4	read()	17
4.1.1.5	runCalibration()	17
4.1.1.6	runCalibrationAndSave()	18
4.1.1.7	saveCameraParams()	19
4.2	src/calibration.hh File Reference	19
4.2.1	Detailed Description	20
4.2.2	Enumeration Type Documentation	20
4.2.2.1	anonymous enum	20
4.2.3	Function Documentation	21
4.2.3.1	calibration()	21
4.2.3.2	runCalibrationAndSave()	21
4.3	src/calibration_run.cc File Reference	22
4.3.1	Function Documentation	22
4.3.1.1	main()	22
4.4	src/create_xml.cc File Reference	22
4.4.1	Function Documentation	23
4.4.1.1	main()	23
4.5	src/detection.cc File Reference	23
4.5.1	Macro Definition Documentation	24
4.5.1.1	WAIT	24
4.5.2	Function Documentation	24
4.5.2.1	crop_number_section()	24
4.5.2.2	detection()	24
4.5.2.3	erode_dilation()	25

4.5.2.4	find_contours()	25
4.5.2.5	load_number_template()	25
4.5.2.6	number_recognition()	26
4.5.2.7	save_convex_hull()	26
4.5.2.8	shape_detection()	26
4.5.3	Variable Documentation	27
4.5.3.1	fs_xml	27
4.5.3.2	templates	27
4.5.3.3	xml_settings	27
4.6	src/detection.hh File Reference	27
4.6.1	Function Documentation	28
4.6.1.1	crop_number_section()	28
4.6.1.2	detection()	29
4.6.1.3	erode_dilation()	29
4.6.1.4	find_contours()	29
4.6.1.5	load_number_template()	30
4.6.1.6	number_recognition()	30
4.6.1.7	save_convex_hull()	30
4.6.1.8	shape_detection()	31
4.7	src/detection_run.cc File Reference	31
4.7.1	Function Documentation	31
4.7.1.1	main()	31
4.8	src/main.cc File Reference	32
4.8.1	Function Documentation	32
4.8.1.1	main()	32
4.9	src/unwrapping.cc File Reference	32
4.9.1	Macro Definition Documentation	33
4.9.1.1	area_ratio	33
4.9.1.2	WAIT	33
4.9.2	Function Documentation	33

4.9.2.1	distance()	33
4.9.2.2	loadCoefficients()	34
4.9.2.3	swap()	34
4.9.2.4	unwrapping()	34
4.9.3	Variable Documentation	35
4.9.3.1	xml_settings	35
4.10	src/unwrapping.hh File Reference	35
4.10.1	Function Documentation	36
4.10.1.1	loadCoefficients()	36
4.10.1.2	unwrapping()	36
4.11	src/unwrapping_run.cc File Reference	37
4.11.1	Function Documentation	37
4.11.1.1	main()	37
4.12	src/utls.cc File Reference	37
4.12.1	Function Documentation	37
4.12.1.1	my_imshow()	38
4.13	src/utls.hh File Reference	38
4.13.1	Macro Definition Documentation	38
4.13.1.1	INFO	39
4.13.2	Function Documentation	39
4.13.2.1	my_imshow()	39
Index		41

Chapter 1

Class Index

1.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Settings	5
------------------------------------	---

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

src/calibration.cc	15
src/calibration.hh	
Library for calibration	19
src/calibration_run.cc	22
src/create_xml.cc	22
src/detection.cc	23
src/detection.hh	27
src/detection_run.cc	31
src/main.cc	32
src/unwrapping.cc	32
src/unwrapping.hh	35
src/unwrapping_run.cc	37
src/utils.cc	37
src/utils.hh	38

Chapter 3

Class Documentation

3.1 Settings Class Reference

```
#include <calibration.hh>
```

Public Types

- enum `Pattern` { `NOT_EXISTING` =0, `CHESSBOARD` =1 }
- enum `InputType` { `INVALID` =0, `IMAGE_LIST` =3 }

Public Member Functions

- `Settings ()`
Constructor that sets `goodInput` to false.
- void `write` (FileStorage &fs) const
Write serialization.
- void `read` (const FileNode &node)
Read serialization.
- void `validate ()`
This function validate the content of the file.
- Mat `nextImage ()`
Get next image from list.

Static Public Member Functions

- static bool `readStringList` (const string &filename, vector< string > &l)
Read from file a list of images.
- static bool `isListOfImages` (const string &filename)
Check if the file from which is trying to retrieve a list is a valid format (xml or yaml).

Public Attributes

- Size `boardSize`
The size of the board -> Number of items by width and height.
- Pattern `calibrationPattern` = `CHESSBOARD`
One of the Chessboard, circles, or asymmetric circle pattern.
- float `squareSize`
The size of a square in your defined unit (point, millimeter, etc).
- int `nrFrames`
The number of frames to use from the input for calibration.
- float `aspectRatio`
The aspect ratio.
- int `delay`
In case of a video input.
- bool `writePoints`
Write detected feature points.
- bool `writeExtrinsics`
Write extrinsic parameters.
- bool `calibZeroTangentDist`
Assume zero tangential distortion.
- bool `calibFixPrincipalPoint`
Fix the principal point at the center.
- bool `flipVertical`
Flip the captured images around the horizontal axis.
- string `outputFileName`
The name of the file where to write.
- bool `showUndistorted`
Show undistorted images after calibration.
- string `input`
The input.
- bool `useFisheye` = `false`
use fisheye camera model for calibration
- bool `fixK1`
fix K1 distortion coefficient
- bool `fixK2`
fix K2 distortion coefficient
- bool `fixK3`
fix K3 distortion coefficient
- bool `fixK4`
fix K4 distortion coefficient
- bool `fixK5`
fix K5 distortion coefficient
- int `cameraID`
- vector< string > `imageList`
- size_t `atImageList`
- VideoCapture `inputCapture`
- InputType `inputType` = `IMAGE_LIST`
- bool `goodInput`
- int `flag`

3.1.1 Member Enumeration Documentation

3.1.1.1 InputType

enum `Settings::InputType`

Enumerator

INVALID	
IMAGE_LIST	

3.1.1.2 Pattern

enum `Settings::Pattern`

Enumerator

NOT_EXISTING	
CHESSBOARD	

3.1.2 Constructor & Destructor Documentation

3.1.2.1 Settings()

```
Settings::Settings ( ) [inline]
```

Constructor that sets `goodInput` to false.

3.1.3 Member Function Documentation

3.1.3.1 isListOfImages()

```
bool Settings::isListOfImages (
    const string & filename ) [static]
```

Check if the file from which is trying to retrieve a list is a valid format (xml or yaml).

Parameters

in	<i>filename</i>	The name of the file to check for validity.
----	-----------------	---

Returns

`false` is the file is not xml or yaml
`true` otherwise.

3.1.3.2 nextImage()

```
Mat Settings::nextImage ( )
```

Get next image from list.

Returns

A matrix containing the next image to consider.

3.1.3.3 read()

```
void Settings::read (
    const FileNode & node )
```

Read serialization.

This function read data from a file and stores each node in their corresponding variables.

Parameters

in	<i>node</i>	The node of the file to consider.
----	-------------	-----------------------------------

3.1.3.4 readStringList()

```
bool Settings::readStringList (
    const string & filename,
    vector< string > & l ) [static]
```

Read from file a list of images.

Parameters

in	<i>filename</i>	The name of the file from which to read.
out	<i>l</i>	A vector which will contain the names of the file from the list.

Returns

`false` if the file could not be opened or if the file doesn't contain a list
`true` otherwise.

3.1.3.5 validate()

```
void Settings::validate ( )
```

This function validate the content of the file.

Even though this function doesn't return anything nor has any parameters for output, it sets a variable of the `Settings` class, that is `googInput`, to `false` if some infos were wrong. `true` otherwise. The options it takes in consideration are the following:

- Size must be positive.
- Cells must be greater than 10^{-6} .
- The number of frames considered, that is images, must be greater than 0.
- Check for valid input, that is a valid list of images.
- Else a list of image is being used.
- Check the field pattern: if it doesn't correspond to a known one than it's invalid.

3.1.3.6 write()

```
void Settings::write (
    FileStorage & fs ) const
```

Write serialization.

This function write data to a file.

Parameters

<code>in</code>	<code>fs</code>	The filename where to write.
-----------------	-----------------	------------------------------

3.1.4 Member Data Documentation

3.1.4.1 aspectRatio

```
float Settings::aspectRatio
```

The aspect ratio.

3.1.4.2 atImageList

```
size_t Settings::atImageList
```

3.1.4.3 boardSize

```
Size Settings::boardSize
```

The size of the board -> Number of items by width and height.

3.1.4.4 calibFixPrincipalPoint

```
bool Settings::calibFixPrincipalPoint
```

Fix the principal point at the center.

3.1.4.5 calibrationPattern

```
Pattern Settings::calibrationPattern = CHESSBOARD
```

One of the Chessboard, circles, or asymmetric circle pattern.

3.1.4.6 calibZeroTangentDist

```
bool Settings::calibZeroTangentDist
```

Assume zero tangential distortion.

3.1.4.7 cameraID

```
int Settings::cameraID
```

3.1.4.8 delay

```
int Settings::delay
```

In case of a video input.

3.1.4.9 fixK1

```
bool Settings::fixK1
```

fix K1 distortion coefficient

3.1.4.10 fixK2

```
bool Settings::fixK2
```

fix K2 distortion coefficient

3.1.4.11 fixK3

```
bool Settings::fixK3
```

fix K3 distortion coefficient

3.1.4.12 fixK4

```
bool Settings::fixK4
```

fix K4 distortion coefficient

3.1.4.13 fixK5

```
bool Settings::fixK5
```

fix K5 distortion coefficient

3.1.4.14 flag

```
int Settings::flag
```

3.1.4.15 flipVertical

```
bool Settings::flipVertical
```

Flip the captured images around the horizontal axis.

3.1.4.16 goodInput

```
bool Settings::goodInput
```

3.1.4.17 imageList

```
vector<string> Settings::imageList
```

3.1.4.18 input

```
string Settings::input
```

The input.

3.1.4.19 inputCapture

```
VideoCapture Settings::inputCapture
```

3.1.4.20 inputType

```
InputType Settings::inputType = IMAGE_LIST
```

3.1.4.21 nrFrames

```
int Settings::nrFrames
```

The number of frames to use from the input for calibration.

3.1.4.22 outputFileName

```
string Settings::outputFileName
```

The name of the file where to write.

3.1.4.23 showUndistorted

```
bool Settings::showUndistorted
```

Show undistorted images after calibration.

3.1.4.24 squareSize

```
float Settings::squareSize
```

The size of a square in your defined unit (point, millimeter,etc).

3.1.4.25 useFisheye

```
bool Settings::useFisheye = false
```

use fisheye camera model for calibration

3.1.4.26 writeExtrinsics

```
bool Settings::writeExtrinsics
```

Write extrinsic parameters.

3.1.4.27 writePoints

```
bool Settings::writePoints
```

Write detected feature points.

The documentation for this class was generated from the following files:

- [src/calibration.hh](#)
- [src/calibration.cc](#)


Chapter 4

File Documentation

4.1 src/calibration.cc File Reference

```
#include "calibration.hh"
```

Include dependency graph for calibration.cc:



Functions

- int [calibration](#) (const string inputFile)
Function to run the complete calibration.
- static void [read](#) (const FileNode &node, [Settings](#) &x, const [Settings](#) &default_value)
Reads settings from file. If there is none then initiate a new [Settings](#).
- static double [computeReprojectionErrors](#) (const vector< vector< Point3f > > &objectPoints, const vector< vector< Point2f > > &imagePoints, const vector< Mat > &rvecs, const vector< Mat > &tvecs, const Mat &cameraMatrix, const Mat &distCoeffs, vector< float > &perViewErrors, bool fisheye)
Compute the errors of the projection.
- void [calcBoardCornerPositions](#) (Size boardSize, float squareSize, vector< Point3f > &corners)
This function compute the position of the upper corners of every cell.
- static bool [runCalibration](#) ([Settings](#) &s, Size &imageSize, Mat &cameraMatrix, Mat &distCoeffs, vector< vector< Point2f > > imagePoints, vector< Mat > &rvecs, vector< Mat > &tvecs, vector< float > &reprojErrs, double &totalAvgErr)
This function run the calibration creating the matrixed for the camera and the distortion coefficients.
- static void [saveCameraParams](#) (const [Settings](#) &s, const Size &imageSize, const Mat &cameraMatrix, const Mat &distCoeffs, const vector< Mat > &rvecs, const vector< Mat > &tvecs, const vector< float > &reprojErrs, const vector< vector< Point2f > > &imagePoints, const double totalAvgErr)
Function to save the computed parameters to a file.
- bool [runCalibrationAndSave](#) ([Settings](#) &s, Size imageSize, Mat &cameraMatrix, Mat &distCoeffs, vector< vector< Point2f > > imagePoints)
Reads settings from file. If there is none then initiate a new [Settings](#).

4.1.1 Function Documentation

4.1.1.1 calcBoardCornerPositions()

```
void calcBoardCornerPositions (
    Size boardSize,
    float squareSize,
    vector< Point3f > & corners )
```

This function compute the position of the upper corners of every cell.

Parameters

in	<i>boardSiz</i>	The dimension of the chess board.
in	<i>squareSize</i>	The dimension of the edge of a cell.
out	<i>corners</i>	A vector of Point3fs which equals to the corners of the cells.

4.1.1.2 calibration()

```
int calibration (
    const string inputFile )
```

Function to run the complete calibration.

Parameters

in	<i>inputFile</i>	Name of the setting.xml file. It's set to default to default.xml
----	------------------	--

Returns

- 2 if the settings file could be load but the input was not well-formed
- 1 if the settings file could not be opened.
- 0 if everything went fine.

4.1.1.3 computeReprojectionErrors()

```
static double computeReprojectionErrors (
    const vector< vector< Point3f > > & objectPoints,
    const vector< vector< Point2f > > & imagePoints,
    const vector< Mat > & rvecs,
    const vector< Mat > & tvecs,
    const Mat & cameraMatrix,
```



```

    const Mat & distCoeffs,
    vector< float > & perViewErrors,
    bool fisheye ) [static]

```

Compute the errors of the projection.

Parameters

in	<i>objectPoints</i>	The real image points which will be projected
in	<i>rvecs</i>	Input vector of rotation vectors estimated for each pattern view.
in	<i>tvecs</i>	Input vector of translation vectors estimated for each pattern view.
in	<i>cameraMatrix</i>	The matrix containing the parameters for the camera
in	<i>distCoeffs</i>	The matrix containing the distortion coefficients.
in	<i>fisheye</i>	A variable which says if a fish eye correction should be applied or no.
out	<i>perViewErrors</i>	A vector containing the error for each image.
out	<i>imagePoints</i>	The projected points for each image.

Returns

The total error.

4.1.1.4 read()

```

static void read (
    const FileNode & node,
    Settings & x,
    const Settings & default_value ) [inline], [static]

```

Reads settings from file. If there is none then initiate a new [Settings](#).

Parameters

in	<i>node</i>	node to consider for getting settings;
in	<i>x</i>	Settings to configure;
in	<i>default_value</i>	Settings default value. Setted to Settings() .

4.1.1.5 runCalibration()

```

static bool runCalibration (
    Settings & s,
    Size & imageSize,
    Mat & cameraMatrix,
    Mat & distCoeffs,
    vector< vector< Point2f > > & imagePoints,
    vector< Mat > & rvecs,

```

```
vector< Mat > & tvecs,
vector< float > & reprojErrs,
double & totalAvgErr ) [static]
```

This function run the calibration creating the matrixed for the camera and the distorsion coefficients.

Parameters

in	<i>s</i>	The Settings read from the file and memorized.
in	<i>imageSize</i>	The size of the image used in <code>calibrateCamera()</code> to initialize the camera matrix.
in	<i>imagePoints</i>	The projected points for each image.
in	<i>reprojErrs</i>	The re-projection error, that is a geometric error corresponding to the image distance between a projected point and a measured one.
out	<i>cameraMatrix</i>	The matrix of the camera parameters
out	<i>distCoeffs</i>	The matrix of the distorsion coefficients.
out	<i>rvecs</i>	Output vector of rotation vectors estimated for each pattern view.
out	<i>tvecs</i>	Output vector of translation vectors estimated for each pattern view.
out	<i>totalAvgErr</i>	The total avarage error given from distorsion.

Returns

`false` if one or more elements in the `cameraMatrix` and `distCoeffs` are invalid.
`true` if all the elements are valid.

4.1.1.6 runCalibrationAndSave()

```
bool runCalibrationAndSave (
    Settings & s,
    Size imageSize,
    Mat & cameraMatrix,
    Mat & distCoeffs,
    vector< vector< Point2f > > imagePoints )
```

Reads settings from file. If there is none then initiate a new [Settings](#).

Parameters

in	<i>s</i>	The Settings being used during the execution.
in	<i>imageSize</i>	The dimensions of the images.
in	<i>imagePoints</i>	The projected points for each image.
out	<i>cameraMatrix</i>	The matrix which is used to store the values for the camera parameters.
out	<i>distCoeffs</i>	The matrix which is used to store the distortion coefficients.

Returns

`true` if the calibration succeded.
`false` otherwise.

4.1.1.7 saveCameraParams()

```
static void saveCameraParams (
    const Settings & s,
    const Size & imageSize,
    const Mat & cameraMatrix,
    const Mat & distCoeffs,
    const vector< Mat > & rvecs,
    const vector< Mat > & tvecs,
    const vector< float > & reprojErrs,
    const vector< vector< Point2f > > & imagePoints,
    const double totalAvgErr ) [static]
```

Function to save the computed parameters to a file.

Parameters

in	<i>s</i>	Use the Settings got at the beginning for information as the output file name, image and board size.
in	<i>imageSize</i>	The size of the image.
in	<i>cameraMatrix</i>	The camera matrix.
in	<i>distCoeffs</i>	The distortion coefficient matrix.
	<i>[int]</i>	rvecs Vector of rotation vectors estimated for each pattern view.
in	<i>tvecs</i>	Vector of translation vectors estimated for each pattern view.
in	<i>reprojErrs</i>	The re-projection error, that is a geometric error corresponding to the image distance between a projected point and a measured one.
in	<i>imagePoints</i>	The projected points for each image.
in	<i>totalAvgErr</i>	The total average error given from distortion.

Open file for writing

Stores time of calibration

Store infos about the images

4.2 src/calibration.hh File Reference

Library for calibration.


```
#include "utils.hh"
#include <iostream>
#include <sstream>
#include <string>
#include <ctime>
#include <cstdio>
#include <opencv2/core.hpp>
#include <opencv2/core/utility.hpp>
#include <opencv2/imgproc.hpp>
#include <opencv2/calib3d.hpp>
#include <opencv2/imgcodecs.hpp>
#include <opencv2/videoio.hpp>
```

```
#include <opencv2/highgui.hpp>
```

Include dependency graph for calibration.hh:



This graph shows which files directly or indirectly include this file:



Classes

- class [Settings](#)

Enumerations

- enum { [DETECTION](#) = 0, [CAPTURING](#) = 1, [CALIBRATED](#) = 2 }

Functions

- int [calibration](#) (const string inputFile="data/calib_config.xml")
Function to run the complete calibration.
- bool [runCalibrationAndSave](#) ([Settings](#) &s, Size imageSize, Mat &cameraMatrix, Mat &distCoeffs, vector< vector< Point2f > > imagePoints)
Reads settings from file. If there is none then initiate a new [Settings](#).

4.2.1 Detailed Description

Library for calibration.

4.2.2 Enumeration Type Documentation

4.2.2.1 anonymous enum

```
anonymous enum
```

Enumerator

DETECTION	
CAPTURING	
CALIBRATED	

4.2.3 Function Documentation

4.2.3.1 calibration()

```
int calibration (
    const string inputFile )
```

Function to run the complete calibration.

Parameters

in	<i>inputFile</i>	Name of the setting.xml file. It's set to default to default.xml
----	------------------	--

Returns

-2 if the settings file could be load but the input was not well-formed
 -1 if the settings file could not be opened.
 0 if everything went fine.

4.2.3.2 runCalibrationAndSave()

```
bool runCalibrationAndSave (
    Settings & s,
    Size imageSize,
    Mat & cameraMatrix,
    Mat & distCoeffs,
    vector< vector< Point2f > > imagePoints )
```

Reads settings from file. If there is none then initiate a new [Settings](#).

Parameters

in	<i>s</i>	The Settings being used during the execution.
in	<i>imageSize</i>	The dimensions of the images.
in	<i>imagePoints</i>	The projected points for each image.
out	<i>cameraMatrix</i>	The matrix which is used to store the values for the camera parameters.
out	<i>distCoeffs</i>	The matrix which is used to store the distortion coefficients.


Returns

true if the calibration succeeded.
false otherwise.

4.3 src/calibration_run.cc File Reference

```
#include "calibration.hh"
```

Include dependency graph for calibration_run.cc:

**Functions**

- int [main](#) ()

4.3.1 Function Documentation**4.3.1.1 main()**

```
int main ( )
```


4.4 src/create_xml.cc File Reference

```
#include <opencv2/core/core.hpp>
```

```
#include <iostream>
```

```
#include <string>
```

Include dependency graph for create_xml.cc:



Functions

- int [main](#) ()

4.4.1 Function Documentation


4.4.1.1 main()

```
int main ( )
```

4.5 src/detection.cc File Reference

```
#include "detection.hh"
```

Include dependency graph for detection.cc:



Macros

- #define [WAIT](#)

Functions

- int [detection](#) ()
Loads some images and detects shapes according to different colors.
- void [load_number_template](#) ()
Load some templates and save them in the global variable 'templates'.
- void [shape_detection](#) (const Mat &img, const int color)
Detect shapes inside the image according to the variable 'color'.
- void [erode_dilation](#) (Mat &img, const int color)
It apply some filtering function for isolate the subject and remove the noise.
- void [find_contours](#) (const Mat &img, Mat original, const int color)
Given an image, in black/white format, identify all the borders that delimit the shapes.
- void [save_convex_hull](#) (const vector< vector< Point >> &contours, const int color, const vector< int > &victims)
Given some vector save it in a xml file.
- int [number_recognition](#) (Rect blob, const Mat &base)
Detect a number on an image inside a region of interest.
- void [crop_number_section](#) (Mat &ROI)
Given an image identify the region of interest(ROI) and crop it out.

Variables

- const string `xml_settings` = "data/settings.xml"
- FileStorage `fs_xml`
- vector< Mat > `templates`

4.5.1 Macro Definition Documentation

4.5.1.1 WAIT

```
#define WAIT
```

4.5.2 Function Documentation

4.5.2.1 crop_number_section()

```
void crop_number_section (
    Mat & ROI )
```

Given an image identify the region of interest(ROI) and crop it out.

Parameters

<code>in, out</code>	<i>ROI</i>	Is the image that the function will going to elaborate.
----------------------	------------	---

4.5.2.2 detection()

```
int detection ( )
```

Loads some images and detects shapes according to different colors.

Returns

Return 0 if the function reach the end.

4.5.2.3 erode_dilation()

```
void erode_dilation (
    Mat & img,
    const int color )
```

It apply some filtering function for isolate the subject and remove the noise.

An example of the sub functions called are: GaussianBlur, Erosion, Dilation and Threshold.

Parameters

<i>in, out</i>	<i>img</i>	Is the image on which the function apply the filtering.
<i>in</i>	<i>color</i>	Can has 4 value: 0 -> Red 1 -> Green 2 -> Blue 3 -> Black According to the color the filtering functions apply can change in the type and in the order.

4.5.2.4 find_contours()

```
void find_contours (
    const Mat & img,
    Mat original,
    const int color )
```

Given an image, in black/white format, identify all the borders that delimit the shapes.

Parameters

<i>in</i>	<i>img</i>	Is an image in HSV format at the base of the elaboration process.
<i>out</i>	<i>original</i>	Is the original source of 'img', it is used for showing the detected contours.
<i>in</i>	<i>color</i>	Can has 3 value: 0 -> Red 1 -> Green 2 -> Blue Is used for decid which procedure apply to the image.

4.5.2.5 load_number_template()

```
void load_number_template ( )
```

Load some templates and save them in the global variable 'templates'.

4.5.2.6 number_recognition()

```
int number_recognition (
    Rect blob,
    const Mat & base )
```

Detect a number on an image inside a region of interest.

Parameters

in	<i>blob</i>	Identify the region of interest inside the image 'base'.
in	<i>base</i>	Is the image where the function will going to search the number.

Returns

The number recognise, '-1' otherwise.

4.5.2.7 save_convex_hull()

```
void save_convex_hull (
    const vector< vector< Point >> & contours,
    const int color,
    const vector< int > & victims )
```

Given some vector save it in a xml file.

Parameters

in	<i>contours</i>	Is a vector that is saved in a xml file.
in	<i>color</i>	Is the parameter according to which the function decide if saved ('color==1') or not ('otherwise') the vector 'victims'.
in	<i>victims</i>	Is a vector that is saved in a xml file.

4.5.2.8 shape_detection()

```
void shape_detection (
    const Mat & img,
    const int color )
```

Detect shapes inside the image according to the variable 'color'.

Parameters

in	<i>img</i>	Image on which the research will done.
in	<i>color</i>	Can has 3 value: 0 -> Red 1 -> Green 2 -> Blue These color identify the possible spectrum that the function search on the image.

4.5.3 Variable Documentation

4.5.3.1 fs_xml

```
FileStorage fs_xml
```

4.5.3.2 templates

```
vector<Mat> templates
```


4.5.3.3 xml_settings

```
const string xml_settings = "data/settings.xml"
```


4.6 src/detection.hh File Reference

```
#include <tesseract/baseapi.h>
#include <leptonica/allheaders.h>
#include "utils.hh"
#include <iostream>
#include <fstream>
#include <string>
#include <cmath>
#include <opencv2/highgui.hpp>
#include <opencv2/core.hpp>
#include <opencv2/opencv.hpp>
#include <opencv2/imgcodecs.hpp>
```

Include dependency graph for detection.hh:



This graph shows which files directly or indirectly include this file:



Functions

- int [detection](#) ()
Loads some images and detects shapes according to different colors.
- void [shape_detection](#) (const Mat &img, const int color)
Detect shapes inside the image according to the variable 'color'.
- void [erode_dilation](#) (Mat &img, const int color)
It apply some filtering function for isolate the subject and remove the noise.
- void [find_contours](#) (const Mat &img, Mat original, const int color)
Given an image, in black/white format, identify all the borders that delimit the shapes.
- int [number_recognition](#) (Rect blob, const Mat &base)
Detect a number on an image inside a region of interest.
- void [save_convex_hull](#) (const vector< vector< Point >> &contours, const int color, const vector< int > &victims)
Given some vector save it in a xml file.
- void [load_number_template](#) ()
Load some templates and save them in the global variable 'templates'.
- void [crop_number_section](#) (Mat &processROI)
Given an image identify the region of interest(ROI) and crop it out.

4.6.1 Function Documentation

4.6.1.1 crop_number_section()

```
void crop_number_section (
    Mat & ROI )
```

Given an image identify the region of interest(ROI) and crop it out.

Parameters

in, out	ROI	Is the image that the function will going to elaborate.
---------	-----	---

4.6.1.2 detection()

```
int detection ( )
```

Loads some images and detects shapes according to different colors.

Returns

Return 0 if the function reach the end.

4.6.1.3 erode_dilation()

```
void erode_dilation (
    Mat & img,
    const int color )
```

It apply some filtering function for isolate the subject and remove the noise.

An example of the sub functions called are: GaussianBlur, Erosion, Dilation and Threshold.

Parameters

in, out	<i>img</i>	Is the image on which the function apply the filtering.
in	<i>color</i>	Can has 4 value: 0 -> Red 1 -> Green 2 -> Blue 3 -> Black According to the color the filtering functions apply can change in the type and in the order.

4.6.1.4 find_contours()

```
void find_contours (
    const Mat & img,
    Mat original,
    const int color )
```

Given an image, in black/white format, identify all the borders that delimit the shapes.

Parameters

in	<i>img</i>	Is an image in HSV format at the base of the elaboration process.
out	<i>original</i>	Is the original source of 'img', it is used for showing the detected contours.

Parameters

in	<i>color</i>	Can has 3 value: 0 -> Red 1 -> Green 2 -> Blue Is used for decid which procedure apply to the image.
----	--------------	--

4.6.1.5 load_number_template()

```
void load_number_template ( )
```

Load some templates and save them in the global variable 'templates'.

4.6.1.6 number_recognition()

```
int number_recognition (
    Rect blob,
    const Mat & base )
```

Detect a number on an image inside a region of interest.

Parameters

in	<i>blob</i>	Identify the region of interest inside the image 'base'.
in	<i>base</i>	Is the image where the function will going to search the number.

Returns

The number recognise, '-1' otherwise.

4.6.1.7 save_convex_hull()

```
void save_convex_hull (
    const vector< vector< Point >> & contours,
    const int color,
    const vector< int > & victims )
```

Given some vector save it in a xml file.

Parameters

in	<i>contours</i>	Is a vector that is saved in a xml file.
in	<i>color</i>	Is the parameter according to which the function decide if saved ('color==1') or not ('otherwise') the vector 'victims'.
in	<i>victims</i>	Is a vector that is saved in a xml file.

4.6.1.8 shape_detection()

```
void shape_detection (
    const Mat & img,
    const int color )
```

Detect shapes inside the image according to the variable 'color'.


Parameters

in	<i>img</i>	Image on which the research will done.
in	<i>color</i>	Can has 3 value: 0 -> Red 1 -> Green 2 -> Blue These color identify the possible spectrum that the function search on the image.

4.7 src/detection_run.cc File Reference

```
#include "detection.hh"
```

Include dependency graph for detection_run.cc:



Functions

- int [main](#) ()

4.7.1 Function Documentation

4.7.1.1 main()

```
int main ( )
```


Functions

- static float [distance](#) (Point c1, Point c2)
Compute the euclidean distance.
- static void [swap](#) (int &a, int &b)
Swap the two integers passed.
- int [unwrapping](#) ()
Take some images according to a xml and unwrap the black rectangle inside the image after applying undistortion trasformation.
- void [loadCoefficients](#) (const string filename, Mat &camera_matrix, Mat &dist_coeffs)
Load coefficients from a file.

Variables

- const string [xml_settings](#) = "data/settings.xml"

4.9.1 Macro Definition Documentation

4.9.1.1 area_ratio

```
#define area_ratio 0.7
```

4.9.1.2 WAIT

```
#define WAIT
```

4.9.2 Function Documentation

4.9.2.1 distance()

```
static float distance (
    Point c1,
    Point c2 ) [static]
```

Compute the euclidean distance.

Parameters

in, out	<i>c1</i>	The first point.
in, out	<i>c2</i>	The second point.

Returns

The euclidean distance.

4.9.2.2 loadCoefficients()

```
void loadCoefficients (
    const string filename,
    Mat & camera_matrix,
    Mat & dist_coeffs )
```

Load coefficients from a file.

Load two matrix 'camera_matrix' and 'distortion_coefficients' from the xml file passed.

Parameters

in	<i>filename</i>	The string that identify the location of the xml file.
out	<i>camera_matrix</i>	Where the 'camera_matrix' matrix is saved.
out	<i>dist_coeffs</i>	Where the 'distortion_coefficients' matrix is saved.

4.9.2.3 swap()

```
static void swap (
    int & a,
    int & b ) [static]
```

Swap the two integers passed.

Parameters

in, out	<i>a</i>	First parameter.
in, out	<i>b</i>	Second parameter.

4.9.2.4 unwrapping()

```
int unwrapping ( )
```

Take some images according to a xml and unwrap the black rectangle inside the image after applying undistortion trasformation.

Load from the xml file 'data/settings.xml' the name of some images, load the images from the file, apply the calibration (undistortion trasformation) thanks to the matrices load with the 'loadCoefficients' function. Then, with the use of a filter for the black the region of interest (a rectangle) is identified and all the perspective is rotated for reach a top view of the rectangle. Finally, the images are saved on some files.

Returns

A 0 is return if the function reach the end.

4.9.3 Variable Documentation


4.9.3.1 xml_settings

```
const string xml_settings = "data/settings.xml"
```


4.10 src/unwrapping.hh File Reference

```
#include "utils.hh"
#include <iostream>
#include <fstream>
#include <string>
#include <cmath>
#include <opencv2/videoio.hpp>
#include <opencv2/highgui.hpp>
#include <opencv2/core.hpp>
#include <opencv2/opencv.hpp>
#include <opencv2/imgcodecs.hpp>
```

Include dependency graph for unwrapping.hh:



This graph shows which files directly or indirectly include this file:



Functions

- int `unwrapping` ()
Take some images according to a xml and unwrap the black rectangle inside the image after applying undistortion trasformation.
- void `loadCoefficients` (const string filename, Mat &camera_matrix, Mat &dist_coeffs)
Load coefficients from a file.

4.10.1 Function Documentation

4.10.1.1 loadCoefficients()

```
void loadCoefficients (
    const string filename,
    Mat & camera_matrix,
    Mat & dist_coeffs )
```

Load coefficients from a file.

Load two matrix 'camera_matrix' and 'distortion_coefficients' from the xml file passed.

Parameters

in	<i>filename</i>	The string that identify the location of the xml file.
out	<i>camera_matrix</i>	Where the 'camera_matrix' matrix is saved.
out	<i>dist_coeffs</i>	Where the 'distortion_coefficients' matrix is saved.

4.10.1.2 unwrapping()

```
int unwrapping ( )
```

Take some images according to a xml and unwrap the black rectangle inside the image after applying undistortion trasformation.

Load from the xml file 'data/settings.xml' the name of some images, load the images from the file, apply the calibration (undistortion trasformation) thanks to the matrices load with the 'loadCoefficients' function. Then, with the use of a filter for the black the region of interest (a rectangle) is identified and all the perspective is rotated for reach a top view of the rectangle. Finally, the images are saved on some files.


Returns

A 0 is return if the function reach the end.

4.11 src/unwrapping_run.cc File Reference

```
#include "unwrapping.hh"
```

Include dependency graph for unwrapping_run.cc:



Functions

- int [main](#) ()

4.11.1 Function Documentation


4.11.1.1 main()

```
int main ( )
```

4.12 src/utils.cc File Reference

```
#include "utils.hh"
```

Include dependency graph for utils.cc:



Functions

- void [my_imshow](#) (const char *win_name, Mat img, bool reset)

4.12.1 Function Documentation


4.12.1.1 my_imshow()

```
void my_imshow (
    const char * win_name,
    Mat img,
    bool reset )
```


4.13 src/utils.hh File Reference

```
#include <tesseract/baseapi.h>
#include <leptonica/allheaders.h>
#include <cstdio>
#include <opencv2/highgui.hpp>
#include <opencv2/core.hpp>
#include <opencv2/opencv.hpp>
#include <opencv2/imgcodecs.hpp>
```

Include dependency graph for utils.hh:



This graph shows which files directly or indirectly include this file:



Macros

- `#define INFO(msg)`

Functions

- `void my_imshow (const char *win_name, Mat img, bool reset=false)`

4.13.1 Macro Definition Documentation

4.13.1.1 INFO

```
#define INFO(  
    msg )
```

4.13.2 Function Documentation

4.13.2.1 my_imshow()

```
void my_imshow (  
    const char * win_name,  
    Mat img,  
    bool reset = false )
```


Index

- area_ratio
 - [unwrapping.cc, 33](#)
- aspectRatio
 - [Settings, 10](#)
- atImageList
 - [Settings, 10](#)
- boardSize
 - [Settings, 10](#)
- calcBoardCornerPositions
 - [calibration.cc, 16](#)
- calibFixPrincipalPoint
 - [Settings, 10](#)
- calibZeroTangentDist
 - [Settings, 10](#)
- calibration
 - [calibration.cc, 16](#)
 - [calibration.hh, 21](#)
- calibration.cc
 - [calcBoardCornerPositions, 16](#)
 - [calibration, 16](#)
 - [computeReprojectionErrors, 16](#)
 - [read, 17](#)
 - [runCalibration, 17](#)
 - [runCalibrationAndSave, 18](#)
 - [saveCameraParams, 18](#)
- calibration.hh
 - [calibration, 21](#)
 - [runCalibrationAndSave, 21](#)
- calibration_run.cc
 - [main, 22](#)
- calibrationPattern
 - [Settings, 10](#)
- cameraID
 - [Settings, 11](#)
- computeReprojectionErrors
 - [calibration.cc, 16](#)
- create_xml.cc
 - [main, 23](#)
- crop_number_section
 - [detection.cc, 24](#)
 - [detection.hh, 28](#)
- delay
 - [Settings, 11](#)
- detection
 - [detection.cc, 24](#)
 - [detection.hh, 29](#)
- detection.cc
 - [crop_number_section, 24](#)
 - [detection, 24](#)
 - [erode_dilation, 24](#)
 - [find_contours, 25](#)
 - [fs_xml, 27](#)
 - [load_number_template, 25](#)
 - [number_recognition, 25](#)
 - [save_convex_hull, 26](#)
 - [shape_detection, 26](#)
 - [templates, 27](#)
 - [WAIT, 24](#)
 - [xml_settings, 27](#)
- detection.hh
 - [crop_number_section, 28](#)
 - [detection, 29](#)
 - [erode_dilation, 29](#)
 - [find_contours, 29](#)
 - [load_number_template, 30](#)
 - [number_recognition, 30](#)
 - [save_convex_hull, 30](#)
 - [shape_detection, 31](#)
- detection_run.cc
 - [main, 31](#)
- distance
 - [unwrapping.cc, 33](#)
- erode_dilation
 - [detection.cc, 24](#)
 - [detection.hh, 29](#)
- find_contours
 - [detection.cc, 25](#)
 - [detection.hh, 29](#)
- fixK1
 - [Settings, 11](#)
- fixK2
 - [Settings, 11](#)
- fixK3
 - [Settings, 11](#)
- fixK4
 - [Settings, 11](#)
- fixK5
 - [Settings, 12](#)
- flag
 - [Settings, 12](#)
- flipVertical
 - [Settings, 12](#)
- fs_xml
 - [detection.cc, 27](#)

- goodInput
 - Settings, 12
- INFO
 - utils.hh, 38
- imageList
 - Settings, 12
- input
 - Settings, 12
- inputCapture
 - Settings, 12
- inputType
 - Settings, 13
- InputType
 - Settings, 7
- isListOfImages
 - Settings, 7
- load_number_template
 - detection.cc, 25
 - detection.hh, 30
- loadCoefficients
 - unwrapping.cc, 34
 - unwrapping.hh, 36
- main
 - calibration_run.cc, 22
 - create_xml.cc, 23
 - detection_run.cc, 31
 - main.cc, 32
 - unwrapping_run.cc, 37
- main.cc
 - main, 32
- my_imshow
 - utils.cc, 37
 - utils.hh, 39
- nextImage
 - Settings, 8
- nrFrames
 - Settings, 13
- number_recognition
 - detection.cc, 25
 - detection.hh, 30
- outputFileName
 - Settings, 13
- Pattern
 - Settings, 7
- read
 - calibration.cc, 17
 - Settings, 8
- readStringList
 - Settings, 8
- runCalibration
 - calibration.cc, 17
- runCalibrationAndSave
 - calibration.cc, 18
- calibration.hh, 21
- save_convex_hull
 - detection.cc, 26
 - detection.hh, 30
- saveCameraParams
 - calibration.cc, 18
- Settings, 5
 - aspectRatio, 10
 - atImageList, 10
 - boardSize, 10
 - calibFixPrincipalPoint, 10
 - calibZeroTangentDist, 10
 - calibrationPattern, 10
 - cameraID, 11
 - delay, 11
 - fixK1, 11
 - fixK2, 11
 - fixK3, 11
 - fixK4, 11
 - fixK5, 12
 - flag, 12
 - flipVertical, 12
 - goodInput, 12
 - imageList, 12
 - input, 12
 - inputCapture, 12
 - inputType, 13
 - InputType, 7
 - isListOfImages, 7
 - nextImage, 8
 - nrFrames, 13
 - outputFileName, 13
 - Pattern, 7
 - read, 8
 - readStringList, 8
 - Settings, 7
 - showUndistorted, 13
 - squareSize, 13
 - useFisheye, 13
 - validate, 9
 - write, 9
 - writeExtrinsics, 14
 - writePoints, 14
- shape_detection
 - detection.cc, 26
 - detection.hh, 31
- showUndistorted
 - Settings, 13
- squareSize
 - Settings, 13
- src/calibration.cc, 15
- src/calibration.hh, 19
- src/calibration_run.cc, 22
- src/create_xml.cc, 22
- src/detection.cc, 23
- src/detection.hh, 27
- src/detection_run.cc, 31
- src/main.cc, 32

- src/unwrapping.cc, [32](#)
- src/unwrapping.hh, [35](#)
- src/unwrapping_run.cc, [37](#)
- src/utils.cc, [37](#)
- src/utils.hh, [38](#)
- swap
 - unwrapping.cc, [34](#)
- templates
 - detection.cc, [27](#)
- unwrapping
 - unwrapping.cc, [34](#)
 - unwrapping.hh, [36](#)
- unwrapping.cc
 - area_ratio, [33](#)
 - distance, [33](#)
 - loadCoefficients, [34](#)
 - swap, [34](#)
 - unwrapping, [34](#)
 - WAIT, [33](#)
 - xml_settings, [35](#)
- unwrapping.hh
 - loadCoefficients, [36](#)
 - unwrapping, [36](#)
- unwrapping_run.cc
 - main, [37](#)
- useFisheye
 - Settings, [13](#)
- utils.cc
 - my_imshow, [37](#)
- utils.hh
 - INFO, [38](#)
 - my_imshow, [39](#)
- validate
 - Settings, [9](#)
- WAIT
 - detection.cc, [24](#)
 - unwrapping.cc, [33](#)
- write
 - Settings, [9](#)
- writeExtrinsics
 - Settings, [14](#)
- writePoints
 - Settings, [14](#)
- xml_settings
 - detection.cc, [27](#)
 - unwrapping.cc, [35](#)