

## C. Chain Reaction

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

There are  $n$  beacons located at distinct positions on a number line. The  $i$ -th beacon has position  $a_i$  and power level  $b_i$ . When the  $i$ -th beacon is activated, it destroys all beacons to its left (direction of decreasing coordinates) within distance  $b_i$  inclusive. The beacon itself is not destroyed however. Saitama will activate the beacons one at a time from right to left. If a beacon is destroyed, it cannot be activated.

Saitama wants Genos to add a beacon **strictly to the right** of all the existing beacons, with any position and any power level, such that the least possible number of beacons are destroyed. Note that Genos's placement of the beacon means it will be the first beacon activated. Help Genos by finding the minimum number of beacons that could be destroyed.

### Input

The first line of input contains a single integer  $n$  ( $1 \leq n \leq 100\,000$ ) — the initial number of beacons.

The  $i$ -th of next  $n$  lines contains two integers  $a_i$  and  $b_i$  ( $0 \leq a_i \leq 1\,000\,000$ ,  $1 \leq b_i \leq 1\,000\,000$ ) — the position and power level of the  $i$ -th beacon respectively. No two beacons will have the same position, so  $a_i \neq a_j$  if  $i \neq j$ .

### Output

Print a single integer — the minimum number of beacons that could be destroyed if exactly one beacon is added.

### Examples

input	Copy
4 1 9 3 1 6 1 7 4	
output	Copy
1	

input	Copy
7 1 1 2 1 3 1 4 1 5 1 6 1 7 1	
output	Copy
3	

### Note

### Codeforces Round #336 (Div. 2)

**Finished**

### → Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

### → Problem tags

dp \*1600

No tag edit access

### → Contest materials

- Announcement (en) ×
- Tutorial (en) ×

For the first sample case, the minimum number of beacons destroyed is 1. One way to achieve this is to place a beacon at position 9 with power level 2.

For the second sample case, the minimum number of beacons destroyed is 3. One way to achieve this is to place a beacon at position 1337 with power level 42.

---

[Codeforces](#) (c) Copyright 2010-2020 Mike Mirzayanov  
The only programming contests Web 2.0 platform  
Server time: Sep/22/2020 16:27:37<sup>UTC-5</sup> (i1).  
Desktop version, switch to [mobile version](#).  
[Privacy Policy](#)

Supported by



ITMO UNIVERSITY