

CTU Open 2024

Presentation of solutions

October 29, 2024

Flagbearer



Bear

- ▶ Just rewrite the nice ascii art compare, shift and print.


Bear

- ▶ Just rewrite the nice ascii art compare, shift and print.
- ▶ You can also observe a regular pattern in the rotation of the hands (with few exceptions).

Fellow Sheep




Sheep




- ▶ The task boils down to finding the maximum flow between the pasture, and the farmyard.

Sheep




- ▶ The task boils down to finding the maximum flow between the pasture, and the farmyard.
- ▶ Maximum flow is equal to the minimum cut.

Sheep




- ▶ The task boils down to finding the maximum flow between the pasture, and the farmyard.
- ▶ Maximum flow is equal to the minimum cut.
- ▶ Observation: for each segment, we can find the minimum cut separately.


Sheep




Sheep




Sheep




Sheep



Sheep



Sheep



$$\min(A + D, B + E, A + C + E, B + C + D)$$

Sheep

Repeat for each segment, take the minimum of all segments.

Hamster




Hamster

- ▶ **Input:** $N \times M$ grid $P_N \times P_M$, each cell with nonnegative integer.
- ▶ **Output:** Find a maximum cost path from top left to bottom right.

Hamster

- ▶ **Input:** $N \times M$ grid $P_N \times P_M$, each cell with nonnegative integer.
- ▶ **Output:** Find a maximum cost path from top left to bottom right.


Observation 1: If N or M is odd there is a path going through all of the cells.



Hamster

- ▶ **Input:** $N \times M$ grid $P_N \times P_M$, each cell with nonnegative integer.
 - ▶ **Output:** Find a maximum cost path from top left to bottom right.


Observation 1: If N or M is odd there is a path going through all of the cells.



Hamster

- ▶ **Input:** $N \times M$ grid $P_N \times P_M$, each cell with nonnegative integer.
- ▶ **Output:** Find a maximum cost path from top left to bottom right.


Observation 1: If N or M is odd there is a path going through all of the cells.



Hamster

- ▶ **Input:** $N \times M$ grid $P_N \times P_M$, each cell with nonnegative integer.
- ▶ **Output:** Find a maximum cost path from top left to bottom right.

Observation 1: If N or M is odd there is a path going through all of the cells.




Hamster

So the interesting case is when both N and M are even.

Hamster

So the interesting case is when both N and M are even.


Observation 2: Color the grid with chessboard pattern, start and end cell are both black.



Hamster

So the interesting case is when both N and M are even.

Observation 2: Color the grid with chessboard pattern, start and end cell are both black.



Colorally: Each path contains one more black than white cell.


Hamster

Observation 3: For each white cell, there is a path that only removes that cell.

Hamster

Observation 3: For each white cell, there is a path that only removes that cell.


► Base case:



Hamster

Observation 3: For each white cell, there is a path that only removes that cell.


► Base case:




Hamster

Observation 3: For each white cell, there is a path that only removes that cell.

- ▶ **Base case:**




- ▶ **Induction step:** Remove 2 left/most most column or 2 first/last rows that do not contain the cell in question.




Hamster

Observation 3: For each white cell, there is a path that only removes that cell.

- ▶ **Base case:**




- ▶ **Induction step:** Remove 2 left/most most column or 2 first/last rows that do not contain the cell in question.




Hamster

Observation 3: For each white cell, there is a path that only removes that cell.

- ▶ **Base case:**




- ▶ **Induction step:** Remove 2 left/most most column or 2 first/last rows that do not contain the cell in question.




Hamster

Observation 3: For each white cell, there is a path that only removes that cell.

- ▶ **Base case:**




- ▶ **Induction step:** Remove 2 left/most most column or 2 first/last rows that do not contain the cell in question.




Hamster

Observation 3: For each white cell, there is a path that only removes that cell.

- ▶ **Base case:**



- ▶ **Induction step:** Remove 2 left/most most column or 2 first/last rows that do not contain the cell in question.



Hamster

Summary:


- ▶ If N or M is odd, return sum of all cells.
- ▶ Else both N and M are even.
 - ▶ Let C_{MIN} be the minimum value on a cell that has sum of its coordinates odd.
 - ▶ Output sum of all cells minus C_{MIN} .

Pray mink



Mink

- ▶ **Input:** Integer $1 \leq N \leq 10^9$.
- ▶ **Task:** How many prime numbers can we obtain in a row when removing digits from N one by one?



Mink

- ▶ N has at most 10 digits.
- ▶ We can obtain 2^{10} different numbers.
- ▶ We can recursively try all possible sequences of removing numbers and use DP.
- ▶ Checking primeness in time $O(\sqrt{n})$ is fast enough.
 - ▶ At most $\sum_{i=1}^{10} \binom{10}{i} \sqrt{10^i} \approx 1.6 \cdot 10^6$ modulo operations.
- ▶ The rest takes $O(2^{\log_{10} n}) = O(2^{\log n / \log 10}) = O(1.24^n)$ time.


(1)

Fishception




Fishception

- ▶ $4N$ points with integer coordinates in a plane.
- ▶ The points represent the vertices of non-intersecting rectangles, each one contained within the next.
- ▶ **Task:** Determine the area of the smallest rectangle.




Fishception

- ▶ $4N$ points with integer coordinates in a plane.
- ▶ The points represent the vertices of non-intersecting rectangles, each one contained within the next.
- ▶ **Task:** Determine the area of the smallest rectangle.




Fishception

- ▶ Sort the points by the x-axis and by the y-axis.
- ▶ In each step, you take the leftmost, topmost, rightmost, and bottommost unmarked points and mark them.
- ▶ The last 4 points form the desired smallest rectangle.
- ▶ Solution with $\mathcal{O}(n \log n)$ will pass.




Fishception

- ▶ Sort the points by the x-axis and by the y-axis.
- ▶ In each step, you take the leftmost, topmost, rightmost, and bottommost unmarked points and mark them.
- ▶ The last 4 points form the desired smallest rectangle.
- ▶ Solution with $\mathcal{O}(n \log n)$ will pass.




Fishception

- ▶ Sort the points by the x-axis and by the y-axis.
- ▶ In each step, you take the leftmost, topmost, rightmost, and bottommost unmarked points and mark them.
- ▶ The last 4 points form the desired smallest rectangle.
- ▶ Solution with $\mathcal{O}(n \log n)$ will pass.




Fishception

- ▶ Sort the points by the x-axis and by the y-axis.
- ▶ In each step, you take the leftmost, topmost, rightmost, and bottommost unmarked points and mark them.
- ▶ The last 4 points form the desired smallest rectangle.
- ▶ Solution with $\mathcal{O}(n \log n)$ will pass.




Fishception

- ▶ Sort the points by the x-axis and by the y-axis.
- ▶ In each step, you take the leftmost, topmost, rightmost, and bottommost unmarked points and mark them.
- ▶ The last 4 points form the desired smallest rectangle.
- ▶ Solution with $\mathcal{O}(n \log n)$ will pass.




Fishception

- ▶ Sort the points by the x-axis and by the y-axis.
- ▶ In each step, you take the leftmost, topmost, rightmost, and bottommost unmarked points and mark them.
- ▶ The last 4 points form the desired smallest rectangle.
- ▶ Solution with $\mathcal{O}(n \log n)$ will pass.



Fishception

- ▶ It is necessary to take care of the case when a rectangle has edges parallel to the axes.



Ornithology



Ornithology

- ▶ **Input:** A bipartite graph with two parts drawn on two parallel straight lines.
- ▶ **Output:** The number of edge crossings.
- ▶ The edges do not cross at the vertices.

Ornithology

- ▶ Purely combinatorial problem, no geometry involved.

Ornithology


- ▶ Purely combinatorial problem, no geometry involved.
- ▶ Let $V = A \cup B$ and. Edges $\{a_1, b_1\}$ and $\{a_2, b_2\}$ cross if and only if $a_1 < a_2 \wedge b_2 < b_1$ or $a_1 > a_2 \wedge b_2 > b_1$.

Ornithology

- ▶ Purely combinatorial problem, no geometry involved.
- ▶ Let $V = A \cup B$ and. Edges $\{a_1, b_1\}$ and $\{a_2, b_2\}$ cross if and only if $a_1 < a_2 \wedge b_2 < b_1$ or $a_1 > a_2 \wedge b_2 > b_1$.
- ▶ $O(|E|^2)$ naive algorithm is too slow. ($|E| \approx 2 \cdot 10^5$).

Ornithology - fast solution


0 0 0 0 0 0



res =

Ornithology - fast solution


1 0 0 0 0 0



res =

Ornithology - fast solution


1 0 1 0 0 0



res =

Ornithology - fast solution


1 0 1 0 1 0



res =

Ornithology - fast solution


1 0 1 0 1 1



res =

Ornithology - fast solution


2 0 1 0 1 1



res = 3

Ornithology - fast solution


2 0 2 0 1 1



$$\text{res} = 3 + 2$$

Ornithology - fast solution


2 0 2 1 1 1



$$\text{res} = 3 + 2 + 2$$

Ornithology - fast solution


2 0 2 1 1 2



$$\text{res} = 3 + 2 + 2$$

Ornithology - fast solution


2 1 2 1 1 2



$$\text{res} = 3 + 2 + 2 + 6$$

Ornithology - fast solution


2 1 2 2 1 2



$$\text{res} = 3 + 2 + 2 + 6 + 3$$

Ornithology - fast solution


2 1 2 2 2 2



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2$$

Ornithology - fast solution


2 1 3 2 2 2



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6$$

Ornithology - fast solution


2 1 3 2 2 3



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6$$

Ornithology - fast solution


2 2 3 2 2 3



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10$$

Ornithology - fast solution


2 2 3 2 3 3



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10 + 3$$

Ornithology - fast solution


2 2 3 2 3 4



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10 + 3$$

Ornithology - fast solution


3 2 3 2 3 4



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10 + 3 + 14$$

Ornithology - fast solution


3 2 4 2 3 4



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10 + 3 + 14 + 9$$

Ornithology - fast solution


3 2 4 3 3 4



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10 + 3 + 14 + 9 + 7$$

Ornithology - fast solution

3 2 4 3 3 4



$$\text{res} = 3 + 2 + 2 + 6 + 3 + 2 + 6 + 10 + 3 + 14 + 9 + 7$$

Ornithology - fast solution

Ornithology - fast solution

- ▶ Sort edges lexicographically.

Ornithology - fast solution

- ▶ Sort edges lexicographically.
- ▶ Initialize an array x of size n with 0's

Ornithology - fast solution

- ▶ Sort edges lexicographically.
- ▶ Initialize an array x of size n with 0's
- ▶ For edge $\{a, b\}$ add 1 to index b and add $\sum_{i=b+1}^{n-1} x_i$ to the result.

Ornithology - fast solution

- ▶ Sort edges lexicographically.
- ▶ Initialize an array suitable data structure x of size n with 0's
- ▶ For edge $\{a, b\}$ add 1 to index b and add $\sum_{i=b+1}^{n-1} x_i$ to the result.
- ▶ Actually instead of a plain array, use your favourite data structure with fast point update and range sum query.

Ornithology - fast solution

- ▶ Sort edges lexicographically.
- ▶ Initialize an array suitable data structure x of size n with 0's
- ▶ For edge $\{a, b\}$ add 1 to index b and add $\sum_{i=b+1}^{n-1} x_i$ to the result.
- ▶ Actually instead of a plain array, use your favourite data structure with fast point update and range sum query.
- ▶ Anything reasonable with $o(N)$ complexity per query was intended to pass (segment tree, fenwick tree, sqrt decomposition, . . .).

Ornithology - fast solution

- ▶ Sort edges lexicographically.
- ▶ Initialize an array suitable data structure x of size n with 0's
- ▶ For edge $\{a, b\}$ add 1 to index b and add $\sum_{i=b+1}^{n-1} x_i$ to the result.
- ▶ Actually instead of a plain array, use your favourite data structure with fast point update and range sum query.
- ▶ Anything reasonable with $o(N)$ complexity per query was intended to pass (segment tree, fenwick tree, sqrt decomposition, . . .).
- ▶ Complexity: $O(|E| \log N)$ with e.g. segment tree.

Ornithology - fast solution without data structures

Ornithology - fast solution without data structures

- ▶ Divide and Conquer approach.

Ornithology - fast solution without data structures

- ▶ Divide and Conquer approach.
- ▶ Rough Idea: Split edges to two parts based on the endpoint in the first part and recurse.

Ornithology - fast solution without data structures

- ▶ Divide and Conquer approach.
- ▶ Rough Idea: Split edges to two parts based on the endpoint in the first part and recurse.
- ▶ Merge step: calculate the intersections between edges that have one endpoint in left and one in right.

Ornithology - fast solution without data structures

- ▶ Divide and Conquer approach.
- ▶ Rough Idea: Split edges to two parts based on the endpoint in the first part and recurse.
- ▶ Merge step: calculate the intersections between edges that have one endpoint in left and one in right.
- ▶ Complexity $O(|E| \log N)$.

Pork cutting



Pork cutting

- ▶ Decompose each number into bit.
- ▶ We need to find such intervals, which have the number of 0-bits of K equal to 0 while the number of 1-bits of K to be at least 1.

Pork cutting

- ▶ Decompose each number into bit.
- ▶ We need to find such intervals, which have the number of 0-bits of K equal to 0 while the number of 1-bits of K to be at least 1.
- ▶ Sweep the array and calculate prefix sum for each bit.
- ▶ Keep the track of "correct" intervals by two pointers.

Pork cutting

- ▶ Decompose each number into bit.
- ▶ We need to find such intervals, which have the number of 0-bits of K equal to 0 while the number of 1-bits of K to be at least 1.
- ▶ Sweep the array and calculate prefix sum for each bit.
- ▶ Keep the track of "correct" intervals by two pointers.
- ▶ Complexity: $O(N \cdot \log(K))$

Rabid rabbit



Rabid rabbit

- ▶ Observe that there is relatively small number of Fibonacci numbers - less than $(\log(|U|))$

Rabid rabbit

- ▶ Observe that there is relatively small number of Fibonacci numbers - less than ($\log(|U|)$)
- ▶ Solve the problem for each Fibonacci number separately.

Rabid rabbit

- ▶ Observe that there is relatively small number of Fibonacci numbers - less than ($\log(|U|)$)
- ▶ Solve the problem for each Fibonacci number separately.
- ▶ Iterate through array, keeping track of last occurrence of every number.
- ▶ Use two pointers technique to find "least interval" for each beginning, where the actual Fibonacci number can be constructed.

Rabid rabbit

- ▶ Observe that there is relatively small number of Fibonacci numbers - less than ($\log(|U|)$)
- ▶ Solve the problem for each Fibonacci number separately.
- ▶ Iterate through array, keeping track of last occurrence of every number.
- ▶ Use two pointers technique to find "least interval" for each beginning, where the actual Fibonacci number can be constructed.
- ▶ Complexity: $O(N \log(|U|) \log(|U|) + Q \log(|U|))$

Watchdogs



Watchdogs

Watchcats

Watchcats

- ▶ **Input:** Tree T with q paths specified by endpoints.
- ▶ **Task:** For each a - b path P a vertex x on P with $|d(a, x) - d(b, x)| \leq 1$ must be selected. One vertex can be selected for multiple paths.
- ▶ **Output:** Minimum number of vertices to select.

Watchcat Niki



Watchcat Mǐša



Watchcats

- ▶ Each a - b path (for pair of lairs (a, b)) has some set of vertices corresponding to vulnerability places – the *vulnerability set*.

Watchcats

- ▶ Each a - b path (for pair of lairs (a, b)) has some set of vertices corresponding to vulnerability places – the *vulnerability set*.
- ▶ Each vulnerability set is either a single vertex or induces an edge.

Watchcats

- ▶ Each $a-b$ path (for pair of lairs (a, b)) has some set of vertices corresponding to vulnerability places – the *vulnerability set*.
- ▶ Each vulnerability set is either a single vertex or induces an edge.
- ▶ If it is a vertex, it must be covered by a watchcat. Let $S \subseteq V$ be the set of vertices v s.t. $\{v\}$ is the vulnerability set for some mouse.

Watchcats

- ▶ Each a - b path (for pair of lairs (a, b)) has some set of vertices corresponding to vulnerability places – the *vulnerability set*.
- ▶ Each vulnerability set is either a single vertex or induces an edge.
- ▶ If it is a vertex, it must be covered by a watchcat. Let $S \subseteq V$ be the set of vertices v s.t. $\{v\}$ is the vulnerability set for some mouse.
- ▶ In the graph $T[V(T) \setminus S]$ we are left with edges that must be covered.


Watchcats

- ▶ Each $a-b$ path (for pair of lairs (a, b)) has some set of vertices corresponding to vulnerability places – the *vulnerability set*.
- ▶ Each vulnerability set is either a single vertex or induces an edge.
- ▶ If it is a vertex, it must be covered by a watchcat. Let $S \subseteq V$ be the set of vertices v s.t. $\{v\}$ is the vulnerability set for some mouse.
- ▶ In the graph $T[V(T) \setminus S]$ we are left with edges that must be covered.
- ▶ Vertex Cover on the remaining forest!

Watchcat Čičinas



Watchcat Denis



Watchcats - How to solve it fast?

- ▶ The vertex cover can be solved in $O(n)$ time on trees by DP:

Watchcats - How to solve it fast?

- ▶ The vertex cover can be solved in $O(n)$ time on trees by DP:
- ▶ Hang the tree on r and for each vertex in bottom up manner compute:

Watchcats - How to solve it fast?

- ▶ The vertex cover can be solved in $O(n)$ time on trees by DP:
- ▶ Hang the tree on r and for each vertex in bottom up manner compute:
- ▶ $D[v][0]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \notin S$.

Watchcats - How to solve it fast?

- ▶ The vertex cover can be solved in $O(n)$ time on trees by DP:
- ▶ Hang the tree on r and for each vertex in bottom up manner compute:
 - ▶ $D[v][0]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \notin S$.
 - ▶ $D[v][1]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \in S$.

Watchcats - How to solve it fast?

- ▶ The vertex cover can be solved in $O(n)$ time on trees by DP:
- ▶ Hang the tree on r and for each vertex in bottom up manner compute:
- ▶ $D[v][0]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \notin S$.
- ▶ $D[v][1]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \in S$.
- ▶ Transition: $D[v][0] = \sum_{u \in \text{child}(v)} D[u][1]$ and
 $D[v][1] = 1 + \sum_{u \in \text{child}(v)} \min\{D[u][0], D[u][1]\}$.

Watchcats - How to solve it fast?

- ▶ The vertex cover can be solved in $O(n)$ time on trees by DP:
- ▶ Hang the tree on r and for each vertex in bottom up manner compute:
- ▶ $D[v][0]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \notin S$.
- ▶ $D[v][1]$ - the size of smallest vertex cover S in the subtree rooted at v where $v \in S$.
- ▶ Transition: $D[v][0] = \sum_{u \in \text{child}(v)} D[u][1]$ and
 $D[v][1] = 1 + \sum_{u \in \text{child}(v)} \min\{D[u][0], D[u][1]\}$.
- ▶ Result is $\min\{D[r][0], D[r][1]\}$.

Watchcat Ritchie



Watchcat Kiwi



Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA!

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.
- ▶ If $d(\ell, a) = d(\ell, b)$, then the resulting set is just $\{\ell\}$.

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.
- ▶ If $d(\ell, a) = d(\ell, b)$, then the resulting set is just $\{\ell\}$.
- ▶ If $d(\ell, a) > d(\ell, b)$, then the result lies on the path from a to ℓ .

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.
- ▶ If $d(\ell, a) = d(\ell, b)$, then the resulting set is just $\{\ell\}$.
- ▶ If $d(\ell, a) > d(\ell, b)$, then the result lies on the path from a to ℓ .
- ▶ To find the central vertices of the path, jump from a to ℓ to distance $t = \lfloor d(\ell, a)/2 \rfloor$ in $O(\log n)$ steps using precomputed jumps from LCA. Let x be the vertex at distance t from a .

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.
- ▶ If $d(\ell, a) = d(\ell, b)$, then the resulting set is just $\{\ell\}$.
- ▶ If $d(\ell, a) > d(\ell, b)$, then the result lies on the path from a to ℓ .
- ▶ To find the central vertices of the path, jump from a to ℓ to distance $t = \lfloor d(\ell, a)/2 \rfloor$ in $O(\log n)$ steps using precomputed jumps from LCA. Let x be the vertex at distance t from a .
- ▶ Distinguish the case when the vulnerability set contains one or two vertices based on parity of $d(a, b)$. Even – $\{x\}$, odd – $\{x, p(x)\}$ ($p(x)$ is the parent of x).

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.
- ▶ If $d(\ell, a) = d(\ell, b)$, then the resulting set is just $\{\ell\}$.
- ▶ If $d(\ell, a) > d(\ell, b)$, then the result lies on the path from a to ℓ .
- ▶ To find the central vertices of the path, jump from a to ℓ to distance $t = \lfloor d(\ell, a)/2 \rfloor$ in $O(\log n)$ steps using precomputed jumps from LCA. Let x be the vertex at distance t from a .
- ▶ Distinguish the case when the vulnerability set contains one or two vertices based on parity of $d(a, b)$. Even – $\{x\}$, odd – $\{x, p(x)\}$ ($p(x)$ is the parent of x).
- ▶ The case $d(\ell, b) > d(\ell, a)$ is symmetric.

Watchcats - what about the vulnerability sets?

- ▶ Naively in $O(n)$ per each mouse. Worst case $\Omega(nq)$ – too slow.
- ▶ Build LCA! Suppose that a, b is a pair of lairs for some mouse and let $\ell = \text{lca}(a, b)$.
- ▶ If $d(\ell, a) = d(\ell, b)$, then the resulting set is just $\{\ell\}$.
- ▶ If $d(\ell, a) > d(\ell, b)$, then the result lies on the path from a to ℓ .
- ▶ To find the central vertices of the path, jump from a to ℓ to distance $t = \lfloor d(\ell, a)/2 \rfloor$ in $O(\log n)$ steps using precomputed jumps from LCA. Let x be the vertex at distance t from a .
- ▶ Distinguish the case when the vulnerability set contains one or two vertices based on parity of $d(a, b)$. Even – $\{x\}$, odd – $\{x, p(x)\}$ ($p(x)$ is the parent of x).
- ▶ The case $d(\ell, b) > d(\ell, a)$ is symmetric.
- ▶ Total running time: $O(n \log n + q \log n + n) = O((n + q) \log n)$.

Watchcat Jiskra



Cowpproximation



Cowpproximation


- ▶ **Input:** Set of N circles, given by x, y and radius r .
- ▶ **Task:** Suppose each circle can travel with speed up to 1 unit of distance per second. In how many seconds can all circles contain a common point?

Cowpproximation

- ▶ **Combinatorial solution:**
- ▶ **Observation:** We can assume each circle moves at maximum speed and waits at some point if needed.
- ▶ Note after t seconds, a circle with radius r can cover exactly the points that are within radius $r + t$.
- ▶ We look for minimum t such that if we increase all radii by t , all circles have non-empty intersection.
- ▶ Binary search on t .


Cowpproximation

- ▶ Verify if the set of circles has nonempty intersection:
- ▶ Consider a circle C . If the common intersection contains the boundary of C , we can find it as follows.
- ▶ The intersections with C give us intervals on the boundary of C .



Cowpproximation

- ▶ Verify if the set of circles has nonempty intersection:
- ▶ Consider a circle C . If the common intersection contains the boundary of C , we can find it as follows.
- ▶ The intersections with C give us intervals on the boundary of C .



Cowpproximation

- ▶ **Observation:** Consider function $f(x, y) = \max_{C \in \text{circles}} \text{dist}((x, y), C)$.
- ▶ The minimum of this function is the solution.
- ▶ This function is convex.
- ▶ Well implemented gradient descend may find the solution quickly.

Reptile eggs



Reptile eggs

- ▶ **Input:** Text s and a regular expression r .
- ▶ **Output:** Find the size of the longest subsequence of s that is matched with r .

Reptile eggs

- ▶ **Input:** Text s and a regular expression r .
- ▶ **Output:** Find the size of the longest subsequence of s that is matched with r .

Use dynamic programming!

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

- ▶ $M[q, i]$ — the longest subsequence on the first i characters of s . (Memory table)

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

- ▶ $M[q, i]$ — the longest subsequence on the first i characters of s . (Memory table)
- ▶ Let $B(q)$ be a function that is 0 if q is the starting state and $-\infty$ otherwise.

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

- ▶ $M[q, i]$ — the longest subsequence on the first i characters of s . (Memory table)
- ▶ Let $B(q)$ be a function that is 0 if q is the starting state and $-\infty$ otherwise.
- ▶ $M[q, 0] = B(q)$

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

- ▶ $M[q, i]$ — the longest subsequence on the first i characters of s . (Memory table)
- ▶ Let $B(q)$ be a function that is 0 if q is the starting state and $-\infty$ otherwise.
- ▶ $M[q, 0] = B(q)$
- ▶ Let Q' be all the possible states q' such that reading character s_i advances A to state q and $1 \leq i \leq |s|$:

$$M[q, i] = \max(M[q, i - 1], \max_{q' \in Q'}(M[q', i - 1] + 1))$$

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

- ▶ $M[q, i]$ — the longest subsequence on the first i characters of s . (Memory table)
- ▶ Let $B(q)$ be a function that is 0 if q is the starting state and $-\infty$ otherwise.
- ▶ $M[q, 0] = B(q)$
- ▶ Let Q' be all the possible states q' such that reading character s_i advances A to state q and $1 \leq i \leq |s|$:

$$M[q, i] = \max(M[q, i - 1], \max_{q' \in Q'}(M[q', i - 1] + 1))$$

Output maximum number such that $M[q_f, i]$ is maximized and nonnegative, where q_f is a final state. If no such pair of q_f and i does not exist, output -1 .

Reptile eggs

Let A be the automaton accepting the set of strings described by r .

- ▶ $M[q, i]$ — the longest subsequence on the first i characters of s . (Memory table)
- ▶ Let $B(q)$ be a function that is 0 if q is the starting state and $-\infty$ otherwise.
- ▶ $M[q, 0] = B(q)$
- ▶ Let Q' be all the possible states q' such that reading character s_i advances A to state q and $1 \leq i \leq |s|$:

$$M[q, i] = \max(M[q, i - 1], \max_{q' \in Q'}(M[q', i - 1] + 1))$$

Output maximum number such that $M[q_f, i]$ is maximized and nonnegative, where q_f is a final state. If no such pair of q_f and i does not exist, output -1 .

Alternatively, the automaton can be represented implicitly by the regular expression. In such case it is enough to consider a position inside the regex instead of a state in the Automaton.

Pigpartite giraffe



Pigpartite giraffe

- ▶ **Input:** Small bipartite graph ($n \leq 8$ vertices in each partite).
- ▶ **Queries:** Given vertices v, u , add a new x vertex with neighborhood $N(x) = (N(v) \setminus N(u)) \cup (N(u) \setminus N(v))$.
- ▶ **Task:** After each query, compute the total sum of distances within the graph.
- ▶ Consider the incidence matrix of the graph. The query corresponds to taking a XOR of two rows (equivalently sum mod 2).

Pigpartite giraffe

- ▶ Each vertex can be described by the set of its original ancestors (the original 8 vertices in its partite).
- ▶ Only 2^8 possible types of vertices in each partite, hence $2 \cdot 2^8$ different type of vertices in total.
- ▶ Two vertices of the same type have the same neighborhood.
- ▶ **Observation:** Adding a new vertex of an existing type will not change distances between other vertices.

Pigpartite giraffe

Adjacency matrix of a bipartite graph G looks like

$$\mathbf{G} = \begin{array}{c|cc} & A & B \\ \hline A & 0 & \mathbf{M} \\ B & \mathbf{M}^T & 0 \end{array}$$

So \mathbf{M} describes our bipartite graph: rows for partite A , columns for partite B .

$$\mathbf{M}_{v,u} = 1 \iff v \in A, u \in B \text{ have an edge.}$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|cccc} (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ (3) & 0 & 0 & 1 & 0 \\ (4) & 0 & 0 & 0 & 1 \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|cccc} (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ \hline (3) & 1 & 0 & 1 & 0 \\ (4) & 1 & 0 & 0 & 1 \\ \hline (3 \oplus 4) & 0 & 0 & 1 & 1 \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|cccc} (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \\ \hline (4) & 1 & 0 & 0 & 1 \\ (3 \oplus 4) & 0 & 0 & 1 & 1 \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|ccccc} (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \\ \hline (4) & 1 & 0 & 0 & 1 \\ (3 \oplus 4) & 0 & 0 & 1 & 1 \\ \hline (3 \oplus 4 \oplus 4 = 3) & 1 & 0 & 1 & 0 \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|cccc} (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \\ (4) & 1 & 0 & 0 & 1 \\ (3 \oplus 4) & 0 & 0 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|cccc} (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \\ (4) & 1 & 0 & 0 & 1 \\ (3 \oplus 4) & 0 & 0 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \\ (\bigoplus_{i \in S \subseteq \{1,2,3,4\}} i) & \cdot & \cdot & \cdot & \cdot \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|cccc} & (1) & (2) & (3) & (4) \\ \hline (1) & 1 & 0 & 0 & 0 \\ (2) & 1 & 1 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \\ (4) & 1 & 0 & 0 & 1 \\ (3 \oplus 4) & 0 & 0 & 1 & 1 \\ (3) & 1 & 0 & 1 & 0 \end{array} \right)$$

Pigpartite giraffe

$$\mathbf{M} = \left(\begin{array}{c|ccccc} & (1) & (2) & (3) & (4) & (1 \oplus 2) \\ \hline (1) & 1 & 0 & 0 & 0 & 1 \\ (2) & 1 & 1 & 1 & 1 & 0 \\ (3) & 1 & 0 & 1 & 0 & 1 \\ (4) & 1 & 0 & 0 & 1 & 1 \\ (3 \oplus 4) & 0 & 0 & 1 & 1 & 0 \\ (3) & 1 & 0 & 1 & 0 & 1 \end{array} \right)$$

Pigpartite giraffe

- ▶ How to efficiently compute the distances?
- ▶ First compute pair-wise distances and keep the distance matrix D ($O(n^3)$).
- ▶ Keep D small by keeping only one vertex for each type.
- ▶ Keep the count for each type.
- ▶ We will keep at most $d \leq 2 \cdot 2^n$ vertices in D .
- ▶ Also keep track of the total distances for each vertex of D .

Pigpartite giraffe

- ▶ When adding a new vertex v :
- ▶ If v has a **new type**:
 - ▶ Compute the distance from v to all others with BFS ($O(d^2)$).
 - ▶ Update D for all other vertices: for each pair $x, y \in V$, check if $dist(x, v) + dist(v, y) < dist(x, y)$ ($O(d^2)$).
- ▶ If v has an **existing type**:
 - ▶ Just update the count of v 's type.
 - ▶ Sum the distances from each vertex ($O(d)$).
 - ▶ Be careful about vertices of the same type as v ! Especially if v is just the second vertex of that type.
- ▶ A new type appears at most $2 \cdot 2^n$ times.
- ▶ Let's evaluate the total runtime.
- ▶ $O(n^3 + 2^n d^2 + Qd)$ with $d = O(2^n)$.
- ▶ $O(n^3 + 2^{3n} + Q2^n)$ with $n \leq 8, Q \leq 10^5$.
- ▶ $\approx 2^9 + 2^{24} + 2^{25}$