

Control Challenges: Solutions

Iacopo Moles

Table of contents

1	Introduction	3
1.1	What is this?	3
2	Block With Friction	4
2.1	State Space representation	4
2.2	Pole Placement	5
2.3	Simulation	7

1 Introduction

1.1 What is this?

This is a collection of write ups on how to solve the various problems presented by [Github user "Janismac"](#).

$$\dot{x} = \mathbf{A}x$$

2 Block With Friction

Position Control with friction. Using Pole Placement + PD.

2.1 State Space representation

We can convert the set of ODE into a state space representation. The final bode plot of the block position is:

```
using DiscretePIDs, ControlSystems, Plots, LinearAlgebra

# System parameters
Ts = 0.02 # sampling time
Tf = 2.5; #final simulation time
g = 9.81 #gravity
α = 0.0 # slope
μ = 1.0 # friction coefficient
x_0 = -2.0 # starting position
dx_0 = 0.0 # starting velocity
τ = 20.0 # torque constant

# State Space Matrix
A = [0 1 0
     0 -μ 1
     0 0 -τ];
B = [0
     0
     τ];
C = [1 0 0
     0 1 0];

sys = ss(A, B, C, 0.0) # Continuous

plot!(bodeplot(tf(sys)), pzmap(tf(sys)))
```




Figure 2.1: Starting Bode Plot and PZ Map

It has the shape we expect from a motor + friction. Slow pole for the mass + friction and a faster pole for the current & inductance.

Numerically they are:

```
display(eigvals(A))
```

3-element Vector{Float64}:

```
-20.0
-1.0
0.0
```

We see that we start with all the pole in the left-half plane, which is good.

2.2 Pole Placement

We can design a controller with pole placement.


For some reason pole placement doesn't work for the observer, I use a Kalman Filter with random fast values.

```
observability(A, C).isobservable &  
controllability(A, B).iscontrollable; #OK  
  
 $\varepsilon$  = 0.01;  
pp = 15.0;  
poles_cont = -2.0 * [pp +  $\varepsilon$ , pp -  $\varepsilon$ , pp];  
L = real(place(sys, poles_cont, :c));  
  
poles_obs = poles_cont * 5.0;  
K = place(1.0 * A', 1.0 * C', poles_obs)'  
cont = observer_controller(sys, L, K; direct=false);
```

We can check the effect of the new controller on the loop

```
closedLoop = feedback(sys * cont)  
print(poles(closedLoop));  
setPlotScale("dB")  
plot!(bodeplot(closedLoop[1, 1], 0.1:40), pzmap(closedLoop))
```

```
ComplexF64[-29.980000105166976 + 0.0im, -29.999999789554334 + 0.0im, -  
30.020000105278555 + 0.0im, -150.00000000000009 + 0.0im, -150.09999999988327  
149.900000000010167 + 0.0im]
```



We can compare this to the open-loop response in @start-bode. We can see that we achieve unitary gain throughout the whole low-frequency range.

We can convert the pole placement controller into the standard PD gain form.

```
K = L[1];
Ti = 0;
Td = L[2] / L[1];
pid = DiscretePID(; K, Ts, Ti, Td);
```

2.3 Simulation

We can simulate this with a motor that only outputs the position:

```
sysreal = ss(A, B, [1 0 0], 0.0)
ctrl = function (x, t)
    y = (sysreal.C*x)[] # measurement
    d = 0 * [1.0] # disturbance
    r = 2.0 * (t ≥ 1) # reference
    # u = pid(r, y) # control signal
```


```

# u + d # Plant input is control signal + disturbance
# u =1
e = x - [r; 0.0; 0.0]
e[3] = 0.0 # torque not observable, just ignore it in the final feedback
u = -L * e + d
u = [maximum([-20.0 minimum([20.0 u]))])]
end
t = 0:Ts:Tf

res = lsim(sysreal, ctrl, t)


display(plot(res,
    plotu=true,
    plotx=true,
    ploty=false
))
ylabel!("u", sp=1);
ylabel!("x", sp=2);
ylabel!("v", sp=3);
ylabel!("T", sp=4);

```



For more stats:


```
si = stepinfo(res);  
plot(si);title!("Step Response")
```



We can also simulate it in a SIMULINK-like environment:

```
using FMI, DifferentialEquations  
fmuPath = abspath(joinpath(@__DIR__,  
    "..",  
    "modelica",  
    "ControlChallenges",  
    "ControlChallenges.BlockOnSlope_Challenges.Examples.WithFriction.fmu"))  
fmu = loadFMU(fmuPath);  
simData = simulateME(  
    fmu,  
    (0.0, 5.0);  
    recordValues=["blockOnSlope.x",  
        "blockOnSlope.xd",  
        "blockOnSlope.usat"],  
    showProgress=false);
```

```
unloadFMU(fmu);  
plot(simData, states=false, timeEvents=false)
```



There is a slight difference between the `lsim` simulation and the FMU simulation. I need to recheck some stuff.