



Continuous integration (CI)

DETI-UA/TQS

Ilídio Oliveira (ico@ua.pt)

v2019-04-09

Continuously integrating the “units”

The essence of it lies in the simple practice of everyone on the team integrating frequently.


spot errors earlier
shared code ownership
everybody is co-responsible

big, unpredictable effort to integrate
app state is not executable most of the time



integrate early
and often

Integration hell



<https://insights.sei.cmu.edu/devops/2015/01/continuous-integration-in-devops-1.html>



Continuous integration practice

1. Developers commit to a shared repository **regularly**
2. Changes in SCM are observed and trigger **automatically builds**
3. Immediate feedback on build failure (broken builds have high-priority)
4. Optional: deploy of artifacts into a reference repository
5. Optional: trigger deployment for integration/acceptance tests
6. Sharing repositories.

CI makes the development process smoother and less risky

- ▶ ↓ “it runs on my computer”
- ▶ Early detection of failures



Continuous... confusion

Continuous Delivery

sw development discipline where you build software in such a way that it **can be released** to production at any time.

You're doing continuous delivery when:

- ▶ Focus on quality of working software
- ▶ Your software is deployable throughout its lifecycle
- ▶ Your team prioritizes keeping the software deployable over working on new features
- ▶ Anybody can get fast, automated feedback on the production readiness

Continuous Deployment/release

every change goes through the pipeline and **automatically gets put** into production.


- ▶ Focus on speed and agility to deploy to production

Continuous Integration



Automatically integrating, building, and testing code within the development environment.




Related (yet different) terms



You are able to do frequent deployments but may choose not to do it (usually related to businesses strategy)



Continuous delivery




The build process

A build has several stages (goals in Maven terms).

A successful build implies success in code correctness and quality checks.

Automatic build tools run quality checks (e.g.: unit testing, code inspections)

Not just compiling...



"Continuous" building: the build process

Build process is a series of steps that transforms the various project components in an application ready to be deployed

Build instructions are outlined in one or more description files

- ▶ e.g.: POM.xml

INPUT

- ▶ the source-code, test code, dependencies, the documentation, etc.


OUTPUT

- ▶ the executable files, the user documentation, packaged libraries, reporting (e.g.: test results)



Key component: build tool

- Maven is a modular automation system built around 4 main elements



- input: project src/resources + POM
- output: tested and packaged artifact

Maven lifecycle

- Default life cycle

`validate`
`generate-sources`
`process-resources`
`compile`
`test-compile`
`test`
`package`
`integration-test`
`verify`
`install`
`deploy`

– (some skipped for clarity)

- Every goal implies all the previous ones

`mvn compile`

– actually executes

`validate`
`generate-sources`
`process-resource`
`compile`


- Stand-alone goals

`mvn scm:update`




Role of (dependencies) repositories

Efficiently sharing and caching binaries
e.g.: JFrog Artifactory



Components of an integration system



Generic workflow

- 1- Checkout (or update) from SCM
- 2- Code a new feature
- 3- Run automated build on local machine
 - ▶ Repeat #2 and #3 till tests pass
- 4- Merge local copy with latest changes from SCM
 - ▶ Fix and rebuild till tests pass
- 5- Commit (integrate with “central”)
- 6- Run a build on a clean machine
 - ▶ Immediately fix bugs and integration issues

Not only tools: CI culture required!



Fowler's 10 CI practices

1. Maintain a Single Source Repository.
2. Automate the Build
3. Make Your Build Self-Testing
4. Everyone Commits To the Mainline Every Day
5. Every Commit Should Build the Mainline on an Integration Machine
6. Keep the Build Fast
7. Test in a Clone of the Production Environment
8. Make it Easy for Anyone to Get the Latest Executable
9. Everyone can see what's happening
10. Automate Deployment

<http://martinfowler.com/articles/continuousIntegration.html>



CI culture

CI is a toolset and a mindset

- ▶ Broken builds are high-priority
- ▶ No manual steps in the build process
- ▶ Everybody must supply the CI with good tests



See also: <https://plugins.jenkins.io/build-monitor-plugin>



Continuous feedback

The most frequent the integration process is, the less painful

Errors are easier to detect in an earlier stage, near the point where they have been introduced:

- ▶ The detection mechanism of such bugs becomes simpler because the natural step in diagnosing the problem is to check what was the latest submitted change.
- ▶ **problems followed by atomic commits are easiest to correct than to fix several problems at once, after bulk commits**

There must be an effective mechanism that automatically informs programmers, testers, database administrators and managers about the status of the build

Feedback aims to → generate reaction in a more accurate and faster way



Continuous testing

Quality checks at all system levels and involve all individuals, not just the elements of the QA team


Most of the tests can be automated and should be run in the CI pipeline to be carried out repeatedly:

- ▶ unit testing, integration testing, regression testing, system testing, load and performance testing, etc.


Build tools can take a crucial role on automating tests



Integration tests



Related technologies



<https://www.jfrog.com/artifactory/>



Jenkins



Easy of use and extremely extensible

- ▶ Plugins-oriented

Hosted

- ▶ vs cloud-centric

Distributed builds

- ▶ Master/slaves architecture

Jenkins vocabulary

- ▶ Job: a runnable task
- ▶ Node: a master or slave machine
- ▶ Build
- ▶ Executor: a stream of builds to run
- ▶ Plugin: module that extends the core functionality.
- ▶ Pipeline: definition of the steps to be executed



Jenkins supports building Java projects since its inception, and for a reason! It's both the language Jenkins is written in, plus the language in use by many if not all the projects Kohsuke Kawaguchi wanted to watch out when he created the tool many years ago.

If you want to build a Java project, there are a bunch of different options. The most typical ones nowadays are generally Apache Maven, or Gradle.

Apache Maven

In any FreeStyle job, as **currently** Maven is supported in standard, you can use the dedicated step. One advantage is, as for all Jenkins tools, that you can select a specific Maven version and have Jenkins automatically install it on the build node it's going to run on.

image::/images/solution-images/jenkins-maven-step.png

Gradle

As the associated plugin is not installed by default, first install the [Gradle plugin](#). Once done, you should be able to add a Gradle step.

image::/images/solution-images/jenkins-gradle-step.png

Java plugins for Jenkins



JUnit plugin

publishes JUnit XML formatted test reports for trending and analysis



Gradle plugin

support invoking Gradle as a build step and listing executing tasks per build



Findbugs plugin

generate trending and analysis for FindBugs reports



PMD plugin

generate trending and analysis for PMD reports



Cobertura plugin

publish and trend code coverage reports from Cobertura



SonarQube plugin

integrate reporting from the SonarQube code quality/inspection platform



Repository Connector plugin

adds features for resolving artifacts from a Maven repository such as Nexus or Artifactory.

→ <https://jenkins.io/solutions/java/>



Pipeline as Code with Jenkins



The default interaction model with Jenkins, historically, has been very web UI driven, requiring users to manually create jobs, then manually fill in the details through a web browser. This requires additional effort to create and manage jobs to test and build multiple projects, it also keeps the configuration of a job to build/test/deploy separate from the actual code being built/tested/deployed. This prevents users from applying their existing CI/CD best practices to the job configurations themselves.

Jenkins ♥ Continuous Delivery Articles

[Multibranch Workflows in Jenkins](#)
[jenkins-ci.org](#)

Continuous Delivery

Pipeline


With the introduction of the Pipeline plugin, users can define a build/test/deploy pipeline in a `Jenkinsfile` and store that as another piece of code checked into source control.

A continuous delivery (CD) pipeline is an automated expression of your process for getting software from version control right through to your users and customers. Every change to your software (committed in source control) goes through a complex process on its way to being released.

Pipeline provides an extensible set of tools for modeling simple-to-complex delivery pipelines "as code" via the Pipeline domain-specific language (DSL) syntax.



Jenkins pipelines




```

pipeline {
    agent {
        docker {
            image 'maven:3-alpine'
            args '-v /root/.m2:/root/.m2'
        }
    }
    options {
        skipStagesAfterUnstable()
    }
    stages {
        stage('Build') {
            steps {
                sh 'mvn -B -DskipTests clean package'
            }
        }
        stage('Test') {
            steps {
                sh 'mvn test'
            }
            post {
                always {
                    junit 'target/surefire-reports/*.xml'
                }
            }
        }
        stage('Deliver') { ❶
            steps {
                sh './jenkins/scripts/deliver.sh' ❷
            }
        }
    }
}

```

```

pipeline {
    agent any
    stages{
        stage('Build'){
            steps {
                sh 'mvn clean package'
            }
            post {
                success {
                    echo 'Now Archiving...'
                    archiveArtifacts artifacts: '**/target/*.war'
                }
            }
        }
        stage ('Deploy to Staging'){
            steps {
                build job: 'Deploy-to-staging'
            }
        }
        stage ('Deploy to Production'){
            steps{
                timeout(time:5, unit:'DAYS'){
                    input message:'Approve PRODUCTION Deployment?'
                }

                build job: 'Deploy-to-Prod'
            }
            post {
                success {
                    echo 'Code deployed to Production.'
                }
                failure {
                    echo ' Deployment failed.'
                }
            }
        }
    }
}

```



[Pages](#) / [Home](#) / [Use Jenkins](#)

 Edit

☆ Save for later

Remote access API

Created by Kohsuke Kawaguchi, last modified by Joshua Shinn less than a minute ago

Jenkins provides machine-consumable remote access API to its functionalities. Currently it comes in three flavors:

1. XML
2. JSON with JSONP support
3. Python

Remote access API is offered in a REST-like style. That is, there is no single entry point for all features, and instead it is a ".../api/" URL where "..." portion is the data that it acts on.

For example, if your Jenkins installation sits at <http://ci.jruby.org/>, visiting <http://ci.jruby.org/api/> will show just the top-level primarily a listing of the configured jobs for this Jenkins instance.

Or if you want to access information about a particular build, e.g. <http://ci.jruby.org/job/jruby-base/lastSuccessfulBuild/> and you'll see the list of functionalities for that build.

The work on this front is ongoing, so if you find missing features, please file an issue.


What can you do with it?


Remote API can be used to do things like these:

1. retrieve information from Jenkins for programmatic consumption.
2. trigger a new build
3. create/copy jobs



Sample scenario (for projects)





smartcode Search Services [Jenkins]

localhost:8080/jenkins/view/Search%20Services/

Search Services

Librarian

Claimed by Alice Jenkins: There's a bunch of flaky tests that keep breaking. Fixing it now.

1.5.0+build.18.sha.7d22a8 19s | 25s

Librarian Acceptance

v1.5.0, run #3

Performance Benchmark

#1 1m 13s

Promote to PROD

#2 1m 2s

Promote to UAT

Identified Problems: Invalid credentials

#12 22s | 2m 7s

Search API Contract Tests (PROD)

#1 17s

Search API Contract Tests (UAT)

#2 37s

Settings

Font Size: 0.5 1.0 2.0

Columns: 1 2

☒ Colour blind mode?

Add/Remove Jobs

Done

Brought to you by Jan Molak

More to explore

Books on Continuous integration:

- ▶ Duvall's Continuous Integration:
<http://www.amazon.com/Continuous-Integration-Improving-Software-Reducing/dp/0321336380>
- ▶ Humble's "Continuous Delivery":
<http://www.amazon.com/Continuous-Delivery-Deployment-Automation-Addison-Wesley/dp/0321601912>

Hudson/Jenkins

- ▶ Extensive information:
<http://www.youtube.com/watch?v=6k0S4O2PnTc#!>

Maven:

- ▶ Free ebook: <http://www.sonatype.com/books/mvnref-book/reference/public-book.html>

