

Class 13: Transcriptomics and the analysis of RNA-Seq data

Idara Ibekwe: A16865157

The data for today's lab comes from a published RNA-seq experiment where airway smooth muscle cells were treated with dex.

Import Data

We need two things for this analysis

```
counts <- read.csv("airway_scaledcounts.csv", row.names=1)
metadata <- read.csv("airway_metadata.csv")
```

```
head(counts)
```

	SRR1039508	SRR1039509	SRR1039512	SRR1039513	SRR1039516
ENSG000000000003	723	486	904	445	1170
ENSG000000000005	0	0	0	0	0
ENSG000000000419	467	523	616	371	582
ENSG000000000457	347	258	364	237	318
ENSG000000000460	96	81	73	66	118
ENSG000000000938	0	0	1	0	2
	SRR1039517	SRR1039520	SRR1039521		
ENSG000000000003	1097	806	604		
ENSG000000000005	0	0	0		
ENSG000000000419	781	417	509		
ENSG000000000457	447	330	324		
ENSG000000000460	94	102	74		
ENSG000000000938	0	0	0		

```
head(metadata)
```

	id	dex	celltype	geo_id
1	SRR1039508	control	N61311	GSM1275862
2	SRR1039509	treated	N61311	GSM1275863
3	SRR1039512	control	N052611	GSM1275866
4	SRR1039513	treated	N052611	GSM1275867
5	SRR1039516	control	N080611	GSM1275870
6	SRR1039517	treated	N080611	GSM1275871

Q1. How many genes are in this dataset?

```
nrow(counts)
```

```
[1] 38694
```

Q2. How many 'control' cell lines do we have

```
table(metadata$dex)
```

```
control treated
      4      4
```

##Examine Data

```
colnames(counts)
```

```
[1] "SRR1039508" "SRR1039509" "SRR1039512" "SRR1039513" "SRR1039516"
[6] "SRR1039517" "SRR1039520" "SRR1039521"
```

```
metadata$id
```

```
[1] "SRR1039508" "SRR1039509" "SRR1039512" "SRR1039513" "SRR1039516"
[6] "SRR1039517" "SRR1039520" "SRR1039521"
```

```
all(c(T,T,T,F))
```

```
[1] FALSE
```

```
all(colnames(counts)==metadata$id)
```

```
[1] TRUE
```

```
##Analysis
```

I want to start by comparing “control” and “treated” columns. I need to find the average for each gene (row) in all “control” columns. Then find the average in the treated columns and compare. This is to measure gene expression.

Let’s do “control” column first.

```
control.inds <- metadata$dex == "control"
```

```
control.counts <- counts[,control.inds]
```

Now find the mean count value per gene using the `apply()` function.

```
control.mean <- apply(control.counts, 1, mean)
```

Now do the same for the “treated” columns. i.e. find `treated.mean` values.

```
treated.inds <- metadata$dex == "treated"
```

```
treated.counts <- counts[,treated.inds]
```

```
treated.mean <- apply(treated.counts, 1, mean)
```


Put it all together

```
meancounts <- data.frame(control.mean, treated.mean)
head(meancounts)
```

	control.mean	treated.mean
ENSG000000000003	900.75	658.00
ENSG000000000005	0.00	0.00
ENSG000000000419	520.50	546.00
ENSG000000000457	339.75	316.50
ENSG000000000460	97.25	78.75
ENSG000000000938	0.75	0.00

Now we will plot this data to compare our control vs. treated


```
plot(meancounts)
```



```
plot(meancounts, log="xy")
```

Warning in xy.coords(x, y, xlabel, ylabel, log): 15032 x values <= 0 omitted from logarithmic plot

Warning in xy.coords(x, y, xlabel, ylabel, log): 15281 y values <= 0 omitted from logarithmic plot



Still a lot of overplotting here. How can this be improved?

```
log(10, base=2)
```

```
[1] 3.321928
```

```
log2(10/10)
```

```
[1] 0
```

```
log2(20/10)
```

```
[1] 1
```

```
log2(10/20)
```

```
[1] -1
```

```
log2(40/10)
```

```
[1] 2
```

We most often work in lg2 units because they have a more intuitive interpretation

Here we calculate the log2 Fold change of treated/control values and add it to our wee data frame results

```
meancounts$log2fc <- log2(meancounts$treated.mean/ meancounts$control.mean)
head(meancounts)
```

	control.mean	treated.mean	log2fc
ENSG000000000003	900.75	658.00	-0.45303916
ENSG000000000005	0.00	0.00	NaN
ENSG000000000419	520.50	546.00	0.06900279
ENSG000000000457	339.75	316.50	-0.10226805
ENSG000000000460	97.25	78.75	-0.30441833
ENSG000000000938	0.75	0.00	-Inf

There are some funky answers in here like NaN (Not a number) and -Inf(minus infinity) that occur because I have zero count genes in my dataset.

It is common practice to filter the zero count genes out.

```
to.keep.inds <- apply(meancounts[,1:2] == 0, 1, sum) == 0

mycounts <- meancounts[to.keep.inds,]
head(mycounts)
```

	control.mean	treated.mean	log2fc
ENSG000000000003	900.75	658.00	-0.45303916
ENSG000000000419	520.50	546.00	0.06900279
ENSG000000000457	339.75	316.50	-0.10226805
ENSG000000000460	97.25	78.75	-0.30441833
ENSG000000000971	5219.00	6687.50	0.35769358
ENSG000000001036	2327.00	1785.75	-0.38194109

Q. how many genes do we have left after zero count filtering?

```
nrow(mycounts)
```

```
[1] 21817
```

A common threshold for calling a gene “up” or “down” is a log2 fold change of +2 or -2

Q. How many “up” regulated genes do we have

```
sum(mycounts$log2fc >= +2)
```

```
[1] 314
```

Q. What about downregulated?

```
sum(mycounts$log2fc <= -2)
```

```
[1] 485
```

##DESeq analysis

We need to do this analysis properly because we are missing some stats.

```
library(DESeq2)
```

To use DESeq we need to get our input data in a very particular format.

```
dds <- DESeqDataSetFromMatrix(countData = counts,  
                               colData = metadata,  
                               design = ~dex)
```

converting counts to integer mode

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

Run DESeq analysis

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

Get the results

```
res <- results(dds)
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG0000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG0000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG0000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG0000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj				
	<numeric>				
ENSG000000000003	0.163035				
ENSG000000000005	NA				
ENSG0000000000419	0.176032				
ENSG0000000000457	0.961694				
ENSG0000000000460	0.815849				
ENSG0000000000938	NA				

I want to make a figure showing an overview of all my results. A plot of **log2 fold change** vs the **p-value**(adjusted p-value)


```


mycols <- rep("gray", nrow(res))
mycols[ abs(res$log2FoldChange) > 2 ] <- "purple"

inds <- (res$padj < 0.01) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj),
      col=mycols, ylab="-Log(P-value)", xlab="Log2(FoldChange)" )

abline(v=-2, col="gray")
abline(v=+2, col="gray")
abline(h=-log(0.05), col="gray")

```



```
log(0.5)
```

```
[1] -0.6931472
```

```
log(.0000005)
```

```
[1] -14.50866
```

```
##Add annotation data
```

We want to add on gene symbols(i.e. gene names) as well as other common identifiers from major databases for all our genes of interest.

```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

Here we can translate between the following:

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj				
	<numeric>				
ENSG000000000003	0.163035				
ENSG000000000005	NA				
ENSG000000000419	0.176032				
ENSG000000000457	0.961694				

```
ENSG000000000460 0.815849
ENSG000000000938 NA
```

My Ids are in the rownames(res)

```
res$symbol <- mapIds(org.Hs.eg.db,
                      keys=row.names(res), # Our genenames
                      keytype="ENSEMBL",   # The format of our genenames
                      column="SYMBOL",     # The new format we want to add
                      multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 7 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029

	padj	symbol
	<numeric>	<character>
ENSG000000000003	0.163035	TSPAN6
ENSG000000000005	NA	TNMD
ENSG000000000419	0.176032	DPM1
ENSG000000000457	0.961694	SCYL3
ENSG000000000460	0.815849	FIRRM
ENSG000000000938	NA	FGR

We also want “GENENAME” and “ENTREZID”

```
res$genename <- mapIds(org.Hs.eg.db,
                        keys=row.names(res), # Our genenames
                        keytype="ENSEMBL",   # The format of our genenames
```

```

column="GENENAME",          # The new format we want to add
multiVals="first")

```

'select()' returned 1:many mapping between keys and columns

```

res$entrez <- mapIds(org.Hs.eg.db,
  keys=row.names(res), # Our genenames
  keytype="ENSEMBL",   # The format of our genenames
  column="ENTREZID",   # The new format we want to add
  multiVals="first")

```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj	symbol		genename	entrez
	<numeric>	<character>		<character>	<character>
ENSG000000000003	0.163035	TSPAN6		tetraspanin 6	7105
ENSG000000000005	NA	TNMD		tenomodulin	64102
ENSG000000000419	0.176032	DPM1	dolichyl-phosphate m..		8813
ENSG000000000457	0.961694	SCYL3	SCY1 like pseudokina..		57147
ENSG000000000460	0.815849	FIRRM	FIGNL1 interacting r..		55732
ENSG000000000938	NA	FGR	FGR proto-oncogene, ..		2268

Let's save our results to a new CSV file

```
write.csv(res, file= "myresults.csv")
```

##Pathway Analysis

Here we will use the “gage” to do some pathway analysis

```
library(pathview)
library(gage)
library(gageData)
```

Have a wee peak at KEGG data

```
data(kegg.sets.hs)

# Examine the first 2 pathways in this kegg set for humans
head(kegg.sets.hs, 2)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"
```

To run gage we need to provide it with a vector of fold-change values(not our big results table)

```
foldchanges <- res$log2FoldChange
#foldchanges
```

Add ENTREZ ids as names to my foldchanges vector

```
names(foldchanges) <- res$entrez
head(foldchanges)
```

```
7105      64102      8813      57147      55732      2268
-0.35070302      NA  0.20610777  0.02452695 -0.14714205 -1.73228897
```

Now run **gage** with this input and the KEGG pathways

```
# Get the results
keggres = gage(foldchanges, gsets = kegg.sets.hs)
```

```
attributes(keggres)
```

```
$names
[1] "greater" "less"    "stats"
```

```
head(keggres$less)
```

	p.geomean	stat.mean
hsa05332 Graft-versus-host disease	0.0004250461	-3.473346
hsa04940 Type I diabetes mellitus	0.0017820293	-3.002352
hsa05310 Asthma	0.0020045888	-3.009050
hsa04672 Intestinal immune network for IgA production	0.0060434515	-2.560547
hsa05330 Allograft rejection	0.0073678825	-2.501419
hsa04340 Hedgehog signaling pathway	0.0133239547	-2.248547
	p.val	q.val
hsa05332 Graft-versus-host disease	0.0004250461	0.09053483
hsa04940 Type I diabetes mellitus	0.0017820293	0.14232581
hsa05310 Asthma	0.0020045888	0.14232581
hsa04672 Intestinal immune network for IgA production	0.0060434515	0.31387180
hsa05330 Allograft rejection	0.0073678825	0.31387180
hsa04340 Hedgehog signaling pathway	0.0133239547	0.47300039
	set.size	expl
hsa05332 Graft-versus-host disease	40	0.0004250461
hsa04940 Type I diabetes mellitus	42	0.0017820293
hsa05310 Asthma	29	0.0020045888
hsa04672 Intestinal immune network for IgA production	47	0.0060434515
hsa05330 Allograft rejection	36	0.0073678825
hsa04340 Hedgehog signaling pathway	56	0.0133239547

Let's have a look at the hsa05310 Asthma pathway with our genes highlighted using the `pathview()` function:

```
pathview(gene.data=foldchanges, pathway.id="hsa05310")
```

