

Enterprise Rect

28 March 2024

Q1. A React application is made up of _____.

- A. views
- B. components
- C. model
- D. function

Answer: C

Q2. Which file contains all of your app info, particularly the dependencies or modules that your app requires to run correctly?

- A. nuget.config
- B. package.json
- C. tsconfig.json
- D. index.html

Answer: B

Q3. Which command is used to view the list of dependencies?

- A. npm list
- B. npm list -g --depth 0
- C. npm init
- D. npm init -y

Answer: A

Q4. To generate a package.json file quickly, use

- A. npm init
- B. npm init --y
- C. npm install -g
- D. npm i -g

Answer: B

Q5. In package.json file, where packages used for development purposes are contained?

- A. scripts
- B. dependencies
- C. devDependencies
- D. dev

Answer: C

Q6. What should you do after cloning a project from a Git repository?

- A. Run npm install command
- B. Run npm init command
- C. Run npm list command
- D. Run npm start command

Answer: A

Q7. _____ in TypeScript serves as documentation itself.

- A. The .tsx file
- B. The .ts file
- C. The .jsx file
- D. The typing

Answer: D

Q8. What is the role of a react component?

- A. It provides a section or a piece of the user interface
- B. It provides a model data to a view
- C. It provides application logic
- D. It provide type definitions

Answer: A

Q9. What is the react virtual DOM?

- A. representation of a UI is kept in memory and synced with the “real” DOM
- B. representation of data kept in memory and changes are synced with UI
- C. representation of the states of UI elements
- D. None

Answer: A

Q9. Which command is used to create a react application?

- A. create-react-app
- B. npm run create-react-app
- C. npx run create-react-app
- D. ng create-react-app

Answer: C

[Currently, you don't need to install create-react-app]

Q10. Which command is used to create a react typescript app?

- A. npx create-react-app <name-of-your-app> -- typescript
- B. npx create-react-app <name-of-your-app> --template typescript
- C. npx create-react-app <name-of-your-app> --language typescript
- D. npx create-react-app <name-of-your-app> --type typescript

Answer: B

Q11. Which file in a react app includes the React code and React to render context?

- A. public/index.html
- B. src/index.html
- C. /index.html
- D. /src/main.tsx

Answer: A

Q12. What does a react component return?

- A. XML
- B. JavaScript
- C. JavaScript/XML (JSX)
- D. HTML

Answer: C

Q13. which one is not valid JSX in a functional components

- A.

```
export default function App() {  
  return (  
    <div>Some</div>  
    </div>Text</div>  
  )  
}
```
- B.

```
export default function App() {  
  return (  
    <div>  
      <div>Some</div>  
      </div>Text</div>  
    </div>  
  )  
}
```
- C.

```
export default function App() {  
  return (  
    <>  
      <div>Some</div>  
      </div>Text</div>  
    </>  
  )  
}
```
- D.

```
export default function App() {  
  return (  
    <div>Some</div>  
    </div>Text</div>  
  )  
}
```

```
<React.Fragment>
  <div>Some</div>
</div>Text</div>
</React.Fragment>
```

)

Answer: A

[Must return a single element]

Q14. Which one is used to pass data to a component?

- A. properties
- B. state
- C. useState
- D. props

Answer: D

Q15. You want to your component as below

```
<MyComponent title="Welcome" text="Content" />
```

How should you write your component?

- A.

```
type Data= {
  title: string;
  text: string;
}
export default function MyComponent= (props: Data)=> {
  let {title, text} = props;
  return (
    <>
      <div>{title}</div>
      <div>{text}</div>
    </>
  );
};
```
- B.

```
type Data= {
  title: string;
  text: string;
}
export default function MyComponent= (props)=> {
  const {title, text} = props;
  return (
    <>
      <div>{title}</div>
      <div>{text}</div>
    </>
  );
};
```
- C.

```
type Data= {
  title: string;
  text: string;
}
export function MyComponent= (props: Data)=> {
  const {title, text} = props;
  return (
    <>
      <div>{title}</div>
      <div>{text}</div>
    </>
  );
};
```
- D.

```
type Data= {
  title: string;
```

```

        text: string;
    }
    export default function MyComponent= (props: Data)=> {
    const {title, text} = Data;;
    return (
        <>
        <div>{title}</div>
        <div>{text}</div>
        </>
    );
}

```

Answer: C

Q16. Which object is used to pass properties to the function component?

- A. properties
- B. state
- C. useState
- D. props

Answer: D

Q17. What do you use in a react function component for state and other React features without writing a class?

- A. props
- B. react hooks
- C. redux
- D. All of the above

Answer: B

Q18. Which hook allows state variables in function components?

- A. useEffect
- B. useRef
- C. useState
- D. useVar

Answer: C

Q19. You want to maintain a state variable. Which code should you write?

- A. `const { title, setTitle} = useEffect ('Initial text')`
- B. `const { title, setTitle} = useState ('Initial text')`
- C. `const { title, setTitle} = useRef ('Initial text')`
- D. `const { title, setTitle} = state ('Initial text')`

Answer: B

Q20. Which one correctly sets the css style in jsx?

- A. `<div style="color: "#ff0000", fontSize: "18px">text</div>`
- B. `<div css="color: "#ff0000", fontSize: "18px">text</div>`
- C. `<div style={{color: "#ff0000", fontSize: "18px"}}>text</div>`
- D. `<div style={color: "#ff0000", fontSize: "18px"}>text</div>`

Answer: C

Q20. Which one correctly sets the css class in jsx?

- A. `<div class="red-text">text</div>`
- B. `<div classClass="red-text">text</div>`
- C. `<div className="red-text">text</div>`
- D. `<div name="red-text">text</div>`

Answer: C

Q21. Which code should you write if you want to run some code only once?

- A. `useEffect() => { //code..});`
- B. `useEffect() => { //code..}, []);`
- C. `useEffect() => { //code..}, [id, title]);`
- D. `useEffect() => { //code..}, {});`

Answer: B

Q22. Which code will run continuously on an infinite loop?

- A. `useEffect(() => { //code..});`
- B. `useEffect(() => { //code..}, []);`
- C. `useEffect(() => { //code..}, [id, title]);`
- D. `useEffect(() => { //code..}, {});`

Answer: A

Q23. Which hook allows side effects like fetching data, directly updating the DOM, and timers?

- A. `useEffect`
- B. `useRef`
- C. `useState`
- D. `useVar`

Answer: A

Q24. Which utility for constructing className strings conditionally?

- A. `Material-UI`
- B. `jest`
- C. `clsx`
- D. `Formik`

Answer: C

Q25. Which one is the from library?

- A. `Material-UI`
- B. `jest`
- C. `clsx`
- D. `Formik`

Answer: D

Q26. Which one is a JavaScript schema builder for value parsing and validation?

- A. `Material-UI`
- B. `Yup`
- C. `clsx`
- D. `Formik`

Answer: B

Q27. Which library is required for routing in reactjs?

- A. `react-dom`
- B. `react-router`
- C. `react-router-dom`
- D. `axios`

Answer: C

Q28. Which element is required to wrap root dom for routing?

- A. `Routes`
- B. `Route`
- C. `BrowserRouter`
- D. `Switch`

Answer: C

Q29. Which is the valid route to navigate to the ProductCatalog component?

- A. `<Route path={"/products"} component=HelloComponent/>`
- B. `<Route path={"/products"} component="HelloComponent"/>`
- C. `<Route path={"/products"} component={{<HelloComponent />}}/>`
- D. `<Route path={"/products"} component={HelloComponent}/>`

Answer: D

Q30. Which one correctly creates the hyperlink for the route below?

`<Route path={"/products"} component={HelloComponent}/>`

- A. `<Link path="/products">Products</Link>`
- B. `<Link to="/products">Products</Link>`
- C. `<Link component="/products">Products</Link>`

D. `<Link redirect="/products">Products</Link>`

Answer: B

Q31. Which feature allows to render the necessary or only critical interface items at initial loading times while lazily and quietly unrolling the other sections as needed?

- A. Hooks
- B. Lazy loading
- C. Server side rendering
- D. Client side rendering

Answer: B

Q32. You have a component MyCompoent. How do you use it with lazy loading?

- A.

```
import MyComponent from './MyComponent';  
function OneComponent() {  
  return (  
    <div>  
      <MyComponent />  
    </div>  
  );  
};
```
- B.

```
const MyComponent = () => import('./MyComponent');  
function OneComponent() {  
  return (  
    <div>  
      <MyComponent />  
    </div>  
  );  
};
```
- C.

```
var import MyComponent = './MyComponent';  
function OneComponent() {  
  return (  
    <div>  
      <MyComponent />  
    </div>  
  );  
};
```
- D.

```
const MyComponent = React.lazy(() => import('./MyComponent'));  
function OneComponent() {  
  return (  
    <div>  
      <MyComponent />  
    </div>  
  );  
};
```

Answer: D

Q33. What is React Suspense?

- A. Suspense provide feedback to UI while the lazy components are loaded
- B. Suspense acts like placeholder content while the lazy components are loaded
- C. Suspense loads lazy components asynchronously
- D. None

Answer: B

Q34. Which of the following are commonly used for HTTP requests?

- A. Fetch api
- B. Axios
- C. HttpClient
- D. XMLHttpRequest

Answer: A, B

Q35. Which is the alternate library for Fetch api?

- A. Axios

-
- B. HttpClient
 - C. XMLHttpRequest
 - D. All of the above

Answer: A

Q36. You want to load a set of Books from a remote URL.

Which one correct way to call using Axios with strict type checking in typescript

- A. `await axios.get(url)`
- B. `await axios.get<Book[]>(url)`
- C. `await axios.get<[]>(url)`
- D. `axios.get<Book>(url)`

Answer: B

Q37. Which one is not the correct way to load data with axios?

- A. `axios.get<Product[]>(url).then(response=>console.log(response.data))`
- B. `const {data} = await axios.get<Product[]>(url); console.log(data)`
- C. `const data = await axios.get<Product[]>(url); console.log(data)`
- D. `const response = await axios.get<Product[]>(url); console.log(response.data)`

Answer: C

Q38. What should you use for automatically passing a ref through a component to one of its children?

- A. `forwardRef`
- B. `HTMLProps`
- C. `ReactNode`
- D. `useRef`

Answer: A

Q39. Which library gives components to build from?

- A. Formik
- B. Yup
- C. Material UI
- D. Axios

Answer: A

Q40. Which one is not Formik property?

- A. `initialValue`
- B. `Validate`
- C. `onSubmit`
- D. `onReset`

Answer: D

Q41. Which library is used for form validation?

- A. Formik
- B. Yup
- C. Material UI
- D. Axios

Answer: B

Q42. You have a schema like below

```
const User = {  
  name: 'name of user'  
  email: 'email of user'  
}
```

How do you create a validation schema using Yup?

- A.

```
import * as Yup from 'Yup'  
const validationSchema= yup.mixed().shape({  
  name: Yup.string().required(),  
  email: Yup.string().email().required()  
});
```
- B.

```
import * as Yup from 'Yup'  
const validationSchema= yup.object().shape({
```

- ```

 name: Yup.string().required(),
 email: Yup.string().email().required()
);
C. import * as Yup from 'Yup'
 const validationSchema= yup.object().shape({
 name: Yup.string().required(),
 email: Yup.string().email().required()
 });
D. import * as Yup from 'Yup'
 const validationSchema= yup.object({
 name: Yup.string().required(),
 email: Yup.string().email().required()
 });

```

Answer: C

Q43. Which array method is used to create elements iterating through the array?

- A. forEach
- B. map
- C. reduce
- D. slice

Answer: B

Q44. You have an array

```

const data = [
{
 Label: 'A'
 Value: 20
},
{
 Label: 'B'
 Value: 30
}];

```

How do you return jsx?

- A. return {data.map(v, index)=><ul><li>{v.Label}</li></ul>};
- B. return {data.map(v, index)=><ul><li key={index}>{v.Label}</li></ul>};
- C. return {data.forEach(v, index)=><ul><li key={index}>{v.Label}</li></ul>};
- D. return {data.forEach(v, index)=><ul><li>{v.Label}</li></ul>};

Answer: B

[Must use map & add key to li element]

Q45. Why is redux used in react?

- A. for managing the global state of an application
- B. for loading remote data
- C. for passing data from one component to another
- D. for managing errors

Answer: A

Q46. What is a store in redux?

- A. in-memory storage of state, and it's globally accessible by any component
- B. physical storage of state, and it's globally accessible by any component
- C. cached data that can be used by components without requesting remote server
- D. A storage that users' data is stored

Answer: A

Q47. Which one is not a core part of redux?

- A. Dispatch:
- B. Reducers
- C. Store:
- D. Components



---

Answer: D

[Dispatch:

Reducers

Store:

Selectors]

Q48. Which one triggers an action?

- A. Dispatch:
- B. Reducers
- C. Store:
- D. Selectors

Answer: A

Q49. What do you need to send the action to the reducer.?

- A. a function to send the action to the reducer
- B. a dispatcher function to send the action to the reducer
- C. a store to send the action to the reducer
- D. a selector to send the action to the reducer

Answer: B

Q50. Which one can modify the Store?

- A. Dispatch:
- B. Reducers
- C. Store:
- D. Selectors

Answer: B

Q51. Which one takes a piece of state to render in the UI?

- A. Dispatch:
- B. Reducers
- C. Store:
- D. Selectors

Answer: D

Q52. \_\_\_\_\_ brings the instructions to the reducer about what to do with the states inside the Store.

- A. A dispatch function
- B. An action
- C. A selector
- D. A store

Answer: B

Q53. Which one basic route configuration and wraps others components?

- A. BrowserRouter
- B. Routes
- C. Route
- D. Switch

Answer: A

[Switch is removed from react, use Routes. Book uses switch]

Q54. Which tag is commonly used to change route path?

- A. <Link>
- B. <a>
- C. <Route>
- D. <Router>

Answer: A

Q55. Which property is required to match the url?

- A. to
- B. path
- C. url
- D. element

Answer: B

---

---

Q56.