

SQL SERVER 2016

Chapter 07: How to insert, update, and delete data

Chapter 08: How to work with data types

INSTRUCTOR: MD. HABIBUL HAQ
domain.habib@gmail.com

Q1. Which SQL Server extension clause lets you create a new table based on the result set defined by the SELECT statement?

- A. FETCH NEXT
- B. INTO
- C. TOP
- D. OVER

Answer: B

[Ref. Page: 217]

Q2. What things are copied, when you use SELECT INTO statement to create a table?

- A. Column definitions and Data
- B. Primary key and foreign key
- C. Default values
- D. Indexes

Answer: A

[Ref. Page: 217]

Q3. Why column names must be unique when you create table using SELECT INTO statement?

- A. Since the new table is based on the columns in the result set returned by the SELECT statement
- B. Since the new table will generate random names for the column
- C. Since new table will ignore duplicate columns
- D. Otherwise data is not copied correctly

Answer: A

[Ref. Page: 217]

Q4. When you do not include column list in the INSERT statement _____.

- A. you must give a value for every column in the table except for the identity column and the values should be listed in the same sequence that the columns appear in the table.
- B. you must give a value for not null columns in the table and the values should be listed in the same sequence that the columns appear in the table.
- C. you must give a value for every column in the table except for the identity column and the values can be listed in any order and SQL Server will put the values in appropriate columns based the data types of the values

- D. you must give a value for every column with default value and the values are listed in the same sequence that the columns appear in the table.

Answer: A

[Ref. Page: 218]

Q5. With INSERT statement a null value is assigned to column using _____.

- A. " value
- B. 0 value
- C. NULL keyword
- D. DEFAULT keyword

Answer: C

Q6. How a date literal value is assigned in an INSERT statement?

- A. Within double quotes
- B. Within single quotes
- C. Within brackets
- D. Within parentheses

Answer: B

Q7. Which statement will **NOT** insert the following ROW in Payments table?

Date	Person	Payment
2018-09-29	Faisal Hossain	2400.00

- A. INSERT INTO Payments VALUES ('2018-09-29',' Faisal Hossain', 2400.00)
- B. INSERT INTO Payments VALUES ('Faisal Hossain',' 2018-09-29', 2400.00)
- C. INSERT INTO Payments ([Date], [Person], [Payment]) VALUES ('2018-09-29','Faisal Hossain', 2400.00)
- D. INSERT INTO Payments ([Person], [Date], [Payment]) VALUES ('Faisal Hossain','2018-09-29', 2400.00)

Answer: B

Q8. Which statement will insert the following three ROWs in Payments table using a single INSERT statement?

Date	Person	Payment
2018-09-29	Faisal Hossain	2400.00
2018-09-29	Amir Hossain	1800.00
2018-09-29	Monir Hossain	2000.00

- A. INSERT INTO Payments VALUES ('2018-09-29',' Faisal Hossain', 2400.00,'2018-09-29',' Amir Hossain', 1800.00, '2018-09-29',' Monir Hossain', 2000.00)
- B. INSERT INTO Payments VALUES (('2018-09-29',' Faisal Hossain', 2400.00), ('2018-09-29',' Amir Hossain', 1800.00), ('2018-09-29',' Monir Hossain', 2000.00))
- C. INSERT INTO Payments VALUES ("2018-09-29',' Faisal Hossain', 2400.00","2018-09-29',' Amir Hossain', 1800.00"," '2018-09-29',' Monir Hossain', 2000.00")
- D. INSERT INTO Payments VALUES ('2018-09-29',' Faisal Hossain', 2400.00), ('2018-09-29',' Amir Hossain', 1800.00), ('2018-09-29',' Monir Hossain', 2000.00)

Answer: D

Q9. Look at the ColorSample table definition

Column name	Data type	Identify	Allow Nulls	Default value
Id	INT	Yes	No	
ColorNumber	INT	No	No	0

ColorName	VARCHAR(20)	No	Yes	
-----------	-------------	----	-----	--

You want to insert Identity value for IDENTITY column, default values for columns with default values and null values for columns that allow Nulls. Which statement will do this correctly?

- A. INSERT INTO ColorSample VALUES (DEFAULT)
- B. INSERT INTO ColorSample VALUES (DEFAULT, DEFAULT, NULL)
- C. INSERT INTO ColorSample VALUES (@@IDENTITY, DEFAULT, NULL)
- D. INSERT INTO ColorSample DEFAULT VALUES

Answer: D

[Ref. Page: 221]

Q10. Which statement do you use to modify existing data in a table?

- A. MODIFY
- B. ALTER
- C. UPDATE
- D. DELETE and INSERT

Answer: C

Q11. Which one is often referred to as upsert statement?

- A. SELECT INTO
- B. UPDATE FROM
- C. DELETE FROM
- D. MERGE

Answer: D

Q12. Which statement typically involves updating existing rows and inserting new rows?

- A. SELECT INTO
- B. UPDATE FROM
- C. SELECT target FROM source
- D. MERGE

Answer: D

[Ref. Page: 234]

Q11. You have the following data in Products table

Id	Name	Price
1	Sulfur dioxide	27.99
2	Hydrogen peroxide	6.77
3	Kerosene	3.21

You have ProductsTemp table data

Id	Name	Price
1	Sulfur dioxide	28.49
3	Kerosene	3.89

You have update data in Products table from data in ProductsTemp table.

Which query will do the task?

- A. UPDATE Products p
SET p.Price = c.Price
INNER JOIN ProductsTemp t
ON p.Id = t.Id
- B. UPDATE Products
SET Price = t.Price
FROM Products p

- INNER JOIN ProductsTemp t
ON p.Id =t.Id
- C. UPDATE Products p
SET p.Price = c.Price
FROM INNER JOIN ProductsTemp t
ON p.Id =t.Id
- D. UPDATE
SET Price = t.Price
FROM Products p
INNER JOIN ProductsTemp t
ON p.Id =t.Id

Answer: B

Q11. You have the following data in Products table

Id	Name	Price
1	Sulfur dioxide	27.99
2	Hydrogen peroxide	6.77
3	Kerosene	3.21

You have ProductsTemp table data

Id	Name	Price
1	Sulfur dioxide	28.49
4	Paraffin	1.89

You have to update data in Products table from data in ProductsTemp table if product's id match otherwise inserts a new row.

Which statement should you use?

- A. MERGE INTO Products AS p
USING ProductsTemp AS t
ON p.id = t.id
WHEN MATCHED THEN
UPDATE
WHEN NOT MATCHED THEN
INSERT
- B. MERGE INTO Products AS p
USING ProductsTemp AS t
WHEN MATCHED THEN
UPDATE SET p.price = t.price
WHEN NOT MATCHED THEN
INSERT (p.id, p.name, p.price) VALUES (t.id, t.name, t.price)
- C. MERGE INTO Products AS p
USING ProductsTemp AS t
ON p.id = t.id
WHEN MATCHED THEN
SET p.price = t.price
WHEN NOT MATCHED THEN
INSERT (p.id, p.name, p.price) VALUES (t.id, t.name, t.price)
- D. MERGE INTO Products AS p
USING ProductsTemp AS t
ON p.id = t.id

```
WHEN MATCHED THEN
    UPDATE SET p.price = t.price
WHEN NOT MATCHED THEN
    INSERT (id, p.name, price) VALUES (t.id, t.name, t.price)
```

Answer: D

Q12. A column's _____ specifies the kind of information the column is intended to store.

- A. data type
- B. default value
- C. allow null property
- D. constraint

Answer: A

[Ref. Page: 240]

Q13. Which of the following is or are temporal data types?

- A. Large character and binary values
- B. Dates, times or both
- C. floating point numbers, currency, and other numeric data
- D. Boolean values

Answer: B

[Ref. Page: 240]

Q14. Which SQL Server data type is synonym for ANSI-standard national character data type?

- A. text
- B. char
- C. nchar
- D. bit

Answer: C

Q15. Which SQL Server data type is synonym for ANSI-standard rowversion data type?

- A. nchar
- B. varbinary
- C. timestamp
- D. bit

Answer: C

Q16. How many Integer data types are there in SQL Server?

- A. 2
- B. 3
- C. 4
- D. 5

Answer: D

[Int, bigint, smallint, tinyint, bit (0 or 1, 0 for false, 1 for true

Ref. Page: 244]

Q17. Which Integer data type of the following does not allow negative number?

- A. Int
- B. Bigint
- C. Smallint
- D. Tinyint

Answer: D

[Ref. Page: 242]

Q18. The precision of a decimal value indicates_____.

- A. the total number of digits that can be stored
- B. the number of digits that can be stored to the right of the decimal point

-
- C. the number of digits that can be stored to the left of the decimal point
 - D. the maximum value that can be stored

Answer: A

[Ref. Page: 243]

Q19. The scale of a decimal value indicates_____.

- A. the total number of digits that can be stored
- B. the number of digits that can be stored to the right of the decimal point
- C. the number of digits that can be stored to the left of the decimal point
- D. the maximum value that can be stored

Answer: B

[Ref. Page: 243]

Q20. Which data types store strings of Unicode characters?

- A. Char and varchar
- B. Text and ntext
- C. Nchar and nvarchar
- D. Text and varbinary

Answer: C

Q21. The maximum number of characters char or varchar data type can store is _____.

- A. 255
- B. 4000
- C. 8000
- D. 64000

Answer: C

[nchar, nvarchar can store 4000 characters]

Q22. Which data type should you use for old ntext data type?

- A. varbinary (max)
- B. varchar (max)
- C. nvarchar (max)
- D. image

Answer: C

[Ref. Page: 249]

Q22. Which data type should you use for deprecated image data type?

- A. varbinary (max)
- B. varchar (max)
- C. nvarchar (max)
- D. ntext

Answer: A

[Ref. Page: 249]

Q23. Which one has the highest order of precedence?

- A. Money
- B. Decimal
- C. Real
- D. Float

Answer: D

[Ref. Page: 251]

Q24. Which one correctly converts the Integer value 100 to money data type?

- A. CAST (money, 100)
- B. CAST (100, money)
- C. CAST (money AS 100)

D. CAST (100 AS money)

Answer: D

Q25. What will be the result of the expression 5/10?

- A. .5
- B. .500000
- C. 0
- D. Null

Answer: C

[int/int results to int, so 5/10 yields to an int]

5.0/10=.5, 5/10.0=.5]

[Ref. Page: 253]

Q26. Which conversion function does not return an error if the expression can't be converted to the data type you specify?

- A. CAST
- B. CONVERT
- C. TRY_CONVERT
- D. All of above

Answer: C

Q27. What does TRY_CONVERT FUNCTION RETURN if the expression can't be converted to the data type you specify?

- A. 0
- B. False
- C. Null
- D. An error

Answer: C

Q28. Which one converts a floating-point number to a character string?

- A. STR
- B. CHAR
- C. NCHAR
- D. ASCII

Answer: A

Q29. Which one converts the leftmost character in a UNICODE string to its equivalent UNICODE code?

- A. NCHAR
- B. ASCII
- C. UNICODE
- D. STR

Answer: C

Q30. Which one returns tab character?

- A. CHAR (9)
- B. CHAR (10)
- C. CHAR (13)
- D. CHAR (65)

Answer: A

[Ref. Page: 259]