

ASP.NET Core in Action

Chapter 06: The binding model: Retrieving and validating user input

19 February 2024

Q1. What is the binding model?

- A. All the information that's provided by the user when making a request, as well as additional contextual data
- B. Anything needed to perform some sort of business action in your application.
- C. The view model for a Razor view
- D. The output of each page handler

Answer: A

[Page 159]

Q2. What is the application model?

- A. All the information that's provided by the user when making a request, as well as additional contextual data
- B. Anything needed to perform some sort of business action in your application.
- C. The view model for a Razor view
- D. The output of each page handler

Answer: B

[Page 159]

Q3. What is the PageModel?

- A. All the information that's provided by the user when making a request, as well as additional contextual data
- B. Anything needed to perform some sort of business action in your application.
- C. The view model for a Razor view
- D. The output of each page handler

Answer: C

[Page 159]

Q4. Which one holds the data required for rendering the view?

- A. Binding model
- B. Application model
- C. PageModel
- D. Rout values

Answer: C

[Page 160]

Q5. Which one is responsible for looking through the request that comes in and finding values to use?

- A. PageModel
- B. Model binder
- C. RoutingMiddleware
- D. EndpointMiddleware

Answer: B

[Page 161]

Q6. The process of creating objects of the appropriate type and assigning these values to your model from data in the request is called _____.

- A. binding

-
- B. routing
 - C. action
 - D. view

Answer: A

[Page 161]

Q7. Which one is not a binding source of values for the model binder?

- A. Form values
- B. Route values
- C. Query string values
- D. Session values

Answer: D

[Page 162]

Q8. _____ obtained from the HTTP request body when a form is submitted using a POST?

- A. Form values
- B. Route values
- C. Query string values
- D. Session values

Answer: A

[Page 162]

Q8. _____ obtained from URL segments?

- A. Form values
- B. Route values
- C. Query string values
- D. Session values

Answer: B

[Page 162]

Q9. What are the ways to use model binding in Razor Pages?

- A. Decorate properties on your PageModel with the [BindProperty] attribute
- B. Add parameters to service method call
- C. Add parameters to your page handler method
- D. All of the above

Answer: A, C

[Page 163]

Q10. You have the following page handler in your PageModel

```
public void OnGet( string currencyIn, string currencyOut, int qty)  
{  
    /* method implementation */  
}
```

The route values: **/GBP/USD?currencyIn=CAD**

Form data: **qty=50**

What will be the bound parameter values?

- A. currencyIn=GBP, currencyOut=USD, qty=50
- B. currencyIn=GBP, currencyOut=null, qty=50
- C. currencyIn=GBP, currencyOut="", qty=50
- D. currencyIn="", currencyOut=USD, qty=50

Answer: A

[Page 167]

Q11. You have the following page handler in your PageModel

```
public void OnGet( string currencyIn, string currencyOut, int qty)  
{  
    /* method implementation */  
}
```

The route values: **/GBP/USD?qty=100**

Form data: **currencyIn=CAD¤cyOut=EUR&qty=50**

What will be the bound parameter values?

- A. currencyIn=CAD, currencyOut=EUR, qty=100
- B. currencyIn=CAD, currencyOut=EUR, qty=50
- C. currencyIn=EUR, currencyOut=GBP, qty=100
- D. currencyIn=USD, currencyOut=GBP, qty=50

Answer: A

[Page 167]

Q12. Which one is used to upload files in ASP.NET Core?

- A. HttpPostedFileBase
- B. HttpPostedFileBase
- C. File
- D. IFormFile

Answer: D

[Page 171]

Q13. Which attribute is explicitly required when binding to JSON requests in Razor Pages?

- A. [FromHeader]
- B. [FromForm]
- C. [FromRoute]
- D. [FromBody]

Answer: D

[Page 173]

Q18. How can you tell the model binder to skip a parameter completely?

- A. [NotRequired]
- B. [BindProperty(false)]
- C. [BindNever]
- D. [BindRequired(false)]

Answer: C

[Page 174]

Q19. How can you indicate that the parameter should be provided using dependency injection?

- A. [FromHeader]
- B. [FromBody]
- C. [FromServices]
- D. [Services]

Answer: C

[Page 173]

Q20. Which attributes allow you to specify the rules that your binding model should conform to?

- A. Binding source attributes
- B. Binding attributes
- C. DataAnnotations attributes
- D. Remote attributes

Answer: C

[Page 176]

Q21. Which attribute validates that a property conforms to a pattern?

- A. [Pattern]
- B. [Format]
- A. [RegularExpression(regex)]
- B. [Compare]

Answer: C

[Page 177]

Q22. Which attribute confirms that two properties have the same value?

- A. [Pattern]

-
- B. [Format]
 - C. [RegularExpression(regex)]
 - D. [Compare]

Answer: D

[Page 177]