

ASP.NET Core in Action

Chapter 07: Rendering HTML using Razor views

19 February 2024

Q1. Where in a Razor Page most of the action happens?

- A. Bound property
- B. Razor view.
- C. Page handler
- D. PageModel

Answer: D

[Page 188]

Q2. Which one handles a single route?

- A. Bound property
- B. Razor view.
- C. Page handler
- D. PageModel

Answer: C

[Page 188]

Q3. What is razor syntax?

- A. It allows you to use C# code to generate HTML
- B. It allows you to mix C# and HTML to generate dynamic UIs
- C. It allows to access PageModel from HTML
- D. None of the above

Answer: B

[Page 189]

Q4. Which one is used in view to customize the HTML element they're attached to, changing how it's rendered?

- A. HTML helpers
- B. Tag helpers
- C. Razor extensions
- D. HTML extensions

Answer: B

[Page 193]

Q5. Tag helper attribute starts with _____.

- A. data-
- B. for-
- C. asp-
- D. aspnet-

Answer: C

[Page 194]

Q6. Which attribute is used to mark a .html as a razor page?

- A. @page
- B. @model
- C. @razor
- D. @using

Answer: A

[Page 194]

Q7. Which attribute indicates which PageModel is associated with the Razor view?

- A. @page
- B. @model
- C. @razor
- D. @using

Answer: B

[Page 194]

Q8. Which one is not a way to pass data from page handler to a razor view?

- A. PageModel properties
- B. ViewData
- C. HttpContext
- D. Route data

Answer: D

[Page 197]

PageModel properties

ViewData

HttpContext

@inject services]

Q9. Which one is the key/value pair dictionary?

- A. PageModel properties
- B. ViewData
- C. HttpContext
- D. @inject services

Answer: B

[Page 197]

Q10. Which one is used to pass arbitrary data to _layout files?

- A. PageModel properties
- B. ViewData
- C. HttpContext
- D. @inject services

Answer: B

[Page 197]

Q11. Which of the following properly sets value in ViewData properly?

- A. [ViewData]
public string Title { get; set; }
- B. ViewData["Subtitle"] = "Welcome";
- C. ViewData.Subtitle = "Welcome";
- D. ViewData.Set("Subtitle", "Welcome");

Answer: A, B

[Page 199]

Q12. Which symbol in razor template indicates where the C# code begins?

- A. #
- B. @
- C. =>
- D. ?

Answer: B'

[Page 200]

Q13. Which of the following properly renders Check all?

- A. Check all
- B. Check all
- C. @{ var task="Check all";}
@Html.Raw(task)
- D. @{ var task="Check all";}
<text>@task</text>

Answer: B, C

Q14. Which one is a template that includes common code for multiple razor pages?

- A. _ViewStart
- B. _ViewImports
- C. _Layout
- D. PartialView

Answer: C

[Page 206]

Q15. What is the typical location of the layout page of razor pages?

- A. Pages
- B. Pages/Layout
- C. Pages/Shared
- D. wwwroot

Answer: C

[Page 207]

Q16. Which function layout page must call?

- A. Render
- B. RenderSection
- C. RenderBody
- D. Html.Raw

Answer: C

[Page 208]

Q17. What is the purpose of the RenderBody method?

- A. It extracts data from the request and create a model object from that data
- B. It tells the templating engine where to insert the content from the child views
- C. It creates body element of the rendered HTML document
- D. It loads the CSS, scripts files required

Answer: B

[Page 208]

Q18. Which one contains directives that will be inserted at the top of every view?

- A. _ViewStart
- B. _ViewImports
- C. _Layout
- D. PartialView

Answer: B

[Page 214]