

ASP.NET Core in Action

Chapter 11: Configuring an ASP.NET Core application

19 February 2024

Q1. What is the setting of an application?

- A. A setting is any value that is required to run the application.
- B. A setting is any value that changes the behavior of the application.
- C. A setting is any value that gets out of the application.
- D. A setting is any value that the application gives other applications as input.

Answer: B

[Page 331]

Q2. What is a secret?

- A. a special type of setting that contains passwords
- B. a special type of setting that contains someone's credit card number
- C. a special type of setting that contains sensitive data
- D. a special type of setting that contains no visible data

Answer: C

[Page 331]

Q3. What is the configuration of an application?

- A. set of external parameters provided to an application that are required to run the application
- B. set of external parameters provided to an application that controls the application's behavior in some way
- C. set of external parameters provided to an application that controls the output of the application
- D. set of values that the application gives other applications as input.

Answer: B

[Page 331]

Q4. From which sources can you load configuration values in an ASP.NET Core application?

- A. JSON file
- B. XML file
- C. environment variables
- D. All of the above

Answer: D

[Page 332]

JSON, XML, YAML, and so on

On top of that, you can load values from environment variables, from command-line arguments, from a database, or from a remote service

Even you can create your own custom configuration provider]

Q5. What are the main classes of the ASP.NET Core configuration model you mostly use?

- A. ConfigurationHostBuilder
- B. ConfigurationBuilder
- C. IHost
- D. IConfiguration

Answer: B, D

[Page 335]

Q6. Which one is not a common location from where ASP.NET Core's built-in configuration providers can load data?

- A. JSON files

-
- B. XML files
 - C. Text files
 - D. INI files

Answer: C

[Page 335]

ASP.NET Core ships with configuration providers for loading data from common locations:

JSON files

XML files

Environment variables

Command-line arguments

INI files]

Q7. What does the Build method ConfigurationBuilder class create?

- A. Host which implements IHost
- B. IConfiguration
- C. IConfigurationRoot, which implements IConfiguration
- D. ConfigurationProvider

Answer: C

[Page 336]

Q8. Which configuration provider loads data from appSettings.json file?

- A. JsonConfigurationProvider
- B. CommandLineProvider
- C. EnvironmentVariablesProvider
- D. None of the above

Answer: A

[Page 338]

Q9. Which configuration provider loads environment variables as configuration variables?

- A. JsonConfigurationProvider
- B. CommandLineProvider
- C. EnvironmentVariablesProvider
- D. None of the above

Answer: C

[Page 338]

Q10. Which one is the most common way of using IConfiguration in Startup class?

- A.

```
public class Startup
{
    public Startup(IConfiguration config)
    {
        Configuration = config;
    }
    public IConfiguration Configuration { get; }
}
```
- B.

```
public class Startup
{
    public Startup(IConfigurationBuilder config)
    {
        ConfigurationBuilder = config;
    }
    public IConfigurationBuilder ConfigurationBuilder { get; }
}
```
- C.

```
public class Startup
{
    public Startup(IConfigurationBuilder config)
    {
        ConfigurationBuilder = config;
```

```

    }
    public IConfigurationBuilder ConfigurationBuilder { get; }
    public IConfiguration Configuration { get=> builder.Build(); }

```

```

    }
D. public class Startup
    {
        public Startup(IConfigurationBuilder builder)
        {
            ConfigurationBuilder = builder;
        }
        public IConfigurationBuilder ConfigurationBuilder { get; }
        public IConfiguration Configuration { get=> builder.AddJsonFile().Build(); }
    }

```

Answer: A

[Page 339]

Q11. You have the following app settings.json

```

{
  "Logging": {
    "LogLevel": {
      "Default": "Information",
      "Microsoft": "Warning",
      "Microsoft.Hosting.Lifetime": "Information"
    }
  },
  "AllowedHosts": "*",
  "MapSettings": {
    "DefaultZoomLevel": 9,
    "DefaultLocation": {
      "latitude": 50.500,
      "longitude": -4.000
    }
  }
}

```

Which of the following statements loads latitude value from the appSettings.json file?

- A. Configuration["MapSettings"].DefaultZoomLevel.latitude;
- B. Configuration.GetSection("MapSettings")["DefaultLocation:Latitude"];
- C. Configuration["MapSettings:DefaultZoomLevel:latitude"];
- D. Configuration["MapSettings.DefaultZoomLevel.latitude"];

Answer: B, C

[Page 339, 340]

Q12. Which one is the easiest and most commonly used approach to storing configuration secrets such as a password, a connection string, or an API key for a remote service etc in production server?

- A. use appsettings.json
- B. use environment variables
- C. use command-line arguments
- D. use a separate JSON file

Answer: B

[Page 342]

Q13. How can you add the environment variable configuration provider?

- A. using the AddJsonFile() extension method
- B. using the AddEnvironmentVariables() extension method,

-
- C. using the Build() method
 - D. using CreateConfiguration() method

Answer: B

[Page 343]

Q14. Which approach is particularly useful for storing configuration secrets when you're publishing your app to a self-contained environment, such as a dedicated server, Azure, or a Docker container?

- A. JSON file
- B. YAML file
- C. Environment variables
- D. Command-line arguments

Answer: C

[Page 344]

Q15. You want to add configuration secret to secrets.json file using dotnet driver tool like below

```
{  
  "webAppSettings": {  
    "appKey": "F5RJT9GFHKR7"  
  }  
}
```

Which command should you run?

- A. dotnet set "webAppSettings:appKey" F5RJT9GFHKR7
- B. dotnet user-secrets "webAppSettings:appKey" F5RJT9GFHKR7
- C. dotnet user-secrets set "webAppSettings:appKey" F5RJT9GFHKR7
- D. dotnet user-secrets add "webAppSettings:appKey" F5RJT9GFHKR7

Answer: C

[Page 345]

Q16 How can you enable the reloading of configuration files when you add any of the file-based providers to your ConfigurationBuilder?

- A. Pass reloadOnChange parameter set to false to the Add*File extension method
- B. Pass reloadOnChange parameter set to true to the Add*File extension method
- C. Add the reloadOnChange event to the ConfigurationBuilder
- D. None of the above

Answer: B

[Page 346]

Q17. Which interface exposes a number of useful properties about the running context of your app?

- A. IOptions
- B. IConfigurationBuilder
- C. IHostEnvironment
- D. IWebHostEnvironment

Answer: C

[Page 355]

Q18. Which one maps to the wwwroot folder?

- A. ContentRootPath property of the IWebHostEnvironment
- B. WebRootPath property of the IWebHostEnvironment
- C. EnvironmentName property of the IWebHostEnvironment
- D. Path property of the IWebHostEnvironment

Answer: B

[Page 358]