

# ASP.NET Core in Action

## Chapter 20: Calling remote APIs with IHttpHttpClientFactory

---

**19 February 2024**

Q1. Which code is most likely to socket exhaustion?

- A. `[HttpGet("values")]`  
`public async Task<string> GetRates()`  
`{`  
    `using (HttpClient client = new HttpClient())`  
    `{`  
        `client.BaseAddress = new Uri("https://api.rates.io");`  
        `var response = await client.GetAsync("latest");`  
        `response.EnsureSuccessStatusCode();`  
        `return await response.Content.ReadAsStringAsync();`  
    `}`  
`}`
- B. `private static readonly HttpClient _client = new HttpClient{ BaseAddress = new Uri("https://api.exchangeratesapi.io");}`  
`[HttpGet("values")]`  
`public async Task<string> GetRates()`  
`{`  
    `var response = await _client.GetAsync("latest");`  
    `response.EnsureSuccessStatusCode();`  
    `return await response.Content.ReadAsStringAsync();`  
`}`
- C. `private static readonly HttpClient _client = new HttpClient{ BaseAddress = new Uri("https://api.exchangeratesapi.io");}`  
`[HttpGet("values")]`  
`public async Task<string> GetRates()`  
`{`  
    `var rates = await _client.GetFromJsonAsync<string>("latest");`  
    `return rates;`  
`}`
- D. `private static readonly HttpClient _client = new HttpClient{ BaseAddress = new Uri("https://api.exchangeratesapi.io");}`  
`[HttpGet("values")]`  
`public async Task<string> GetRates()`  
`{`  
    `return await _client.GetFromJsonAsync<string>("latest");;`  
`}`

Answer: A

[Page 672]

Q2. You added IHttpHttpClientFactory to application services in ConfigureServices method using code `services.AddHttpClient()`

What is the lifetime of HttpClient?

- A. Scoped
- B. Transient
- C. Singleton
- D. Per call

---

Answer: C

[Page 676]

Q3. Which method of the IHttpConnectionFactory to create a HttpClient object?

- A. Create()
- B. CreateClient()
- C. CreateNew()
- D. New()

Answer: B

[Page 676]