Machine Learning Notes

CHAPTER 1 : INTRODUCTION

Definition: A computer program is said to **learn** from **experience E** with respect to some **class of tasks T** and **performance measure P**, if its performance at tasks in T, as measured by P, improves with experience E.

For example, a computer program that learns to play checkers might improve its performance as measured by its ability to win at the class of tasks involving playing checkers games, through experience obtained by playing games against itself. In general, to have a well-defined learning problem, we must identity these three features:

1. the class of tasks,
2. the measure of performance to be improved, and
3. the source of experience.

A checkers learning problem:

- **Task T:** playing checkers
- **Performance measure P:** percent of games won against opponents
- **Training experience E:** playing practice games against itself

We can specify many learning problems in this fashion, such as learning to recognize handwritten words, or learning to drive a robotic automobile autonomously.

A handwriting recognition learning problem:

Task T: recognizing and classifying handwritten words within images

Performance measure P: percent of words correctly classified

Training experience E: a database of handwritten words with given classifications

A robot driving learning problem:

Task T: driving on public four-lane highways using vision sensors

Performance measure P: average distance travelled before an error (as judged by human overseer)

DEEPAK RAJPUT

Training experience E: a sequence of images and steering commands recorded while observing a human driver

CHAPTER 2: CONCEPT LEARNING AND THE GENERAL-TO-SPECIFIC ORDERING

INTRODUCTION

Concept learning. Inferring a Boolean valued function from training examples of its input and output.

A CONCEPT LEARNING TASK

The attribute EnjoySport indicates whether or not Aldo enjoys his favourite water sport on this day. The task is to learn to predict the value of EnjoySport for an arbitrary day, based on the values of its other attributes.

Let us begin by considering a simple representation in which each hypothesis consists of a conjunction of constraints on the instance attributes. In particular, let each hypothesis be a vector of six constraints, specifying the values of the six attributes Sky, AirTemp, Humidity, Wind, Water, and Forecast. For each attribute, the hypothesis will either 0 indicate by a "?' that any value is acceptable for this attribute, 0 specify a single required value (e.g., Warm) for the attribute, or 0 indicate by a "0" that no value is acceptable.

- indicate by a "?' that any value is acceptable for this attribute,
- specify a single required value (e.g., Warm) for the attribute, or
- indicate by a "Φ" that no value is acceptable.

If some instance x satisfies all the constraints of hypothesis h, then h classifies x as a positive example (h(x) = 1). To illustrate, the hypothesis that Aldo enjoys his favourite sport only on cold days with high humidity (independent of the values of the other attributes) is represented by the expression

(?, Cold, High, ?, ?, ?)

Example Sky AirTemp Humidity Wind Water Forecast EnjoySport

1 Sunny Warm Normal Strong Warm Same Yes

2 Sunny Warm High Strong Warm Same Yes

3 Rainy Cold High Strong Warm Change No

DEEPAK RAJPUT

4 Sunny Warm High Strong Cool Change Yes

The most general hypothesis-that every day is a positive example-is represented by

(?, ?, ?, ?, ?, ?)

and the most specific possible hypothesis-that no day is a positive example-is represented by

(Φ, Φ, Φ, Φ, Φ, Φ)

Notation

The set of items over which the concept is defined is called the set of instances, which we denote by X. In the current example, X is the set of all possible days, each represented by the attributes Sky, AirTemp, Humidity, Wind, Water, and Forecast. The concept or function to be learned is called the target concept, which we denote by c. In general, c can be any boolean-valued function defined over the instances X; that is, c : X -> {O, 1}.

In the current example, the target concept corresponds to the value of the attribute EnjoySport

(i.e., c(x) = 1 if EnjoySport = Yes, and c(x) = 0 if EnjoySport = No).

- Given: 0
  - Instances X: Possible days, each described by the attributes
    - Sky (with possible values Sunny, Cloudy, and Rainy),
    - AirTemp (with values Warm and Cold),
    - Humidity (with values Normal and High),
    - Wind (with values Strong and Weak),
    - Water (with values Warm and Cool), and
    - Forecast (with values Same and Change).
  - Hypotheses H: Each hypothesis is described by a conjunction of constraints on the attributes Sky, AirTemp, Humidity, Wind, Water, and Forecast. The constraints may be "?" (any value is acceptable), " Φ”(no value is acceptable), or a specific value.

DEEPAK RAJPUT

- Target concept c: EnjoySport : X -> {0,1}
- Training examples D: Positive and negative examples of the target function (see Table 2.1).
- Determine:
    - hypothesis h in H such that h(x) = c(x) for all x in X.

Instances for which c(x) = 1 are called positive examples, or members of the target concept. Instances for which c(x) = 0 are called negative examples, or nonmembers of the target concept.

In general, each hypothesis h in H represents a boolean-valued function defined over X; that is, h : X -> {O, 1}. The goal of the learner is to find a hypothesis h such that h(x) = c(x) for all x in X.

The Inductive Learning Hypothesis

The inductive learning hypothesis. Any hypothesis found to approximate the target function well over a sufficiently large set of training examples will also approximate the target function well over other unobserved examples.

General-to-Specific Ordering of Hypotheses(Not Necessary)

To illustrate the general-to-specific ordering, consider the two hypotheses

h1 = (Sunny, ?, ?, Strong, ?, ?)

h2 = (Sunny, ?, ?, ?, ?, ?)

Now consider the sets of instances that are classified positive by h1 and by h2. Because h2 imposes fewer constraints on the instance, it classifies more instances as positive. In fact, any instance classified positive by h1 will also be classified positive by h2. Therefore, we say that h2 is more general than h1.

This intuitive "more general than" relationship between hypotheses can be defined more precisely as follows. First, for any instance x in X and hypothesis h in H, we say that x satisfies h if and only if h(x) = 1. We now define the more_general_than_or_equal_to relation in terms of the sets of instances that satisfy the two hypotheses: Given hypotheses h_j and h_k, h_j is more_general_than_or_equal_to h_k if and only if any instance that satisfies h_k also satisfies h_i.

Definition: Let h_j and h_k be boolean-valued functions defined over X. Then h_j is more_general_than_or_equal_to h_k (written $h_j >=_g h_k$) if and only if

$$(\forall x \in X)[(h_k(x) = 1) \rightarrow (h_j(x) = 1)]$$

We will also find it useful to consider cases where one hypothesis is strictly more general than the other. Therefore, we will say that h_j is (strictly) more_general_than_or_equal_to h_k (written $h_j >_g h_k$) if and only if ($h_j >=_g h_k$) ($h_k >!=_g h_j$). Finally, we will sometimes find the inverse useful and will say that hj is more_specific_than h_k when h_k is more_general_than h_j.

The $>=_g$ relation is important because it provides a useful structure over the hypothesis space H for any concept learning problem. The following sections present concept learning algorithms that take advantage of this partial order to efficiently organize the search for hypotheses that fit the training data.

FIND-S: FINDING A MAXIMALLY SPECIFIC HYPOTHESIS

Find-S Algorithm is a basic concept learning algorithm which find the most specific hypothesis that fits all the positive example.

The **find-S Algorithm** also starts with most specific hypothesis & generalizes this hypothesis each time. It fails classify and observe positive training data.

Hence **find-S Algorithm** moves from the most specific hypothesis to most generalizes hypothesis.

DEEPAK RAJPUT

CHAPTER 6: BAYESIAN LEARNING

INTRODUCTION

Bayesian learning methods are relevant to our study of machine learning for two different reasons. First, Bayesian learning algorithms that calculate explicit probabilities for hypotheses, such as the naive Bayes classifier, are among the most practical approaches to certain types of learning problems.

The second reason that Bayesian methods are important to our study of machine learning is that they provide a useful perspective for understanding many learning algorithms that do not explicitly manipulate probabilities.

Features of Bayesian learning methods include:

- Each observed training example can incrementally decrease or increase the estimated probability that a hypothesis is correct. This provides a more flexible approach to learning than algorithms that completely eliminate a hypothesis if it is found to be inconsistent with any single example.
- Prior knowledge can be combined with observed data to determine the final probability of a hypothesis. In Bayesian learning, prior knowledge is provided by asserting

  (1) a prior probability for each candidate hypothesis, and

  (2) a probability distribution over observed data for each possible hypothesis.
- Bayesian methods can accommodate hypotheses that make probabilistic predictions (e.g., hypotheses such as "this pneumonia patient has a 93% chance of complete recovery").
- New instances can be classified by combining the predictions of multiple hypotheses, weighted by their probabilities.
- Even in cases where Bayesian methods prove computationally intractable, they can provide a standard of optimal decision making against which other practical methods can be measured.

BAYES THEOREM

P(h) to denote the initial probability that hypothesis h holds, before we have observed the training data. P(h) is often called the prior probability of h.

P(D) to denote the prior probability that training data D will be observed (i.e., the probability of D given no knowledge about which hypothesis holds).

DEEPAK RAJPUT

P(D|h) to denote the probability of observing data D given some world in which hypothesis h holds.

P(xly) to denote the probability of x given y.

P(h|D) that h holds given the observed training data D. P (h 1 D) is called the posterior probability of h.

Bayes theorem is the cornerstone of Bayesian learning methods because it provides a way to calculate the posterior probability P(h|D), from the prior probability P(h), together with P(D) and P(D(h)).

$$P(h|D) = \frac{P(D|h)P(h)}{P(D)}$$

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

(Formula used in example)

Example :- (10 marks confirm)

S. No.	Outlook	Temperature	Humidity	Windy	Play on
1	Rainy	Hot	High	FALSE	No
2	Rainy	Hot	High	TRUE	No
3	Overcast	Hot	High	FALSE	Yes
4	Sunny	Mild	High	FALSE	Yes
5	Sunny	Cool	Normal	FALSE	Yes
6	Sunny	Cool	Normal	TRUE	No
7	Overcast	Cool	Normal	TRUE	Yes
8	Rainy	Mild	High	FALSE	No
9	Rainy	Cool	Normal	FALSE	Yes
10	Sunny	Mild	Normal	FALSE	Yes
11	Rainy	Mild	Normal	TRUE	Yes
12	Overcast	Mild	High	TRUE	Yes
13	Overcast	Hot	Normal	FALSE	Yes
14	Sunny	Mild	High	TRUE	No

DEEPAK KAPOOT

Outlook

	Yes	No	Probability of Yes	Probability of No
Rainy	2	3		
Sunny	3	2		
Overcast	4	0		
Total	9	5	100	100

Temperature

	Yes	No	Probability of Yes	Probability of No
Hot	2	2		
Mild	3	1		
Cool	4	2		
Total	9	5	100	100

Humidity

	Yes	No	Probability of Yes	Probability of No
High	3	4		
Normal	6	1		
Total	9	5	100	100

Windy

	Yes	No	Probability of Yes	Probability of No
TRUE	6	2		
FALSE	3	3		
Total	9	5	100	100

Play On

	Number	Probability
Yes	9	(9/14)
No	5	(5/14)
Total	14	

DEEPAK RAJPUT



Pattern Recognition and Machine Learning

The Curse of Dimensionality

Curse of Dimensionality describes the explosive nature of increasing data dimensions and its resulting exponential increase in computational efforts required for its processing and/or analysis.

As the dimensionality increases, the number of data points required for good performance of any machine learning algorithm increases exponentially.

Scatter plot of the oil flow data for input variables x6 and x7, in which red denotes the 'homogenous' class, green denotes the 'annular' class, and blue denotes the 'laminar' class. Our goal is to classify the new test point denoted by 'x'.

DEEPAK



Illustration of a simple approach to the solution of a classification problem in which the input space is divided into cells and any new test point is assigned to the class that has a majority number of representatives in the same cell as the test point. As we shall see shortly, this simplistic approach has some severe shortcomings.



The problem with an exponentially large number of cells is that we would need an exponentially large quantity of training data in order to ensure that the cells are not empty. Clearly, we have no hope of applying such a technique in a space of more than a few variables, and so we need to find a more sophisticated approach

The Art and Science of Algorithms that Make Sense of Data

Kinds of feature

Consider two features, one describing a person's age and the other their house number. Both features map into the integers, but the way we use those features can be quite different. Calculating the average age of a group of people is meaningful, but an average house number is probably not very useful! In other words, what matters is not just the domain of a feature, but also the range of permissible operations. These, in turn, depend on whether the feature values are expressed on a meaningful **scale**. Despite appearances, house numbers are not really integers but **ordinals**: we can use them to determine that number 10's neighbours are number 8 and number 12, but we cannot assume that the distance between 8 and 10 is the same as the distance between 10 and 12. Because of the absence of a linear scale it is not meaningful to add or subtract house numbers, which precludes operations such as averaging.

Calculations on features

Three main categories are **statistics of central tendency, statistics of dispersion** and **shape statistics.** Each of these can be interpreted either as a theoretical property of an unknown population or a concrete property of a given sample – here we will concentrate on sample statistics.

Starting with statistics of central tendency, the most important ones are:

- the **mean** or average value;
- the **median**, which is the middle value if we order the instances from lowest to highest feature value; and
- the **mode**, which is the majority value or values.

Imagine a swimmer who swims the same distance d on two different days, taking a seconds one day and b seconds the next. On average, it took her therefore $c = (a + b)/2$ seconds, with an average speed of $d/c = 2d/(a + b)$. Notice how this average speed is not calculated as the normal or **arithmetic mean** of

DEEPAK RAJPUT

the speeds, which would yield (d/a + d/b)/2: to calculate average speed over a fixed distance we use a different mean called the **harmonic mean**. Given two numbers x and y (in our swimming example these are the speeds on either day, d/a and d/b), the harmonic mean h is defined as

Since 1/h(x, y) = (1/x + 1/y)/2, we observe that calculating the harmonic mean on a scale with unit u corresponds to calculating the arithmetic mean on the **reciprocal scale** with unit 1/u.

In the example, speed with fixed distance is expressed on a scale reciprocal to the time scale, and since we use the arithmetic mean to average time, we use the harmonic mean to average speed. (If we average speed over a fixed time interval this is expressed on the same scale as distance and thus we would use the arithmetic mean.)

A good example of where the harmonic mean is used in machine learning arises when we average precision and recall of a classifier. Remember that precision is the proportion of positive predictions that is correct (prec = TP/(TP + FP)), and recall is the proportion of positives that is correctly predicted (rec = TP/(TP + FN)). Suppose we first calculate the number of mistakes averaged over the classes: this is the arithmetic mean Fm = (FP + FN)/2. We can then derive

We recognise the last term as the harmonic mean of precision and recall. Since the enumerator of both precision and recall is fixed, taking the arithmetic mean of the denominators corresponds to taking the harmonic mean of the ratios. In information retrieval this harmonic mean of precision and recall is very often used and called the **F-measure**.

Yet other means exist for other scales. In music, going from one note to a note one octave higher corresponds to doubling the frequency. So frequencies f and 4f are two octaves apart, and it makes sense to take the octave in between with frequency 2f as their mean. This is achieved by the **geometric mean**, which is defined as *

Since * it follows that the geometric mean corresponds to the arithmetic mean on a logarithmic scale. All these means have in common that the mean of two values is an interediate value, and that they can easily be extended to more than two values.

The second kind of calculation on features are statistics of **dispersion** or '**spread'**. Two well-known statistics of dispersion are the **variance** or **average**

DEEPAK RAJPUT

squared deviation from the (arithmetic) mean, and its square root, the **standard deviation**.

Variance and **standard deviation** essentially measure the same thing, but the latter has the advantage that it is expressed on the same scale as the feature itself. **For example,** the variance of the body weight in kilograms of a group of people is measured in kg 2 (kilograms-squared), whereas the standard deviation is measured in kilograms. The absolute difference between the mean and the median is never larger than the standard deviation – this is a consequence of **Chebyshev's inequality**, which states that at most 1/k 2 of the values are more than k standard deviations away from the mean.

A simpler dispersion statistic is the difference between maximum and minimum value, which is called the **range**. A natural statistic of central tendency to be used with the range is the **midrange point**, which is the mean of the two extreme values. These definitions assume a linear scale but can be adapted to other scales using suitable transformations. **For example**, for a feature expressed on a logarithmic scale, such as frequency, we would take the ratio of the highest and lowest frequency as the range, and the harmonic mean of these two extremes as the midrange point.

Other statistics of dispersion include **percentiles**. The p-th percentile is the value such that p per cent of the instances fall below it. If we have 100 instances, the 80th percentile is the value of the 81st instance in a list of increasing values. If p is a multiple of 25 the percentiles are also called **quartiles**, and if it is a multiple of 10 the percentiles are also called **deciles**. Note that the 50th percentile, the 5th decile and the second quartile are all the same as the median. **Percentiles**, **deciles** and **quartiles** are special cases of **quantiles**. Once we have quantiles we can measure dispersion as the distance between different quantiles. For instance, the **interquartile range** is the difference between the third and first quartile (i.e., the 75th and 25th percentile).

Example 10.1 (Percentile plot). Suppose you are learning a model over an instance space of countries, and one of the features you are considering is the gross domestic product (GDP) per capita. Figure 10.1 shows a so-called **percentile plot** of this feature. In order to obtain the p-th percentile, you intersect the line y = p with the dotted curve and read off the corresponding percentile on the x-axis. Indicated in the figure are the 25th, 50th and 75th percentile. Also indicated is the mean (which has to be calculated from the raw data). As you can see, the mean is considerably higher than the median; this is

DEEPAK RAJPUT

mainly because of a few countries with very high GDP per capita. In other words, the mean is more sensitive to **outliers** than the median, which is why the median is often preferred to the mean for skewed distributions like this one.



Figure 10.1. Percentile plot of GDP per capita for 231 countries (data obtained from www.wolframalpha.com by means of the query 'GDP per capita'). The vertical dotted lines indicate, from left to right: the **first quartile** ($900); the **median** ($3600); the **mean** ($11284); and the **third quartile** ($14 750). The **interquartile range** is $13 850, while the **standard deviation** is $16 189.

DEEPAK