SF 1535

MATERIAL SAFETY DATA SHEET

1530
1535
4/1/2000

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SUPER WEATHERSTRIP ADHESIVE
IES PART NUMBER: 1530 (AMBER) & 1535 (BLACK)
MANUFACTURER: ADDRESS: Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186
24 HOUR EMERGENCY PHONE (INFOTRAC) (800) 535-5053
INFORMATION PHONE: (800) 451-7206
DATE PREPARED: APRIL 1, 2000
SECTION 1 NOTES: This material safety data sheet complies with OSHA'S Hazard Communication standard,1910, 1200. If any item is not applicable (N/A) or no information is available (N/I), the space is marked to indicate that.

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components Specific chemical identity Common Name (s)	CAS NO.	OSHA VPEL TWA	OSHA VPEL STEL	ACGIH TLV TWA	ACGIH TLV STEL	Approx. V/V % (optional)
N-Hexane	110-54-3	50 ppm	50ppm	50ppm	50ppm	35-40
Toluene	108-88-3	100 ppm	150ppm	50ppm	150ppm	30-35
Acetone	67-64-1	750ppm	1000ppm	500ppm	750ppm	5-10

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Flammable liquid, solvent order. Irritating to eyes, skin and respiratory tract. Overexposure may cause Central Nervous System effects.

ROUTES OF ENTRY: Inhalation = Yes, Skin Contact = Yes, Ingestion = Yes

POTENTIAL HEALTH EFFECTS

EYES: Exposure to liquid or vapor may cause mild eye irritation. Symptoms may include burning, tearing, Redness, stinging, blurred vision and corneal injury.

SKIN: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking and skin burns. Pre-existing skin disorders may be aggravated by exposure to this material. Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal conditions of handling and use.

BREATHING: Symptoms are typically seen at air concentrations exceeding the recommended exposure Limits. Symptoms of exposure may include:

1. Nasal and respiratory irritation (nose, throat and lungs) pre-existing lung disorder, e.g. asthma-like conditions, may be aggravated by exposure to this material.
2. Central Nervous System (CNS) Depression / Effect (dizziness, drowsiness, weakness, fatigue, nausea, headache, possible unconsciousness, coma, and even death.
3. Cardiac arrhythmia's (irregular heartbeat)
4. Cough

INGESTION: This material can enter the lungs during swallowing or vomiting and cause lung inflammation and or damage. Aspiration of material into the lungs can cause chemical pneumonia, which can be fatal. Symptoms of exposure may include:

1. Throat Irritation
2. Gastrointestinal irritation (nausea, vomiting, diarrhea)
3. Central Nervous System (CNS) Depression / Effect (dizziness, drowsiness, weakness, fatigue, nausea, headache, possible unconsciousness, coma, and even death)
4. High blood sugar.

SECTION 4: FIRST AID MEASURES

EYES: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes with water for at least 15 minutes while holding eyelids apart. If symptoms persist, seek medical attention.

SKIN: Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, apply a clean dressing and seek immediate medical attention. If skin is not damaged, wash exposed area with soap and water if symptoms persist, seek medical attention. Launder clothing before use.

INGESTION: DO NOT INDUCE VOMITING. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Seek medical attention. If possible, do not leave individual unattended. Aspiration of material into the lungs can cause chemical pneumonia, which can be fatal.

INHALATION: If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention. Keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:
ACETONE This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.
HEXANE Exposure to high concentrations of this material (e.g. deliberate abuse or enclosed spaces) may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: 12.6%
(% BY VOLUME) LOWER: 1%

FLASH POINT: METHOD USED: TCC
F = -10°, C = -23.3°

NFPA HAZARD CLASSIFICATION: (0= LEAST, 1= SLIGHT, 2= MODERATE, 3= HIGH, 4= EXTREME)
HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0

EXTINGUISHING MEDIA: Regular foam or carbon dioxide or dry chemical foam.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus with full-face mask operated in the positive pressure mode when fighting fires. Water may not be effective for fighting fires. Water may be used to keep fire-exposed containers cool until fire is extinguished.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. All five-gallon pails and larger metal containers should be grounded and / or bonded when material is transferred. Material is highly volatile and readily gives of vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.
Warning !! Sudden release of hot organic chemical vapors or mist from process equipment operated at elevated temperature and pressure or sudden ingress of air into vacuum equipment may result in ignitions without the presence of obvious ignition sources. Published "auto ignition" or "ignition" temperature values cannot be treated as safe operation temperatures in chemical processes without analysis of the actual process conditions. Any use of this product at elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.
HYDROCARBON SOLVENTS ARE BASICALLY NON-CONDUCTORS OF ELECTRICITY AND CAN BECOME ELECTRO STATICALLY CHARGED DURING MIXING, FILTERING OR PUMPING AT HIGH FLOW RATES. IF THIS CHARGE REACHES A SIGNIFICANTLY HIGH LEVEL, SPARKS CAN FORM THAT MAY IGNITE VAPORS OF FLAMMABLE LIQUIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials; carbon dioxide and carbon monoxide, various hydrocarbons, etc.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled:
SMALL SPILL: Absorb liquid on paper, vermiculite, floors absorbent or other absorbent material and transfer to hood.
LARGE SPILLS: Eliminate all ignition sources (flares, flames – including pilot lights- electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean up has been completed. Stop spill at source; dike areas to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up by sand, clay, earth, floor absorbent or other absorbent material and shoveled into containers. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.
Waste disposal method:
SMALL SPILL: Allow volatile portion to evaporate in hood. Allow sufficient time for vapors to completely clear hood ductwork. Dispose of remaining material in accordance with applicable regulations.
LARGE SPILLS: Destroy by liquid incineration. Contaminated absorbent may be disposed in a landfill in accordance with local, state and federal regulations.

SECTION 7: HANDLING AND STORAGE

HANDLING : See section 8, Exposure Controls/Personal Protection
STORAGE TEMPERATURE: Ambient
STORAGE PRESSURE: Atmospheric
GENERAL: Keep container closed. Loosen closure cautiously before opening,
STORAGE: Store in a cool well-ventilated place away from incompatible materials. (See SECTION 10 STABILITY AND REACTIVITY DATA)

1. Keep away from heat, sparks and flame.
2. Protect material from direct sunlight.
3. Ground and bond containers when transferring materials.
4. Empty containers may retain hazardous properties.
5. Follow all MSDS / label warnings even after container is emptied.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION : Local Exhaust: Yes ---- Mechanical (General): Yes----- Special: Non Listed------ Other: Non listed

RESPIRATORY PROTECTION: (Specify Type) A NIOSH / MSHA jointly approved air supplied respirator is advised in absence of proper environmental control

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised. However OSHA regulations also permit other types of safety glasses. Consult your safety representative for specific recommendations

SKIN PROTECTION: Wear resistant gloves. Consult your safety representative for specific recommendations.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: To prevent prolonged or repeated skin contact, wear impervious clothing and boots. Consult your safety representative for specific recommendations.

WORK HYGIENIC PRACTICES: Keep inhalation and skin exposure to a minimum. Wash before eating, smoking, or using the restroom.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Amber or Black

ODOR: Solvent odor

PHYSICAL STATE: Liquid

pH AS SUPPLIED: N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (con't)

BOILING POINT: @ 760.00 mm Hg
F: 133°
C: 56.1°

MELTING POINT: N/A

FREEZING POINT: N/A

VAPOR PRESSURE (mmHg): 181

VAPOR DENSITY (AIR = 1): 3.08

SPECIFIC GRAVITY (H2O = 1): .85

EVAPORATION RATE: (Butyl Acetate = 1) : 14.4

SOLUBILITY IN WATER: Negligible

VOLATILE ORGANIC COMPOUNDS (VOC): 4.31 #/Gal

VISCOSITY: 3000 cps

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Heat, sparks, flames and other sources of ignition.

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizing agents, acids

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide, carbon dioxide, and hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Carcinogenicity:
NTP: Not listed
IARC: monographs – not listed
OSHA: Regulated- not listed
Exposure to vapor or mist is possible. Short – term inhalation toxicity is low. Breathing small amounts during handling is not likely to cause harmful effects; breathing large amounts may be harmful.

Single dose oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.
EFFECTS OF CHRONIC OVEREXPOSURE:
Some reports have associated repeated and prolonged exposure to solvents with permanent brain damage and nervous system damage (sometime referred to as "solvent" or "painters" syndrome). Symptoms reported included fatigue, concentration difficulties, anxiety, depression, rapid mood swing, and short-term memory loss. These reports are not clear with regards to the type of solvents that cause these symptoms. There also is controversy among scientists as to whether the condition exists or is caused by this type of product. Since many diseases cause some or all of these symptoms, a doctor should be consulted if any symptoms appear.

This material(or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals.

Overexposure to this material (or its components) has apparently been found to cause the following effects in laboratory animals:
1. Liver abnormalities, 2. Kidney damage, 3. Nasal damage, 4. Brain damage.

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate pre-existing disorders of these organs in humans:
1. Mild, reversible liver effects/damage, 2. Mild reversible kidney effects/damage, 3. Nervous system damage, 4. Lung damage, 5. Nasal damage, 6. Testis damage.

Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate pre-existing disorders of these organs:
1. Central Nervous Systems Effects, 2. Visual impairment.

TOLUENE: Intentional misuse by deliberate inhalation of toluene has been associated with liver, kidney, and brain damage in humans. Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals; the human health consequences of this finding is uncertain.
N-HEXANE: Prolonged and repeated exposure to N-Hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of arms and legs) and result in muscular weakness and loss of sensation.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: no information available

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS: U-226
WASTE DISPOSAL METHOD: Consult an expert on the disposal of recovered material. Ensure disposal in compliance with governmental requirements and ensure conformity to local disposal regulations.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION
PROPER SHIPPING NAME: Adhesive 3 UN1133 PGII Flammable Liquid.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS
TSCA (TOXIC SUBSTANCE CONTROL ACT):

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):

Component	RQ (lbs.)
N-HEXANE	5000
ACETONE	5000
TOLUENE	1000

We recommend you contact local authorities to determine if there may be other local reporting requirements.
SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

311/312 HAZARD CATEGORIES: Immediate Health, Delayed Health, and Fire.

313 REPORTABLE INGREDIENTS: N-Hexane, Toluene, and Zinc Oxide.

SECTION 15: REGULATORY INFORMATION (CON'T)

INTERNATIONAL REGULATIONS:
ACOIN (AUSTRALIA) The intentional ingredients of this product are listed as follows: Toluene, Hexane.
DSL (CANADA) The intentional ingredients of this product are listed as follows: N-Hexane, Toluene
ELC (SOUTH KOREA) The intentional ingredients of this product are listed as follows : Toluene, Hexane.
EINECS (EUROPE) The intentional ingredients of this product are listed as follows: Toluene, Hexane.
ENCS (JAPAN) The intentional ingredients of this product are listed as follows: Toluene, Hexane.

STATE REGULATIONS:

California Proposition 65
The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.
BENZENE, TOLUENE

New Jersey RTK Label Information

N-HEXANE	110-54-3
ACETONE	67-64-1
TOLUENE	108-88-3

Pennsylvania RTK Label Information

N-HEXANE	110-54-3
ACETONE	67-64-1
TOLUENE	108-88-3

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and **International Epoxies & Sealers** disclaims any and all liability or legal responsibility or use or reliance upon same.