CA 2032

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Date Prepared: 05/08/06
Date Printed: 05/09/06
MSDS No: 525.0411195-001.001

CB C/V DYE CHESTNUT 12/16OZ

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity
Product Name: CB C/V DYE CHESTNUT 12/16OZ
SAP Material No: CBOOG014-0032

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Telephone Numbers
Emergency: 1-800-274-5263
Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
ACETONE	67-64-1	23.0- 33.0
A70 HYDROCARBON PROPELLANT (INDISC)	68476-86-8	18.0- 28.0
TOLUENE	108-88-3	19.0- 19.0
METHYL ETHYL KETONE	78-93-3	5.0- 15.0
NORMAL BUTANOL	71-36-3	5.0- 5.0
XYLENE	1330-20-7	5.0- 5.0
CALCIUM CARBONATE	1317-65-3	0.0- 10.0
TALC	14807-96-6	0.0- 10.0
ETHYLBENZENE	100-41-4	0.9- 1.1

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye
Can cause severe eye irritation and injure eye tissue.

Skin
Can cause skin irritation. Prolonged or repeated contact may dry and crack the skin. Passage through the skin may add to toxic effects from breathing or swallowing.

Swallowing
Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation
Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), tight feeling in the chest, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle weakness,

Continued on next page

respiratory depression (slowing of the breathing rate), blurred vision, shortness of breath, loss of coordination, confusion, irregular heartbeat, high blood sugar, narcosis (dazed or sluggish feeling), coma, and death.

Target Organ Effects

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Based on animal studies, exposure to methyl ethyl ketone (MEK) increases the onset of peripheral neuropathy caused by exposure to methyl butyl ketone (MBK), and/or n-hexane, and/or ethyl butyl ketone. MEK alone has not been shown to cause peripheral neuropathy. Prolonged intentional toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: cardiac sensitization, anemia, respiratory tract damage (nose, throat, and airways), testis damage, kidney damage, liver damage, lung damage, effects on hearing, central nervous system damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these organs: central nervous system effects, cardiac sensitization, anemia, effects on hearing, kidney damage.

Developmental Information

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

Cancer Information

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC (International Agency for Research on Cancer) has classified ethylbenzene as a possible human carcinogen.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

---

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Continued on next page

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidneys, central nervous system, male reproductive system, auditory system, Exposure to this material may aggravate any pre-existing condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with pre-existing heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

(for component) Lower 1.0 Upper 12.8 %

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Continued on next page

Extinguishing Media
regular foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions
Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating
Health - 2, Flammability - 4, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill
Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill
Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occured. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames, including pilot lights,electrical sparks).

7. HANDLING AND STORAGE

Handling
Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be mininized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Continued on next page

Storage
Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection
Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin Protection
Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Other protective equipment: eyewash station, emergency shower.

Respiratory Protections
If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls
Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines
Component

ACETONE (67-64-1)
OSHA VPEL 750.000 ppm - TWA
OSHA VPEL 1000.000 ppm - STEL
ACGIH TLV 500.000 ppm - TWA
ACGIH TLV 750.000 ppm - STEL

A70 HYDROCARBON PROPELLANT (INDISC) (68476-86-8)
No exposure limits established

TOLUENE (108-88-3)
OSHA VPEL 100.000 ppm - TWA
OSHA VPEL 150.000 ppm - STEL
ACGIH TLV 50.000 ppm - TWA ((Skin))
ACGIH TLV 0.000 mg/m3 - Ceiling ((Skin))

METHYL ETHYL KETONE (78-93-3)
OSHA VPEL 200.000 ppm - TWA
OSHA VPEL 300.000 ppm - STEL
ACGIH TLV 200.000 ppm - TWA
ACGIH TLV 300.000 ppm - STEL

NORMAL BUTANOL (71-36-3)
OSHA VPEL 50.000 ppm - Ceiling ((Skin))
ACGIH TLV 20.000 ppm - TWA

XYLENE (1330-20-7)
OSHA VPEL 100.000 ppm - TWA
OSHA VPEL 150.000 ppm - STEL

Continued on next page

ACGIH TLV 100.000 ppm - TWA
ACGIH TLV 150.000 ppm - STEL
OTHER LIMIT 46.000 ppm - TWA

CALCIUM CARBONATE (1317-65-3)
OSHA VPEL 5.000 mg/m3 - TWA respirable fraction
OSHA VPEL 15.000 mg/m3 - TWA total dust
ACGIH TLV 10.000 mg/m3 - TWA

TALC (14807-96-6)
OSHA VPEL 2.000 mg/m3 - TWA respirable dust (less than 1% crystalline silica)
ACGIH TLV 2.000 mg/m3 - TWA

ETHYLBENZENE (100-41-4)
OSHA VPEL 100.000 ppm - TWA
OSHA VPEL 125.000 ppm - STEL
ACGIH TLV 100.000 ppm - TWA
ACGIH TLV 125.000 ppm - STEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
(for component) 133.0 F (56.1 C)

Vapor Pressure
(for component) 185.000 mmHg @ 60.00 F

Specific Vapor Density
No data

Specific Gravity
No data

Liquid Density
No data

Percent Volatiles (Including Water)
No data

Volatile Organic Compounds (VOC) (Maximum)
416.000 g/l
3.470 lbs/gal

Evaporation Rate
No data

Appearance
No data

State
LIQUID

Physical Form
AEROSOL

Continued on next page

Color
VARIOUS

Odor
No data

pH
No data

10. STABILITY AND REACTIVITY

Hazardous Polymerization
Product will not undergo hazardous polymerization.

Hazardous Decomposition
May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability
Stable.

Incompatibility
Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information
Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101
DOT Description:
Not Regulated

Continued on next page

Container/Mode:
CASES/SURFACE - COMBUSTIBLE EXCEPTION

NOS Component:
None

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs)	Component
2000	XYLENES (O-, M-, P- ISOMERS)
5249	TOLUENE
17857	ACETONE
50000	ETHYL METHYL KETONE

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status
TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4

Component	Component
ACETONE	5000
TOLUENE	1000
METHYL ETHYL KETONE	5000
N-BUTYL ALCOHOL	5000
XYLENES (O-, M-, P- ISOMERS)	100
ETHYLBENZENE	1000

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate(X) Delayed(X) Fire(X) Reactive( ) Sudden Release of Pressure( )

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number
TOLUENE	108-88-3
N-BUTYL ALCOHOL	71-36-3
XYLENE (MIXED ISOMERS)	1330-20-7
ETHYLBENZENE	100-41-4

International Regulations

Inventory Status
DSL (CANADA) The intentional ingredients of this product are listed.

State and Local Regulations

California Proposition 65
The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.
ETHYL BENZENE

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.

Continued on next page

TOLUENE

New Jersey RTK Label Information

ACETONE	67-64-1
TOLUENE	108-88-3
METHYL ETHYL KETONE	78-93-3
N-BUTYL ALCOHOL	71-36-3
XYLENES	1330-20-7
TALC	14807-96-6
ETHYL BENZENE	100-41-4

Pennsylvania RTK Label Information

2-PROPANONE	67-64-1
BENZENE, METHYL-	108-88-3
2-BUTANONE	78-93-3
1-BUTANOL	71-36-3
BENZENE, DIMETHYL-	1330-20-7
LIMESTONE	1317-65-3
TALC (MG3H2(SIO3)4)	14807-96-6
BENZENE, ETHYL-	100-41-4

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.