CQ 1450

CAR BRITE

Material Safety Data Sheet

HMIS Ratings	
Health	2
Flammability	2
Reactivity	0
Protection	X

1 Chemical Product and Company Identification

Manufacturer Information	Wesmar Products, Inc. 1440 NW 45th St Seattle, Wa 98107
Phone	(206) 782-8186
Emergency Phone	1-800-424-9300 FOR INTERNATIONAL CALLS 703-527-3887
Date Prepared	2001-Oct-01
Supercedes	2001-Aug-31
Product Identity	FOAM PAD GLAZE
Product Code Number	A090
Product Use	Automotive Reconditioning Products
Version #	1.0
CAS #	Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits TLV-ACGIH	Carcinogen
SOLVENT NAPHTHA, PETROLEUM, MEDIUM ALIPH.	64742-88-7	15 - 40			No
KAOLIN	66402-68-4	7 - 13			No
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT	64742-47-8	3 - 7			No
1,2,3-PROPANETRIOL	56-81-5	1 - 5	10 mg/m3	10 mg/m3	No
ALUMINUM OXIDE (AL2O3)	1344-28-1	1 - 5	5 mg/m3	10 mg/m3	No
Non-hazardous and other ingredients below reportable levels	Proprietary	51.5	N/AP	N/AP	N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.

Inhalation Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Ingestion Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements

COMBUSTIBLE

4 First Aid Measures

First Aid

Skin	Immediately take off all contaminated clothing. For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to non-contaminated air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.
Notes to Physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Carbon dioxide. Alcohol foam.

General Fire Hazards

This product is combustible at high temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Flash Point	> 141 F PM
Flammability Limits in Air, Lower, % by Volume	0.7 %
Flammability Limits in Air, Upper, % by Volume	6 %

6 Accidental Release Measures

Containment Procedures

Eliminate sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Avoid prolonged or repeated skin contact with this material.

Storage Procedures

Keep the container tightly closed and in a cool, well-ventilated place. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material. Eye wash fountain and emergency showers are recommended.

9 Physical & Chemical Properties

Boiling Point	> 212 F
Specific Gravity	< 1
Vapor Pressure	< 20 mm/Hg
Evaporation Rate	faster than water
Vapor Density	> 1
Solubility (H2O)	Dispersible
pH	8
Freezing Point	32 F

10 Chemical Stability & Reactivity Information

Chemical Stability

Stable under normal conditions.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

General

This product is not regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

15 Regulatory Information

US Federal Regulations

CERCLA/SARA - Section 313 - Emission Reporting

ALUMINUM OXIDE (AL2O3)

KAOLIN

16 Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By	Technical Department
Issue Date	01-Oct-2001