SAFETY DATA SHEET

Issue Date 06-22-2018 **Revision Date** 06-22-2018 **Version** 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name:	CORRECTION™

Other means of identification

Common Name:	3180
UN/ID No	NA1993 (Domestic)
Synonyms	None
Product Categories	Automotive Polish

Recommended use of the chemical and restrictions on use

Sale and Use Restrictions	Not applicable
Recommended Use	Restricted to professional users.
Uses advised against	Consumer use

Details of the supplier of the safety data sheet

Supplier Address
MOC PRODUCTS CO., INC.
12306 Montague Street
Pacoima, CA 91331

Emergency telephone number

Company Phone Number	MOC PRODUCTS CO., INC. (818) 794-3500
Emergency Telephone	CHEMTREC 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Germ cell mutagenicity	Sub-category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements
Harmful if inhaled
May cause genetic defects
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Appearance Cream, Viscous **Physical state** Cream/ Lotion **Odor** Fruity

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment (if metal)
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response
If exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
IF SWALLOWED: Immediately call a POISON CONTROL CENTER or doctor/physician
Do not induce vomiting
In case of fire: Use CO_2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)
Other information
• Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %	Trade Secret
Aluminum Oxide	1344-28-1	10-20	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	0-20	*
Petroleum distillates, hydrotreated light	64742-47-8	0-20	*
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0-20	*
Decamethylcyclopentasiloxane	541-02-6	5-15	*
Montan Wax, mono and diester of ethylene glycol	73138-45-1	1-2	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice If exposed or concerned: Get medical advice/attention.

Skin contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Rinse immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before reuse.

Inhalation Remove to fresh air. Keep at rest position comfortable for breathing.

Eye contact Flush immediately with large amount of water for at least 15 minutes. Consult a physician.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Notes to Physician Aspiration hazard if swallowed - can enter lungs and cause damage. Causes central nervous system depression. Dermatitis may result from prolonged or repeated exposure.

Most important symptoms and effects, both acute and delayed

Symptoms Drowsiness, Dizziness, Headache, Hearing loss, Nausea, Vomiting, Coughing and/ or wheezing, Weakness, Unconsciousness. Skin irritation. Eye irritation.

Indication of any immediate medical attention and special treatment needed

Self-protection of the first aider Avoid breathing vapors or mists. Avoid contact with skin.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:
Use dry chemical, CO2, water spray (fog) or alcohol resistant foam.

Small Fire Dry chemical or CO2.

Large Fire Water spray or fog; Alcohol resistant foam.

Explosive properties: Risk of explosion if heated under confinement. Fire or intense heat may cause violent rupture of packages.

Specific hazards arising from the chemical
FLAMMABLE LIQUID AND VAPOR. Keep product and empty container away from heat and sources of ignition. May be ignited by heat, sparks or flames. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Hazardous combustion products Carbon monoxide, Carbon dioxide (CO_2), Hydrocarbons, Aldehydes, Silicon dioxide, Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

Specific methods:
Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge Yes. May be ignited by heat, sparks or flames.

Special firefighting procedures:
Flammable liquid and vapor. No action shall be taken involving any personal risk without suitable training. Evacuate surrounding areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not use a solid water stream as it may scatter and spread fire. Water mist may be used to cool closed containers. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Dike to collect large liquid spills. Do not allow run-off from fire-fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. See Section 8 for information on appropriate personal protective equipment. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Ensure adequate ventilation. Pay attention to flashback. Avoid dust formation.

For emergency responders Use personal protection recommended in Section 8. Remove all sources of ignition. Ventilate the area. Pay attention to flashback. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

Environmental precautions

Environmental precautions: Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Methods and material for containment and cleaning up

Methods for Containment Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to state, local, federal regulations.

Methods for clean-up: Clean-up methods - small spillage: Soak up with inert absorbent material. Shovel into suitable container for disposal. Clean-up methods - large spillage: Large spills present a vapor explosion and liquid fire hazard; evacuate area and ensure response by personnel trained and equipped to respond to flammable material incident or off-site emergency responders or fire department.

Prevention of secondary hazards Avoid dust formation. Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling: Avoid breathing (dust, vapor, mist, gas). Do not get in eyes, on skin, or on clothing. Do not store at temperatures above 120°F (50°C0. Protect from physical damage. Protect from freezing (<0°C, or 32°F). Keep product and empty container away from heat and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Store in a cool, well ventilated area. Empty containers retain product residue and can be hazardous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose these containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death.

Conditions for safe storage, including any incompatibilities

Technical measures/precautions: Mechanical ventilation required if used indoors on a continuous basis. Eye wash and safety shower should be easily accessible.

Materials to avoid: Chlorine, Strong oxidizing agents, Strong acids, Alkalis.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines .

Chemical Name	ACGIH TLV	OSHA Exposure Limits:	NIOSH IDLH
Aluminum Oxide 1344-28-1	TWA: 1 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction TWA: 10 mg/m³ total dust	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	-	Z1 PEL: 500 ppm TWA: 2900 mg/m³ Z1A TWA: 100 ppm TWA: 525 mg/m³ (as Stoddard Solvent)	-
Petroleum distillates, hydrotreated light 64742-47-8	-	Not established	-
Naphtha (petroleum), hydrotreated heavy 64742-48-9	-	Not established	-
Decamethylcyclopentasiloxane 541-02-6	-	Not established	-
Montan Wax, mono and diester of ethylene glycol 73138-45-1	-	Not established	-

Other information Decamethylcyclopentasiloxane (CAS#541-02-6): 10 ppm TWA 8Hrs.

Appropriate engineering controls

Engineering measures: Mechanical ventilation required if used indoors on a continuous basis. Eye wash and safety shower should be easily accessible.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear normal work clothing, Chemical resistant gloves (consult with the specific manufacturer to confirm performance).

Respiratory protection Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Use personal protective equipment. Avoid breathing (dust, vapor, mist, gas). Wash face, hands and any exposed skin thoroughly after handling. Take off contaminated clothing and wash it before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Cream/ Lotion		
Appearance	Cream, Viscous	**Odor**	Fruity
Color	Orange	**Odor threshold**	No information available

Property	**Values**	**Remarks • Method**
pH	No information available	Not applicable
Melting point/freezing point	No information available	
Boiling point / boiling range	> 93 °C / 200 °F	(based on components)
Flash point	47 °C / 117 °F	Pensky-Martens Closed Cup (PMCC)
Evaporation rate		
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
Upper flammability limit	No Data Available	
Lower flammability limit	No Data Available	
Vapor pressure	No Data Available	
Vapor density	No Data Available	Heavier than air
Specific Gravity	1.10	
Water solubility	Partially soluble	
Solubility in other solvents	No Data Available	
Partition coefficient	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Kinematic viscosity	No information available	
Dynamic viscosity	20,000-25,000 cPs	@ 25 °C
Explosive properties	No Data Available	
Oxidizing properties	No Data Available	

Other information

Softening point	No Data Available
Molecular weight	No Data Available
VOC Content (%)	
VOC Content (%)	14.06 Contains a VOC exempt solvent
Density	1.10 g/cc
Bulk density	No Data Available

10. STABILITY AND REACTIVITY

Reactivity

Reactivity Stable.

Chemical stability

Possibility of Hazardous Reactions May react with oxidizing agents

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Materials to avoid: Chlorine, Strong oxidizing agents, Strong acids, Alkalis.

Hazardous Decomposition Products

Hazardous Decomposition Products Carbon monoxide, Carbon dioxide (CO2), Hydrocarbons, Aldehydes, Silicon dioxide, Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Harmful if inhaled. May cause genetic defects. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Inhalation Harmful if inhaled. Avoid breathing vapors or mists. Do not breathe dust. Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye contact Contact with eyes may cause irritation.

Skin Contact May cause irritation.

Ingestion May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aluminum Oxide 1344-28-1	> 5000 mg/kg (Rat)	-	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Naphtha (petroleum), hydrotreated heavy 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
Decamethylcyclopentasiloxane 541-02-6	-	-	=8.67 mg/L (Rat) 4h dust-mist
Montan Wax, mono and diester of ethylene glycol 73138-45-1	> 2000 mg/kg (Rat)	-	-

Information on toxicological effects

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Skin Sensitization: Not expected. Respiratory Sensitization: Not classified.
Mutagenic effects: Is classified by the European Union as a mutagen of category 1B. Substances which should be regarded as being mutagenic to man.
Carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by IARC, NTP, or OSHA.
Reproductive toxicity No information available.
STOT - single exposure Not classified.
STOT - repeated exposure Category 1: Causes damage to organs through prolonged or repeated exposure.
Chronic toxicity Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged exposure may cause central nervous system damage. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects Liver, Kidney, Respiratory system, Eyes, Ears, Skin, Central nervous system, Blood, Stomach, Reproductive System.
Neurological effects Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system.
Other adverse effects Caused kidney effects in male rats which are not considered relevant to humans. Auditory system: prolonged and repeated exposure to high concentrations have resulted in hearing losses in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss. Results from a 2 year repeated vapor inhalation exposure study to rats of Decamethylcyclopentasiloxane (D5) indicate effects (uterine endometrial tumors) in female animals. This finding occurred at the highest exposure dose (160 ppm) only. Studies to date have not demonstrated if this effect occurs through a pathway that is relevant to humans. Based on the available information on its potential to cause harm to human health. Stomach irregularities.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	8210 mg/kg
ATEmix (dermal)	6539 mg/kg
ATEmix (inhalation-vapor)	19.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute Aquatic Toxicity: Harmful to aquatic life. Chronic Aquatic Toxicity: Toxic to aquatic life with long lasting effects.

32.1 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static		100: 48 h Daphnia magna mg/L EC50
Petroleum distillates, hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Naphtha (petroleum), hydrotreated heavy 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50		
Montan Wax, mono and diester of ethylene glycol 73138-45-1		50 - 100: 96 h Brachydanio rerio mg/L LC50 static		

Persistence and degradability
This product contains components which may be persistent in the environment.

Bioaccumulation
Bioaccumulative potential.

Mobility
No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Do not reuse container. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Limited quantity (LQ) < 5 Liters

DOT
UN/ID No NA1993

Proper Shipping Name:	Combustible liquid, n.o.s. (Solvent Naphtha)
Hazard Class	Comb. Liq.
Packing Group:	III
Emergency Response Guide Number	128

IATA

UN/ID No	NA1993
Proper Shipping Name:	Flammable liquids, n.o.s. (Solvent Naphtha)
Hazard Class	3
Packing Group:	III

IMDG

UN/ID No	UN1993
Proper Shipping Name:	Flammable liquids, n.o.s. (Solvent Naphtha)
Hazard Class	3
Packing Group:	III

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Federal Regulations

SARA 313
No SARA 313 chemicals are present above the reporting threshold.

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)
This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA
This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

State Regulations (RTK)

California Proposition 65
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm:

Chemical Name	CAS Number	California Proposition 65
Tetraethylrhodamine, Hydrochloride	81-88-9	Carcinogen
1,3-Dichloropropene	542-75-6	Carcinogen
Methylene chloride	75-09-2	Carcinogen
Ethylene oxide	75-21-8	Carcinogen Developmental Female Reproductive Male Reproductive
1,4-Dioxane	123-91-1	Carcinogen
Ethyl acrylate	140-88-5	Carcinogen
Acrylamide	79-06-1	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

U.S. EPA Label Information
EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA Rating
Health hazards 1

Flammability 2
Instability 0
Physical and Chemical Properties -
HMIS Rating
Health hazards 1*
Flammability 2
Physical hazards 0
Personal protection B
Chronic Hazard Star Legend ** = Chronic Health Hazard*

Prepared by Environmental Health and Safety Department
Issue Date 06-22-2018
Revision Date 06-22-2018
Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet