DE 2610.1000

Material Safety Data Sheet gemäß 91/155/EWG

Art.-Nr. 6.2610.1000

4CR 2610 Acrylic Putty

Date: 03.05.04 Revision Date: 08.01.04

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

Name, full adress and tel. of Company:

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC.

EINECS-Nr CAS-No.	Names R-phrases	Symb.	Conc.%
215-535-7 1330-20-7	xylene, mixture of isomers 10-20/21-38	Xn	2.5 - 10
203-933-3 112-07-2	2-butoxyethyl acetate 20/21	Xn	1 - 2.5
204-658-1 123-86-4	n-butyl acetate 10-66-67		10 - 12.5

Extra notices:
(See full text of R phrases under chapter 16)

3. HAZARDS IDENTIFICATION OF THE PREPERATION.

n.a.

10 Flammable.

4. FIRST AID MEASURES.

General :
In all causes of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation :
Remove or fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artifical respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Eye contact :
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact :
Remove contaminated clothing. Wash skin thorougly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion :
If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES.

Extinguishing media : recommended : alcohol resistant foam, CO2, powders, waterspray
not to be used : waterjet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run- off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercouses.
Clean preferabily with a detergent; avoid use of solvents.
If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE.

Handling.
Vapours are heavier than air and may spread along floors. Vapours may form Explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
Preperation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type
Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.
Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.
Smoking, eating and drinking should be prhibited in application area.
For personal protection se Section 8.
Never use pressure to empty : container is not a pressure vessel.
Always keep in containers of same material as the original one.
Comply with the health and safety at work laws.
Storage.
Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act.
Observe label precaution. Stoage: protected against frost on a dry, well ventilated place away from sources of heat and direct sunlight.
Keep away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials.
No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Material Safety Data Sheet
According to 91/155 EEC

Date: 03.05.04 Revision Date: 08.01.04

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

Engineering Measures.
Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.
Exposure Limits.
Occupational exposure limit for :

EINECS-No.	Names	STL mg/m3	LTL mg/m3
215-535-7	xylene, mixture of isomers	150	100 ppm
203-933-3	2-butoxyethyl acetate	50	20 ppm
204-658-1	n-butyl acetate	200	150 ppm

Personal Protection:
Respiratory protection.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection.
For prolonged or repeated contact, use :
Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occured.
Eye protection.
Use safety eyewear designed to protect against splash of liquids.
Skin protection.
Personel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9. PHYSICAL AND CHEMICAL PROPERTIES.

				Methode
Physical form	:	pasty		
color	:	see trade name		
odor		typical		
flash point	:	34	°C	DIN 53213
viscosity	:	at 20 oC 900 dPas		DIN 53211
density	:	1.54	g/cm3	
solvent content	:	21	%	
vapour pressure	:	2	mbar	
ignition temperature	:	280	°C	
boiling point	:	126	°C	
solid weight	:	79.28	%	
solid volume	:	41.34	1/100kg	
lower explosion limit	:	1.1	Vol. %	
upper explosion limit	:	8.0	Vol. %	
solubility in water	:	insoluble		

10. STABILITY AND REACTIVITY.

Stabile under recommended storage and handling conditions.(See section 7)
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.
Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION.

There are no data available on the preparation itself.
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsines and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
The liquid splashed in the eyes may cause irritation and reversible damage.
Remark: The product has not been tested as such, but is categorised by means of conventional method.(EC-Guidelines 1999/45/EC)

12. ECOLOGICAL INFORMATION.

The product should not be allowed to enter drains or water courses.

The preparation itself is labelled in accordance with the conventional dangerous preparations directive (1999/45/EG) as not dangerous for the environment.

13. DISPOSAL CONSIDERATIONS.

080111 waste paint and varnish containing organic solvents or other dangerous substances

Do not allow into drains or water courses.
Empty containers are to be deposited according to the official rules.

14. TRANSPORT INFORMATION.

Road/rail-transportation
ADR/RID According to 2.2.3.1.5
UN-Nr.: n.a.
Transport document: n.a.
contains:
Packaging group: n.a.
Sea transport
IMDG/Class: n.a.
EMS-Nr.: n.a.
UN-Nr.: n.a.
Proper shipping name:
contains: /

Packaging group: n.a.
Marine pollutant: n.a.

ICAO/IATA Class: 3 UN Nr. : 1866
Proper shipping name: Resin solution flammable

/

Packaging group : III

15. REGULARY INFORMATION.

The requirements of the Classification Packaging and Labelling of Dangerous Substances Regulations.(EC Guidelines 1999/45/EC)
The product is labelled as follows :
n.a.

Danger classification :
n.a.
contains:
R phrases:
10 Flammable.

S phrases:

38	In case of insufficient ventilation, wear suitable respiratory equipment.
51	Use only in well-ventilated areas.
23	Do not breathe vapour.

P phrases:
n.a.

Water hazard class: 2

VOC (g/l) DIN ISO 11890: 319.410

16. OTHER INFORMATION.

Full text of R phrases with no appearing in section 2 :

10	Flammable.
20/21	Harmful by inhalation and in contact with skin.
38	Irritating to skin.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

The information of this MSDS is based on the present state of our knowledge and on current EEC and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction.
It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.