SF 0631 Quickweld Kit

MATERIAL SAFETY DATA SHEET

650
3/21/2002

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QUICK SET ACTIVATOR
IES PART NUMBER: 650

MANUFACTURER: Wesmar Products, Inc.
ADDRESS: 1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

24 HOUR EMERGENCY PHONE: (INFOTRAC) 800-535-5053
INFORMATION PHONE: (800) 451-7206
DATE PREPARED: MARCH 21, 2002

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT:	CAS NO.	OSHA PEL-	ACGIH TLV	HAZARDOUS	% WT
ACETONE	67-64-1	1000ppm	750ppm	yes	99 %
N,N-DIMETHYL-P-TOLUIDINE	99-97-8	not listed	not listed	yes	1%

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM.

SAFETY RATING:
HEALTH; 1 (SLIGHT), FLAMMABILTY; 4 (EXTREME), REACTIVITY; 2 (MODERATE), CONTACT; 1 (SLIGHT)

POTENTIAL HEALTH EFFECTS
- EYES: Possible Irritation
- SKIN: Possible (Irritation and Dermatitis)
- INGESTION: Possible (May produce CNS depression)
- INHALATION: Possible (Irritant)

ACUTE HEALTH HAZARDS:
Liquid is severely irritating to eyes. High vapor concentration is also irritating to eyes.
Liquid is mildly irritating to skin. Prolonged or repeated contact will cause defatting of skin and lead to irritation and dermatitis.
If inhaled, high vapor concentration may lead to CNS depression. Ingestion may produce CNS depression

CHRONIC HEALTH HAZARDS: Unknown

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting eye and skin disorders May be aggravated by exposure to Acetone.

OTHER: Signs and symptoms of exposure, irritation as noted above, early to moderate CNS (Central Nervous System)
Depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases Unconsciousness and death may occur.
Medical conditions generally aggravated by exposure: preexisting eye and skin disorders may be aggravated by exposure to Acetone.

SECTION 4: FIRST AID MEASURES

EYES: Flush eyes with water. Hold eyelids open. Get medical attention if symptoms develop and persist.

SKIN: Remove clothing, flush exposed skin with water. Get medical attention if symptoms develop and persist.

INGESTION: ASPIRATION HAZARD. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE VOMITING .If vomiting occurs, keep head below hips to prevent aspiration into lungs. Get medical attention. never give unconscious person any thing by mouth.

INHALATION: Remove victim too fresh air and if needed, immediately begin artificial respiration. Give oxygen if breathing is labored Get emergency medical help. Contact Physician immediately.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: 12.8%
(% BY VOLUME / AIR) LOWER: 2.6%

FLASH POINT: (-15° F) (-26.1° C) METHOD USED: TCC

NFPA HAZARD CLASSIFICATION
HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 2

EXTINGUISHING MEDIA: Dry powder, Carbon Dioxide (CO^2) " Alcohol " Foam, use water to cool containers.

SPECIAL FIRE FIGHTING PROCEDURES: DANGER EXTREMELY FLAMMABLE. Get all people out of the area. Wear protective clothing and NIOSH approved pressure supplied masks. Cool containers first.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers may rupture from internal pressure if confined to fire area. Cool with water. Get non-essential people out of the area.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Danger ! Extremely Flammable, remove all ignition sources.
Small spills: Pick up with absorbent media. Store as hazardous waste.
Large Spills: Contain with dikes, pick up with vacuum truck. Handle as hazardous waste. Notify proper Local, State and Federal Agencies.
Vapor release: Get people out of the area, shut off ignition sources, and ventilate the area. Notify proper authorities if required by SARA Title III.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a cool, ventilated area, away from ignition sources. Store away from oxidizers or materials bearing a yellow "DOT" label.

OTHER PRECAUTIONS: Containers even those, which have been emptied, may contain explosive vapors. Do not cut, weld, grind or perform similar operations unless the container has been properly cleaned.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION : Local (preferred) and or general exhaust systems are recommended to keep employee exposures below the Airborne Exposure Limits.

RESPIRATORY PROTECTION: NIOSH approved organic vapor mask.

EYE PROTECTION: Chemical Goggled or full-face shield.

SKIN PROTECTION: Chemical resistant gloves suitable for Ketone Solvents.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not normally needed.

WORK HYGIENIC PRACTICES: Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown in Section VI. Launder contaminated clothing before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless, Mobile liquid.

ODOR: Mild odor.

BOILING POINT: 133° F, 56.1°C

MELTING POINT: (-139° F), (- 95°C)

VAPOR PRESSURE (mmHg): 175 @ 20° C

VAPOR DENSITY (AIR = 1): 2.0

SPECIFIC GRAVITY (H2O = 1): 0.80 @ 60° F

EVAPORATION RATE (BuAc=1): 5.6

SOLUBILITY IN WATER: Completely Soluble

VOLATILE ORGANIC COMPOUNDS (VOC): 791 grams / Liter

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Product is stable.
INCOMPATIBILITY (MATERIAL TO AVOID): Oxidizers or oxydizing materials. Mixing large quantities with cyanoacrylate adhesives will cause violent reaction.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon dioxide and carbon monoxide may form when heated to decomposition.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGY INFORMATION:

Ingredient	CAS#	NTP CARCINOGEN (KNOWN)	NTP CARCINOGEN OR (ANTICIPATED)	IARC CATEGORY
ACETONE:	67-64-1	NO	NO	NONE
N,N-DIMETHYL-P-TOLUIDINE:	99-97-8	NO	NO	NONE

SECTION 12: ECOLOGICAL INFORMATION:

ACETONE: CAS # 67-64-1;
Environmental Fate; When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to too quickly evaporate. When released into water, this material is expected to readily biodegrade. This material has a log octanol-water partition coefficient of less than 3.0. This material is not expected to significantly bioaccumulate. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to be readily removed from the atmosphere b wet deposition.
Environmental Toxicity: This material is not expected to be toxic to aquatic life. The LC50/96-hour values for fish are over 100 mg/l
N,N-DIMETHYL-P-TOLUIDINE: CAS # 99-97-8
Environmental Fate; No information found.
Environmental Toxicity; No information found.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: EPA approved hazardous waste disposal site. Follow applicable regulations.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION
PROPER SHIPPING NAME: Acetone
HAZARD CLASS: 3 (Flammable Liquid)
ID NUMBER: UN 1090
PACKING GROUP: II

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS
TSCA (TOXIC SUBSTANCE CONTROL ACT): 40 CFR 710 Sources of the raw materials used in this mixture assure that all chemical ingredients present are in compliance with TSCA.
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): RQ 5000
SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): Yes
Threshold Planning Quality: None **Reportable Quantity:** None

313 REPORTABLE INGREDIENTS:	CHEMICAL NAME	CAS #	WEIGHT %
	ACETONE	67-64-1	99

CLEAN AIR ACT; Yes **CLEAN WATER ACT:** Not Listed

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and **International Epoxies & Sealers** disclaims any and all liability or legal responsibility or use or reliance upon same.

SF 0012

MATERIAL SAFETY DATA SHEET

612
7/27/2005

Product Number: 612
Product Name: QUICK-WELD # 1 (Cyanoacrylate Adhesive)

Wesmar Products, Inc.
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

EMERGENCY PHONE: (INFOTRAC) (800) 535-5053
Information Phone (IES) (800) 451-7206

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Cyanoacrylate Adhesive
Product Type: Modified Cyanoacrylate Ester

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS NO.	%
Cyanoacrylate ester	Proprietary	90-95
Poly (methyl methacrylate)	9011-14-7	5-10
HYDROQUINONE	123-31-9	0.1-1

Ingredients, which have exposure limits

Exposure Limits: Ingredients	(TWA) ACGIH (TLV)	OSHA (PEL)	OTHER
Cyanoacrylate ester	None	None	0.2 ppm TWA
HYDROQUINONE	2mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWA 4 mg/m3 STEL

3. HAZARDS IDENTIFICATION

Toxicity: Skin contact may cause burns
Bonds skin rapidly and strongly
Skin and eye irritant

Primary Routes of Entry: None Known
Signs and Symptoms Of Exposure: Vapor is irritating to eyes and mucous membranes above TLV.
Exposure to vapors above the established limits may cause
Symptoms of non-allergic asthma.

Existing Conditions
Aggravated by Exposure: None Known

Ingredients	Literature Referenced Target organ and other Health Effects	Carcinogen NTP	IARC	OSHA
Cyanoacrylate ester	ALG IRR	NO	NO	NO
Poly (methyl methacrylate)	IRR	NO	N/A	NO
Cyanoacetate	NTO	NO	NO	NO
HYDROQUINONE	BLO BNM CNS IMM IRR LIV MUT	NO	N/A	NO

HYDROQUINONE BLO BNM CNS IMM IRR LIV MUT NO N/A NO SKI THY

Abbreviations

N/A Not Applicable	LIV Liver	BNM Bone Marrow	SKI Skin
BLO Blood	NTO No Target Organs	EYE eyes	
CNS Central nervous system	THY Thyroid	IRR Irritant	
IMM Immune System	ALG Allergen	MUT Mutagen	

4. First Aid Measures

Ingestion: Ingestion is not likely. See page 5 for emergency procedures.
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Soak in warm water. See page 5 for emergency procedures.
Eye Contact: Flush with water. See page 5 for emergency procedures.

5. Fire Fighting Measures

Flash Point: 185° F Method: Tag Closed Cup
Recommended
Extinguishing Agents: Carbon dioxide, foam, dry chemical
Special Firefighting
Procedures: Not Available
Hazardous Products Formed
By fire or thermal, decomp Irritating Organic vapors
Unusual fire or explosion Hazards None

Explosive Limits:
(% by volume in air) Lower Not Available
(% by volume in air) Upper Not Available

6. Accidental Release Measures

Steps to be taken in case
Of spill or leak: Flood with water to polymerize. Soak up with an inert Absorbent

7. Handling Controls, Personal Protection

Safe Storage: Store below 75° F
Heading: Avoid skin or eye contact. Avoid breathing vapor.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Safety glasses or goggles
Skin: Nitrile or polyethylene gloves and aprons
Do not use cotton
See supplemental page for additional information
Ventilation: Local ventilation may be desirable when using large amounts in a confined area.

Respiratory Not Available

See section 2 for Exposure Limits

9. Physical and Chemical Properties

Appearance: Water white to straw colored liquid
Odor: Negligible
Boiling Point: More than 300° F
Ph: Does not apply
Solubility in Water: Polymerized by water
Specific Gravity: 1.1
Volatile Organic Compound
(EPA Method 24) 32.9%; 345 grams per liter
Less than 20 g/l (California SCAQMD method 316B)
Vapor Pressure: Less than 0.02 mm Mg
Vapor Density: Not Available
Evaporation Rate:
(Ether=1) Not Available

10. Stability and Reactivity

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: Polymerized by contacts water, alcohols, amines or alkalis
Conditions to avoid: Not Available
Hazardous Decomposition Products (non-thermal): None

11. Toxicological Information:

Estimated oral LD50 more than 5000 mg/kg
Estimated dermal LD50 more than 2000 mg/kg

12. Ecological Information

No Data Available

13. Disposal Considerations

Recommended methods of Disposal: Polymerize as above. Incinerate following EPA and local Regulations

EPA Hazardous waste Number: NH- Not a RCRA Hazardous waste Material

14. Transportation Information

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name: Unrestricted (not more than 450 liters); Combustible Liquid (More than 450 liters)
Identification Number: None (Not more than 450 liters);
NA 1993 (more than 450 liters)
Marine Pollutant: None
IATA
Proper Shipping Name: Unrestricted (Not more than one pint)
Aviation regulated liquid, n.o.s., (Cyanoacrylate Ester) (More than one pint)
Class or Division: Unrestricted (Not more than one pint);
Class 9 (More than one pint)
UN or ID Number: None (Not More than one pint)
UN 3334 (More than one pint)

15. Regulatory Information

CA Proposition 65: No California Proposition 65 chemicals are known to be present.

16. Other Information

Estimated NFPA(R) Code:
Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 1
Specific Hazard: Does not apply

Estimated HMIS (R) Code:
Health Hazard: 2

Flammability Hazard: 2

16. Other Information
Reactivity Hazards: 1
Personal Protection: See Section 8

NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

DISCLAIMER:

The information contained within this MSDS applies only to the product to which the sheet relates. The information provided is based on our best knowledge at the time of issue.
The information contained within this MSDS is believed to be accurate and is given in good faith. However, no warranty is made, either express or implied, regarding its accuracy or any liability arising out of the use of the information herein or the product supplied.
When used in other preparations, formulations, or in mixtures, it is necessary to ascertain whether the classifications of the hazards have changed. The attention of the user is drawn to the possibility of creating other hazards when the product is used for purpose other than that for which it was recommended. In such cases, a reassessment may be necessary and should be made by the user.
This safety data sheet should only be used and reproduced in order that the necessary measures are taken relating to the protection of health and safety at work.
It is the responsibility of the handlers to pass on the totality of the information contained within this document to any subsequent person(s) who will come in to contact with, handle or use this product in any way.
They should check the adequacy of the information provided within this MSDS before passing it on to their customers/staff.

INFORMATION FOR FIRST AID AND CASUALTY ON TREATMENT FOR ADHESION OF HUMAN SKIN TO ITSELF IF: CAUSED BY CYANOACRYLATE ADHESIVES

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue including skin in seconds. Experience has shown that accidents due to cyanoacrylates are handled best by passive, non-surgical first aid. Treatment of specific types of accidents are given below.

SKIN ADHESION

First immerse the bonded surfaces in warm soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g. a spatula or a teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action.

EYELID TO EYELID OR EYEBALL ADHESION

In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation.

ADHESIVE ON THE EYEBALL

Cyanoacrylate introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, generally covering several hours. This will cause periods of weeping until clearance is achieved. During the period of contamination, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

MOUTH

If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in ½ to 2 days. In case a lump forms in the mouth, position the patient to prevent ingestion of the lump when it detaches

BURNS

Cyanoacrylates give off heat on solidification. In rare cases a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.

SURGERY

It should never be necessary to use such drastic method to separate accidentally bonded skin.

SF 0022

MATERIAL SAFETY DATA SHEET

622
7/27/2005

Product Number: 622
Product Name: QUICK-WELD # 2 (Cyanoacrylate Adhesive)

Wesmar Products, Inc.
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

EMERGENCY PHONE: (INFOTRAC) (800) 535-5053
Information Phone (IES) (800) 451-7206

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Cyanoacrylate Adhesive
Product Type: Modified Cyanoacrylate Ester

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS NO.	%
Cyanoacrylate ester	Proprietary	90-95
Poly (methyl methacrylate)	9011-14-7	5-10
HYDROQUINONE	123-31-9	0.1-1

Ingredients, which have exposure limits

Exposure Limits: Ingredients	(TWA) ACGIH (TLV)	OSHA (PEL)	OTHER
Cyanoacrylate ester	None	None	0.2 ppm TWA
HYDROQUINONE	2mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWA 4 mg/m3 STEL

3. HAZARDS IDENTIFICATION

Toxicity: Skin contact may cause burns
Bonds skin rapidly and strongly
Skin and eye irritant

Primary Routes of Entry: None Known
Signs and Symptoms Of Exposure: Vapor is irritating to eyes and mucous membranes above TLV.
Exposure to vapors above the established limits may cause
Symptoms of non-allergic asthma.

Existing Conditions
Aggravated by Exposure: None Known

Ingredients	Literature Referenced Target organ and other Health Effects	Carcinogen NTP	IARC	OSHA
Cyanoacrylate ester	ALG IRR	NO	NO	NO
Poly (methyl methacrylate)	IRR	NO	N/A	NO
Cyanoacetate	NTO	NO	NO	NO
HYDROQUINONE	BLO BNM CNS IMM IRR LIV MUT	NO	N/A	NO SKI THY

Abbreviations

N/A Not Applicable	LIV Liver	BNM Bone Marrow	SKI Skin
BLO Blood	NTO No Target Organs	EYE eyes	
CNS Central nervous system	THY Thyroid	IRR Irritant	
IMM Immune System	ALG Allergen	MUT Mutagen	

4. First Aid Measures

Ingestion: Ingestion is not likely. See page 5 for emergency procedures.
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Soak in warm water. See page 5 for emergency procedures.
Eye Contact: Flush with water. See page 5 for emergency procedures.

5. Fire Fighting Measures

Flash Point: 185° F Method: Tag Closed Cup
Recommended
Extinguishing Agents: Carbon dioxide, foam, dry chemical
Special Firefighting
Procedures: Not Available
Hazardous Products Formed
By fire or thermal, decomp Irritating Organic vapors
Unusual fire or explosion Hazards None

Explosive Limits:
(% by volume in air) Lower Not Available
(% by volume in air) Upper Not Available

6. Accidental Release Measures

Steps to be taken in case
Of spill or leak: Flood with water to polymerize. Soak up with an inert Absorbent

7. Handling Controls, Personal Protection

Safe Storage: Store below 75° F
Heading: Avoid skin or eye contact. Avoid breathing vapor.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Safety glasses or goggles
Skin: Nitrile or polyethylene gloves and aprons
Do not use cotton
See supplemental page for additional information
Ventilation: Local ventilation may be desirable when using large amounts in a confined area.

Respiratory Not Available

See section 2 for Exposure Limits

9. Physical and Chemical Properties

Appearance: Water white to straw colored liquid
Odor: Negligible
Boiling Point: More than 300° F
Ph: Does not apply
Solubility in Water: Polymerized by water
Specific Gravity: 1.1
Volatile Organic Compound
(EPA Method 24) 32.9%; 345 grams per liter
Less than 20 g/l (California SCAQMD method 316B)
Vapor Pressure: Less than 0.02 mm Mg
Vapor Density: Not Available
Evaporation Rate:
(Ether=1) Not Available

10. Stability and Reactivity

Stability: Stable
Hazardous
Polymerization: Will not occur
Incompatibility: Polymerized by contacts water, alcohols, amines or alkalis
Conditions to avoid: Not Available
Hazardous
Decomposition
Products (non-thermal): None

11. Toxicological Information:

Estimated oral LD50 more than 5000 mg/kg
Estimated dermal LD50 more than 2000 mg/kg

12. Ecological Information

No Data Available

13. Disposal Considerations

Recommended methods of Disposal: Polymerize as above. Incinerate following EPA and local Regulations

EPA Hazardous waste Number: NH- Not a RCRA Hazardous waste Material

14. Transportation Information

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name: Unrestricted (not more than 450 liters); Combustible Liquid
(More than 450 liters)
Identification Number: None (Not more than 450 liters);
NA 1993 (more than 450 liters)
Marine Pollutant: None
IATA
Proper Shipping Name: Unrestricted (Not more than one pint)
Aviation regulated liquid, n.o.s., (Cyanoacrylate Ester) (More than one pint)
Class or Division: Unrestricted (Not more than one pint);
Class 9 (More than one pint)
UN or ID Number: None (Not More than one pint)
UN 3334 (More than one pint)

15. Regulatory Information

CA Proposition 65: No California Proposition 65 chemicals are known to be present.

16. Other Information

Estimated NFPA(R) Code:
Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 1
Specific Hazard: Does not apply

Estimated HMIS (R) Code:
Health Hazard: 2

Flammability Hazard: 2

16. Other Information
Reactivity Hazards: 1
Personal Protection: See Section 8

NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

DISCLAIMER:

The information contained within this MSDS applies only to the product to which the sheet relates. The information provided is based on our best knowledge at the time of issue.
The information contained within this MSDS is believed to be accurate and is given in good faith. However, no warranty is made, either express or implied, regarding its accuracy or any liability arising out of the use of the information herein or the product supplied.
When used in other preparations, formulations, or in mixtures, it is necessary to ascertain whether the classifications of the hazards have changed. The attention of the user is drawn to the possibility of creating other hazards when the product is used for purpose other than that for which it was recommended. In such cases, a reassessment may be necessary and should be made by the user.
This safety data sheet should only be used and reproduced in order that the necessary measures are taken relating to the protection of health and safety at work.
It is the responsibility of the handlers to pass on the totality of the information contained within this document to any subsequent person(s) who will come in to contact with, handle or use this product in any way.
They should check the adequacy of the information provided within this MSDS before passing it on to their customers/staff.

INFORMATION FOR FIRST AID AND CASUALTY ON TREATMENT FOR ADHESION OF HUMAN SKIN TO ITSELF IF: CAUSED BY CYANOACRYLATE ADHESIVES

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue including skin in seconds. Experience has shown that accidents due to cyanoacrylates are handled best by passive, non-surgical first aid. Treatment of specific types of accidents are given below.

SKIN ADHESION

First immerse the bonded surfaces in warm soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g. a spatula or a teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action.

EYELID TO EYELID OR EYEBALL ADHESION

In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation.

ADHESIVE ON THE EYEBALL

Cyanoacrylate introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, generally covering several hours. This will cause periods of weeping until clearance is achieved. During the period of contamination, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

MOUTH

If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in ½ to 2 days. In case a lump forms in the mouth, position the patient to prevent ingestion of the lump when it detaches

BURNS

Cyanoacrylates give off heat on solidification. In rare cases a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.

SURGERY

It should never be necessary to use such drastic method to separate accidentally bonded skin.