Material Safety Data Sheet gemäß 91/155/EWG

Art.-Nr. 6.0407.1001
Art.-Nr. 6.0407.1002
Art.-Nr. 6.0407.0501
Art.-Nr. 6.0407.2501
Art.-Nr. 6.0407.2503

4CR 0407 Universal Hardener

Date: 17.02.03 Revision Date: 28.01.03

DE 0407.1001
1002
0501
2501
2503

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

Name, full adress and tel. of Company:

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC.

EINECS-No. CAS-No.	R-phrases	Symb.	Conc.%
215-535-7 1330-20-7	xylene, mixture of isomers 10-20/21-38	Xn	2.5 - 10
223-810-8 4083-64-1	4-isocyanatosulphonyltoluene 14-36/37/38-42	Xn	< 1
204-658-1 123-86-4	n-butyl acetate 10-66-67		25 - 50
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate 10-36	Xi	2.5 - 10
28182-81-2	Homopolymer of HDI 43	Xi	25 - 50
265-199-0 64742-95-6	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified 10-37-51/53-65-66-67	Xn,N	2.5 - 10

(See full text of R phrases under chapter 16)

3. HAZARDS IDENTIFICATION OF THE PREPERATION.

Xi irritant

10	Flammable.
43	May cause sensitisation by skin contact.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67	Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES.

General :
In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation :
Remove or fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artifical respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Eye contact :
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
Skin contact :
Remove contaminated clothing. Wash skin thorougly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion :
If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES.

Extinguishing media : recommended : alcohol resistant foam, CO2, powders, water spray
not to be used : waterjet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run- off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a siutable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts), concentrated (d : 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts), water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to local regulations (see section 13).
Do not allow to enter drains or watercouses.
If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE.

Persons with a history of asthma, allergies, chronic or recurrentent respiratory disease should not be employed in any process in which this preparation is used
Handling.

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Material Safety Data Sheet
According to 91/155 EEC

Keep container tightly closed. Precautions should be taken to inimise exposure to atmospheric humidity or water : CO_2 will be formed which in closed containers can result in pressuration. Care should be taken when re-opening partly used containers. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.
Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.
Smoking, eating and drinking should be forbidden in application area.
For personal protection se Section 8.
Never use pressure to empty : container is not a pressure vessel.
Always keep in containers of same material as the original one.
Comply with the health and safety at work laws.
Storage.
Observe label precaution. Store between 15°C and 30 oC in a dry, well ventilated place away from sources of heat and direct sunlight.
Keep away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials as well as of amines, alcohols and water. No smoking. Prevent unauthorized access.
Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in original containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

Persons with a history of asthma, allergies, chronic or recurrentent respiratory disease should not be employed in any process in which this preparation is used.
Engineering Measures.
Provide adequate ventilation. This should be achieved by the use of local exhaust ventilation and good general extraction.
Airfed protective respiratory equipment must be worn by spray operator even when good ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.
Exposure Limits.
Occupational exposure limit for :

EINECS-No.	Names	STL mg/m3	LTL mg/m3
215-535-7	xylene, mixture of isomers	150	100 ppm
204-658-1	n-butyl acetate	200	150 ppm
203-603-9	2-methoxy-1-methylethyl acetate	100	50 ppm
	Homopolymer of HDI	MAK	0 ppm
265-199-0	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha unspecified	MAK	50 ppm

Personal Protection:
Respiratory protection:
By spraying: air fed respirator.
By other operations than spraying : in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and paticulate filter mask.
Hand protection.
For prolonged or repeated contact, use :
Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.
Eye protection.
Use safety eyewear designed to protect against splash of liquids.
Skin protection.
Personel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. ***

9. PHYSICAL AND CHEMICAL PROPERTIES.

				Method
Physical state	:	liquid		
color	:	colourless		
odor	:	typical		
flash point	:	30		DIN 53213
viscosity	:	at 23 oC	13 s 4 mm	DIN 53211
specific gravity	:	0.97	g/cm3	
vapour pressure 23 °C	:	5	mbar	
lower explosion limit	:	1.1		
solubility in water	:	insoluble		
solvent content	:	64	%	
boiling point	:	126	°C	
ignition temperature	:	315	°C	
solid weight	:	36.15	%	
solid volume	:	30.94	1/100kg	

10. STABILITY AND REACTIVITY.

Dangerous conditions:
Stable under recommended storage and handling conditions. (See section 7)
Dangerous reactions:
Keep well away from strongly acidic and strongly alkaline materials as well as from oxidising agents.
Amines and alcohols may produce exotermic reactions. The product reacts slowly with water liberating carbon dioxide. Risk of pressure in the sealed containers which may cause container deformation,swelling or in extremly situation even bursting.

Dangerous products of decoposition :
When exposed to high temperatures these products may produce hazardous decomposition products such as carbon monoxide and dioxide,smoke, oxides of nitrogen as well as hydrocyanic acid, isocyanate monomers, amines and alcohols.

11. TOXICOLOGICAL INFORMATION.

There are no data available on the preparation itself.
Acrylic components of the preparation have irritating properties.
Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc. Cases of allergic skin reactions have been observed .
The liquid splashed in the eyes may cause irritation.
The inhalation of aerial droplets or aerosols may cause irritation of the respiratory tract.
Ingestion may cause collapse, severe respiratory difficulties and central nervous system stimulation.
Remarks: The product has not been tested as such, but categorised by means of conventional method (EC-Guidelines 1999/45/EC)

12. ECOLOGICAL INFORMATION.

The product should not be allowed to enter drains or water courses.
The preparation itself is labelled in accordance with the conventional dangerous preparations directive (1999/45/EG) as not dangerous for the environment.

13. DISPOSAL CONSIDERATIONS.

080111 waste paint and varnish containing organic solvents or other dangerous substances

Do not allow into drains or water courses.
Wastes and empty containers are to be deposited according to the official rules.

14. TRANSPORT INFORMATION.

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

ADR/RID Class: 3
UN no. : 1263
Transport document: Paint related material
contains

IMDG/GGVS Class: 3
EmS: F-E, S-E
UN-no.: 1263
Proper shipping name: PAINT RELATED MATERIAL
Packaging group: III
Marine pollutant :n.a.

ICAO/IATA Class: 3 UN no. : 1263
Proper shipping name: Paint related material

Packaging group :III

15. REGULATORY INFORMATION.

The requirements of the Classification Packaging and Labelling of Dangerous Substances Regulations.
The product is labelled as follows :

Xi irritant

Danger classification :
Homopolymer of HDI
contains::

R phrases:

10	Flammable.
43	May cause sensitisation by skin contact.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67	Vapours may cause drowsiness and dizziness.

S phrases:

24	Avoid contact with skin.
37	Wear suitable gloves.
38	In case of insufficient ventilation, wear suitable respiratory equipment.
51	Use only in well-ventilated areas.
61	Avoid release to the environment. Refer to special instructions/safety data sheets.
23	Do not breathe vapour.

P phrases:

91	Contains isocyanates. See information supplied by the manufacturer.

Water hazard class: 2
VOC (g/l) DIN ISO 11890: 619.272

VOC (g/l) ASTM D-3960-1: 619.306

16. OTHER INFORMATION.

Full text of R phrases with no appearing in section 2 :

10	Flammable.
20/21	Harmful by inhalation and in contact with skin.
38	Irritating to skin.
14	Reacts violently with water.
36/37/38	Irritating to eyes, respiratory system and skin.
42	May cause sensitisation by inhalation.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.
36	Irritating to eyes.
43	May cause sensitisation by skin contact.
37	Irritating to respiratory system.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.

The information of this MSDS is based on the present state of our knowledge and on current EEC and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction.
It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.

The information in this Safety Data Sheet is required pursuant to Dangerous Substances Regulations 1984.