


WHMIS Code

N/A
None

Material Safety Data Sheet

ResistAll Paint Sealant w/ EnviroGuard



Section 1 - Material Identification and Use

Manufacturer's Name..... **Cal-Tex Protective Coatings, Incorporated**
 Manufacturer's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 Emergency Phone Number..... INFOTRAC 1-800-535-5053 24 Hours Per Day, 7 Days Per Week
 Supplier Name and Identifier..... **Cal-Tex Protective Coatings, Incorporated**
 Supplier's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 MSDS Prepared By Ronnie L. Meadows (210) 564-3200
 Trade Name..... **ResistAll Paint Sealant w/ EnviroGuard**
 Product Use..... Auto Paint Sealant Protector

Section 2 - Hazardous Ingredients of Material

No.	Chemical Identity	Concentration	CAS	PEL	TLV	STEL	IDLH
2	Solvent Naphtha (Petroleum) Medium Aliphatic	Trade Secret	64742-88-7	100	100	N/A	
4		Trade Secret					
5	Organic Emulsion	Trade Secret	Mixture				
6	Poly (Dimethylsiloxane)	Trade Secret	63148-62-9				

NA = Not Applicable ND = No Data Available < = Less Than > = More Than * Ceiling Value ** Chemical Believed to be a Potential Carcinogen (NIOSH)

Section 3 - Hazardous Identification

EYE	☒	This chemical may affect the eye or visual capacity	WHMIS Warning: None
SKIN	☒	This chemical may affect the dermal layer of the body	
LUNGS	☒	This chemical may irritate or damage pulmonary tissue	
NERVOUS SYSTEM	☐	This chemical may produce a toxic affect on the nervous system	
REPRODUCTIVE	☐	May affect reproductive capabilities including mutations and effects on the fetus.	
BLOOD	☐	This chemical may act on the blood or hematopoietic system; decrease hemoglobin function; deprive tissue of oxygen	
LIVER	☐	This chemical may produce liver damage - Hepatotoxins	None
KIDNEYS	☐	This chemical may produce kidney damage - Neprotoins	

Section 4 - First Aid Measures


INGESTION	☒	DO NOT induce vomiting. Rinse mouth with water and give plenty of milk. Never give liquids to an unconscious victim - Seek Immediate Medical Attention
EYE CONTACT	☒	Flush immediately with plenty of water for at least 15 minutes - Seek Medical Attention
SKIN CONTACT	☒	Wash thoroughly with soap and water - Seek Medical Attention if irritation persists
INHALATION	☒	Remove to fresh air. If breathing is difficult give oxygen - If not breathing give artificial respiration -Get Medical Attention
SPECIAL	☐	None Identified

WHMIS Code

N/A
None

Material Safety Data Sheet

ResistAll Paint Sealant w/ EnviroGuard



Section 5 - Fire-Fighting Measures

Flashpoint F

N/A

Flashpoint C

N/A

Upper Explosion Limit

Not Determined

Lower Explosion Limit

Not Determined

Auto-Ignition Temp.

Not Determined

Extinguishing Media

Carbon dioxide, dry chemical, water fog, water spray, foam.

☐ DO NOT USE WATER

Special Fire Fighting Procedures

Use self contained breathing apparatus when fighting large fires.

Section 6 - Accidental Release Measures

Spill and Leak
Requirements

Small leaks-mop up, wipe up, or soak up immediately. Large spills-contain material and ventilate area. Do not dump into sewers, on the ground, or into any body of water.

Section 7 - Handling and Special Storage

Handling and
Special Storage

Keep containers closed when not in use. Store in a cool place with adequate ventilation. Storage location should be constructed for containment and dilution/neutralization of spills.

Additional Storage
Requirements

Section 8 - Exposure Controls and Personal Protection

Eye Protection

Wear approved eye protection to safeguard against potential eye contact, irritation.

Skin Protection

Wear gloves to avoid prolonged contact with skin.

Comments

N/A

Section 9 - Physical and Chemical Properties

Physical State

Liquid-Cream

Odor and Appearance

Light Brown Cream - Slight Solvent Odor

Specific Gravity

0.9916

Vapour Pressure

Not Determined

Vapour Density

>1

Evaporation Rate

Like Water

Boiling Point

220 F

Freezing Point

Not Determined

pH

6.5

Density (g/ml)

Not Determined

Section 10 - Stability and Reactivity

Stability

☒ Material is Stable☐ Material is NOT Stable

Incompatibility

Strong Oxidizing Material

Hazardous Decomposition Products

Thermal decomposition may yield carbon monoxide and/or carbon dioxide

Hazardous Polymerization

☐ May Occur☒ Will NOT Occur


MSDS Number: 4

WHMIS Code

N/A
None

Material Safety Data Sheet

ResistAll Paint Sealant w/ EnviroGuard



Section 11 - Toxicological Information

Acute Over Exposure Effects	Not Determined
Chronic Over Exposure Effects	Not Determined
Eye Contact	May cause irritation.
Skin Contact	May cause irritation, avoid prolonged contact with skin.
If Inhaled	N/A
If Swallowed	May cause damage to gastrointestinal tissue which may include pain, vomiting, nausea, abdominal tenderness, burns of mouth, difficulty swallowing, blood in vomitus, blood in feces, and ulceration.

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Dispose in accordance with local, state, and federal regulations.

Section 14 - Transportation Information

Ship as per DOT requirements in 49 CFR. Ship in accordance with local, state, and federal regulations.

Section 15 - Regulatory Information

No.	Chemical Identity	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
2	Solvent Naphtha (Petroleum) Medium Aliphatic																						
4																							
5	Organic Emulsion																						
6	Poly (Dimethylsiloxane)																						

(1) EHS-RQ (2) CERCLA (3) RQ (4) CAA 122r (5) TPQ (6) FIFRA (7) RCRA Code (8) Cal-CARC (9) Priority Pollutant (10) Cal-Well Monitoring (11) SARA 313 (12) SARA 302 (13) MCL (14) Cal-HOT SPOT (15) Cal-Drinking Water (16) Cal-Toxic Air (17) NESHAP (18) Cal-Prop 65 (19) DOT Inhalation (20) Director's List (21) EPA Air (22) Cal-Reg Pest.

An "X" in Column 11 indicates that this product contains a toxic chemical subject to the reporting requirements of Section 313 of EPCRA (40 CFR 372)

MSDS No.	4	Date Reviewed	4/15/2007	Prepared By	Ronnie L. Meadows
Trade Name	ResistAll Paint Sealant w/ EnviroGuard	Supersedes	5/23/2002	Phone Number	(210) 564-3200

TLV - Threshold Limit Value. An estimate of the average safe airborne concentration of a substance in representative conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. TLVs are published annually by the ACGIH (American Conference of Governmental Industrial Hygienists).
 PEL - Permissible Exposure Limit. The OSHA limit of employee exposure to chemicals; found primarily in 29 CFR 1910.1000.
 STEL - Short Term Exposure Limit. The maximum concentration for a continuous 15-minute exposure period.
 IDLH - Immediately Dangerous to Life and Health. The concentration of a airborne chemical which may cause irreversible health effects or death.
 Ceiling - The maximum allowable concentration to which an employee may be exposed.

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using this product, read label. The information contained in this publication is intended for general information purposes only. This publication is not a substitute for review of the applicable government regulations and standards, and should not be construed as legal advice or opinion. Readers with specific questions should refer to the cited references.