


WHMIS Code

N/A
None

Material Safety Data Sheet

NG Vinyl / Leather Sealant



Section 1 - Material Identification and Use

Manufacturer's Name..... **Cal-Tex Protective Coatings, Incorporated**
 Manufacturer's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 Emergency Phone Number..... INFOTRAC 1-800-535-5053 24 Hours Per Day, 7 Days Per Week
 Supplier Name and Identifier..... **Cal-Tex Protective Coatings, Incorporated**
 Supplier's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 MSDS Prepared By Ronnie Meadows (210) 564-3200
 Trade Name..... **NG Vinyl / Leather Sealant**
 Product Use..... Protecting automotive vinyl and leather

Section 2 - Hazardous Ingredients of Material

No.	Chemical Identity	Concentration	CAS	PEL	TLV	STEL	IDLH
1	Benzophenone	Trade Secret	119-61-9				
2		Trade Secret					
3	Dimethicone Emulsion Mixture	Trade Secret	MIXTURE	N/A	N/A	N/A	N/A
4	2-Polyacrylic Acid	Trade Secret	9003-01-4				
5	Lanolin	Trade Secret	61792-81-6	n/a	n/a	n/a	
6	Nonionic Fluoropolymer Emulsion	Trade Secret					
7	Nonionic Surfactant	Trade Secret	26027-38-3				
8	Decamethylcyclotrisiloxane	Trade Secret	541-02-6				

NA = Not Applicable ND = No Data Available < = Less Than > = More Than * Ceiling Value ** Chemical Believed to be a Potential Carcinogen (NIOSH)

Section 3 - Hazardous Identification

EYE	☒	This chemical may affect the eye or visual capacity	WHMIS Warning: None
SKIN	☒	This chemical may affect the dermal layer of the body	
LUNGS	☒	This chemical may irritate or damage pulmonary tissue	
NERVOUS SYSTEM	☐	This chemical may produce a toxic affect on the nervous system	
REPRODUCTIVE	☐	May affect reproductive capabilities including mutations and effects on the fetus.	
BLOOD	☐	This chemical may act on the blood or hematopoietic system; decrease hemoglobin function; deprive tissue of oxygen	
LIVER	☐	This chemical may produce liver damage - Hepatotoxins	
KIDNEYS	☐	This chemical may produce kidney damage - Neprotoins	

Section 4 - First Aid Measures


INGESTION	☒	DO NOT induce vomiting. Rinse mouth with water and give plenty of milk. Never give liquids to an unconscious victim - Seek Immediate Medical Attention
EYE CONTACT	☒	Flush immediately with plenty of water for at least 15 minutes - Seek Medical Attention
SKIN CONTACT	☒	Wash thoroughly with soap and water - Seek Medical Attention if irritation persists
INHALATION	☒	Remove to fresh air. If breathing is difficult give oxygen - If not breathing give artificial respiration -Get Medical Attention
SPECIAL	☐	None Identified

WHMIS Code

N/A
None

Material Safety Data Sheet

NG Vinyl / Leather Sealant



Section 5 - Fire-Fighting Measures

Flashpoint F
Flashpoint C

N/A
N/A

Upper Explosion Limit
Lower Explosion Limit
Auto-Ignition Temp.

Not Determined
Not Determined
Not Determined

Extinguishing Media

Carbon dioxide, dry chemical, water fog, water spray, foam.

☐ DO NOT USE WATER

Special Fire Fighting Procedures

Use self contained breathing apparatus when fighting large fires.

Section 6 - Accidental Release Measures

Spill and Leak Requirements

Small leaks-mop up, wipe up, or soak up immediately. Large spills-contain material and ventilate area. Do not dump into sewers, on the ground, or into any body of water.

Section 7 - Handling and Special Storage

Handling and Special Storage

Keep from sources of ignition. Keep containers closed when not in use. Store in a cool place with adequate ventilation. Storage location should be constructed for containment and dilution/neutralization of spills

Additional Storage Requirements

Section 8 - Exposure Controls and Personal Protection

Eye Protection

Wear approved eye protection to safeguard against potential eye contact, irritation or injury.

Skin Protection

Wear chemical resistant gloves, avoid long term contact.

Comments

None needed with proper engineering controls. Use when concentrations exceed the PEL/TLV. Maintain ventilation to keep vapor concentration below the PEL/TLV.

Section 9 - Physical and Chemical Properties

Physical State

Liquid

Odor and Appearance

Sweet odor, milky liquid

Specific Gravity

Not Determined

Vapour Pressure

Not Determined

Vapour Density

Not Determined

Evaporation Rate

Not Determined

Boiling Point

Not Determined

Freezing Point

Not Determined

pH

Not Determined

Density (g/ml)

Not Determined

Section 10 - Stability and Reactivity

Stability

☒ Material is Stable

☐ Material is NOT Stable

Incompatibility

Strong Oxidizing Material

Hazardous Decomposition Products

Thermal decomposition may yield carbon monoxide and/or carbon dioxide

Hazardous Polymerization

☐ May Occur


☒ Will NOT Occur

WHMIS Code

N/A
None

Material Safety Data Sheet

NG Vinyl / Leather Sealant



Section 11 - Toxicological Information

Acute Over Exposure Effects	Not Determined
Chronic Over Exposure Effects	Not Determined
Eye Contact	May produce eye irritation. If contact occurs, rinse eyes for 15 minutes with water and seek medical attention.
Skin Contact	May cause irritation, wash with soap and water, seek medical attention if irritation persists.
If Inhaled	If inhaled move to fresh air, seek medical attention.
If Swallowed	If swallowed may cause irritation, do not induce vomiting, seek medical attention.

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Section 14 - Transportation Information

Section 15 - Regulatory Information

No.	Chemical Identity	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
1	Benzophenone																						
2																							
3	Dimethicone Emulsion Mixture																						
4	2-Polyacrylic Acid																						
5	Lanolin																						
6	Nonionic Fluoropolymer Emulsion																						
7	Nonionic Surfactant																						
8	Decamethylcycllopentasiloxane																						

(1) EHS-RQ (2) CERCLA (3) RQ (4) CAA 122r (5) TPQ (6) FIFRA (7) RCRA Code (8) Cal-CARC (9) Priority Pollutant (10) Cal-Well Monitoring (11) SARA 313 (12) SARA 302 (13) MCL (14) Cal-HOT SPOT (15) Cal-Drinking Water (16) Cal-Toxic Air (17) NESHAP (18) Cal-Prop 65 (19) DOT Inhalation (20) Director's List (21) EPA Air (22) Cal-Reg Pest.

An "X" in Column 11 indicates that this product contains a toxic chemical subject to the reporting requirements of Section 313 of EPCRA (40 CFR 372)

MSDS No.	226	Date Reviewed	1/20/2010	Prepared By	Ronnie Meadows
Trade Name	NG Vinyl / Leather Sealant	Supersedes	1/20/2010	Phone Number	(210) 564-3200

TLV - Threshold Limit Value. An estimate of the average safe airborne concentration of a substance in representative conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. TLVs are published annually by the ACGIH (American Conference of Governmental Industrial Hygienists).
 PEL - Permissible Exposure Limit. The OSHA limit of employee exposure to chemicals; found primarily in 29 CFR 1910.1000.
 STEL - Short Term Exposure Limit. The maximum concentration for a continuous 15-minute exposure period.
 IDLH - Immediately Dangerous to Life and Health. The concentration of a airborne chemical which may cause irreversible health effects or death.
 Ceiling - The maximum allowable concentration to which an employee may be exposed.

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using this product, read label. The information contained in this publication is intended for general information purposes only. This publication is not a substitute for review of the applicable government regulations and standards, and should not be construed as legal advice or opinion. Readers with specific questions should refer to the cited references.