

MATERIAL SAFETY DATA SHEET

Tarr

Date Issued: 06/30/2005

MSDS No: S365

Date-Revised: 03/09/2007

Revision No: 1

MINERAL SPIRITS 365

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MINERAL SPIRITS 365**PRODUCT CODE:** S365**ALTERNATE TRADE NAME(S):** SOLVENT 365, S325**MANUFACTURER**

Distributed by Tarr, LLC

P.O. Box 12570

Portland OR 97212

Service Number: 503-288-5294**24 HR. EMERGENCY TELEPHONE NUMBERS****CHEMTREC (US Transportation) :**(800) 424 - 9300**CANUTEC (Canadian Transportation) :**(613) 996 - 6666

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW**IMMEDIATE CONCERNS:** WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed.

Vapor harmful. May cause central nervous system depression. May be irritating to eyes and skin.

POTENTIAL HEALTH EFFECTS**EYES:** Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating.

Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness.

SKIN: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).**INGESTION:** Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonia.**INHALATION:** Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression.**SIGNS AND SYMPTOMS OF OVEREXPOSURE****ACUTE TOXICITY:** Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonia may be evidenced by coughing, labored breathing and cyanosis.**MEDICAL CONDITIONS AGGRAVATED:** Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product.**COMMENTS HEALTH:** Male rats exposed for 90 days by inhalation to vapors of similar solvents showed evidence of kidney damage. The relevance of this effect to humans is unknown. In one of the studies a low grade anemia was also observed.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Solvent naphtha (petroleum), medium aliphatic	100	064742-88-7

COMMENTS: Contains the following constituents: Xylenes (1330-20-7) less than 1 % by weight and trimethylbenzene, 1,2,4,- less than 1% by weight.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Immediately wash skin with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, DO NOT INDUCE vomiting. If conscious, have victim rinse mouth out with water, then drink sips of water to remove taste from mouth. DO NOT GIVE LIQUIDS TO A DROWSY, CONVULSING OR UNCONSCIOUS PERSON. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Transport to nearest medical facility for additional treatment.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (110°F) to (143°F) TAG CC

FLAMMABLE LIMITS: 0.01 to 0.07

AUTOIGNITION TEMPERATURE: No data available.

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: Clear fire area of all non-emergency personnel. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus. Containers exposed to intense heat from fires should be cooled with large quantities of water to prevent weakening of container structure which could result in container rupture.

FIRE FIGHTING EQUIPMENT: The use of SCBA is recommended for firefighters. Water spray may be used to cool containers exposed to heat or flame.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Remove all sources of ignition and provide ventilation. Wear protective clothing as given in section 8. Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material with absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal using non-sparking equipment. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for proper disposal.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Store away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Do not weld, cut, grind, solder, or drill on or near empty containers. Empty containers may contain explosive concentrations of product vapors.

STORAGE TEMPERATURE: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles and face shield in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild odor.

COLOR: Clear, colorless liquid.

pH: 5.5 to 6.0

PERCENT VOLATILE: 100

VAPOR PRESSURE: < 5

VAPOR DENSITY: Heavier than air.

BOILING POINT: (320°F) to (372°F)

FREEZING POINT: NDA = no data available.

MELTING POINT: No data available.

FLASHPOINT AND METHOD: (110°F) to (143°F) TAG CC

SOLUBILITY IN WATER: Negligible

EVAPORATION RATE: Slower than ether.

DENSITY: 6.4

SPECIFIC GRAVITY: 0.775 to 0.785

(VOC): 6.400 lbs./gal.

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Solvent naphtha (petroleum), medium aliphatic	25000	> 4000	> 700

CHRONIC: Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Not listed as a carcinogen by the NTP, IARC, or OSHA.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Petroleum distillates, n.o.s.

TECHNICAL NAME: (naphtha solvent)

PRIMARY HAZARD CLASS/DIVISION: Combustible liquid

UN/NA NUMBER: UN 1268

PACKING GROUP: III

NAERG: 128

OTHER SHIPPING INFORMATION: USDOT combustible exception: 173.150(f)(1).

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes
CHRONIC: Yes

313 REPORTABLE INGREDIENTS: Xylenes (CAS 1330-20-7) and Trimethylbenzene, 1,2,4,-
(CAS 95-63-6)

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

16. OTHER INFORMATION

PREPARED BY: P. Rodabaugh

REVISION SUMMARY: Revision #: 1 This MSDS replaces the March 08, 2006 MSDS. Any changes in information are as follows: In Section 1 Reason for Issue In Section 14 DOT Primary Hazard Class/Division Labels Other DOT Shipping Information In Section 15 SARA 311/312 Hazard Categories 302/304 Emergency Planning In Section 16 Additional MSDS Information

HMIS RATING

HEALTH:	☐	1
FLAMMABILITY:	☐	2
PHYSICAL HAZARD:	☐	0
PERSONAL PROTECTION:	H	

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.