


SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 1

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL		0
PPE	X	



Printed: 07/11/2012
Revision: 04/15/2011
Supercedes Revision: 02/17/2011

1. Product and Company Identification

Product Code: 1616

Product Name: General Purpose Automotive Lacquer Thinner

Manufacturer Information

Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113

Phone Number: (901)775-0100

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Web site address: www.wmbarr.com

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Intended Use: Paint thinning

Synonyms
CWT50, GWT50, DWT50

2. Hazards Identification

GHS Hazard Phrases

No data available.

GHS Precaution Phrases

No data available.

GHS Response Phrases

No data available.

GHS Storage and Disposal Phrases

No data available.

Potential Health Effects (Acute and Chronic)

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness; headache; watering of eyes; irritation of respiratory tract; weakness; drowsiness; nausea; numbness in fingers, arms and legs; depression of central nervous system; loss of appetite; fatigue; hallucinations; light headedness; visual disturbances; giddiness and intoxication; sleepiness; cough and dyspnea; cold, clammy extremities; diarrhea; vomiting; dilation of pupils; spotted vision. Severe overexposure may cause convulsions; unconsciousness; coma; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

May be absorbed through the skin. May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

Ingestion Acute Exposure Effects:

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 2
Printed: 07/11/2012
Revision: 04/15/2011
Supersedes Revision: 02/17/2011

Poison. Cannot be made non-poisonous. May be fatal or cause blindness. May cause dizziness; headache; nausea; vomiting; burning sensation in mouth, throat, and stomach; loss of coordination; depression of the central nervous system; narcosis; stupor; gastrointestinal irritation; liver, kidney, and heart damage; diarrhea; loss of appetite; coma and death. May produce symptoms listed under inhalation.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. Prolonged skin contact may result in absorption of a harmful amount of this material. May cause conjunctivitis; gastric disturbances; insomnia; dizziness; headache; weakness; fatigue; nausea; heart palpitations; skin irritation; numbness in hands and feet; permanent central nervous system changes; some loss of memory; pancreatic damage; giddiness; visual impairment or blindness; kidney or liver damage; and death. May cause symptoms listed under inhalation.

Target Organs: Central Nervous System, Liver, Kidney, Heart, Stomach, Respiratory System

Primary Routes of Entry: Inhalation, Ingestion, Skin Absorption

Signs and Symptoms Of Exposure

See Potential Health Effects.

Medical Conditions Generally Aggravated By Exposure

Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	10.0 -30.0 %
2. Toluene {Benzene, Methyl-, Toluol}	108-88-3	30.0 -60.0 %
3. Acetone {2-Propanone}	67-64-1	15.0 -40.0 %
4. Light aliphatic solvent naphtha (petroleum)	64742-89-8	0.5 -1.5 %

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or artificial medical assistance can be rendered.

Skin Contact:

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

Ingestion:

Call your local poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.

Note to Physician

Poison. This product contains methanol. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Call your local poison control center for further information.

5. Fire Fighting Measures

Flammability Classification: NFPA Class IB
Flash Pt: 0 F (-17.8 C) Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits: LEL: 1 % UEL: 36 %
Autoignition Pt: No data available.

Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Flammable Properties and Hazards

Extremely flammable. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by an ignition source, such as pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from the material handling point. Product residue can ignite explosively. Do not weld or cut on empty containers.

Hazardous Combustion Products

Carbon monoxide and carbon dioxide, other various unburned hydrocarbons.

Suitable Extinguishing Media

Use carbon dioxide, dry powder, or alcohol resistant foam.

Unsuitable Extinguishing Media

None known.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

Keep out of confined spaces, sewers, and bodies of water.

7. Handling and Storage

Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 4
Printed: 07/11/2012
Revision: 04/15/2011
Supersedes Revision: 02/17/2011

Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA TWA	ACGIH TWA	Other Limits
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
3. Acetone {2-Propanone}	67-64-1	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
4. Light aliphatic solvent naphtha (petroleum)	64742-89-8	No data.	No data.	No data.

Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV.

For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection

Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury.

Protective Gloves

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile, rubber, and unsupported neoprene may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance Practices

Wash hands thoroughly after use and before eating, drinking, or smoking.
Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Melting Point:	No data.
Boiling Point:	130 F (55.0 C) - 230 F (111.7 C)

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 5
Printed: 07/11/2012
Revision: 04/15/2011
Supersedes Revision: 02/17/2011

Autoignition Pt: No data.
Flash Pt: 0 F (-17.8 C) Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits: LEL: 1 % UEL: 36 %
Specific Gravity (Water = 1): 0.82
Density: 6.824 LB/GL
Vapor Pressure (vs. Air or mm Hg): No data.
Vapor Density (vs. Air = 1): > 1
Evaporation Rate: > 1
Solubility in Water: Slight
Percent Volatile: 100 % by weight.
VOC / Volume: 530 G/L
Appearance and Odor
Water White / Free and Clear

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

No data available.

Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents, strong caustics.

Acetone may form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol.

Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide; carbon dioxide; formaldehyde; and unidentified organic compounds in black smoke.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions

No data available.

11. Toxicological Information

Toxicological Information

This product has not been tested as a whole. Information below will be for individual ingredients.

Acute Toxicity:

Methanol:

LD50 Rat oral 5628 mg/kg
LC50 Rat inhalation 64000 ppm/4 hr
LC50 Rat inhalation 87.5 mg/L/6 hr
LD50 Rabbit dermal 15,800 mg/kg bw

Toluene:

LD50 Rat oral 2.6 to 7.5 g/kg
LD50 Rabbit dermal 14.1 ml/kg
LC50 Mouse ihl 400 ppm/24 hr
LC50 Mice inhalation 5320 ppm/8 hr

Acetone:

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 6
Printed: 07/11/2012
Revision: 04/15/2011
Supersedes Revision: 02/17/2011

LD50 Rat oral 10.7 mL/kg (=8450 mg/kg bw); acetone given by gastric intubation to groups of five non-fasted Carworth-Wistar female rats
LD50 Rat oral 9800 mg/kg/ bw
LD50 Rabbit oral 5340 mg/kg bw
LC50 Rat inhalation exposure 76 mg/L/4 hr

Skin Corrosion/Irritation:

Methanol, toluene, and acetone are skin irritants.

Serious Eye Damage/Irritation:

Methanol and acetone are eye irritants.

Toluene is a severe eye irritant.

Respiratory or Skin Sensitization: No data available.

Aspiration Hazard: No data available.

Chronic Toxicological Effects

This product has not been tested as a whole. Information below will be for individual ingredients.

Germ Cell Mutagenicity: No data available.

Reproductive Toxicity: Gross toluene exposure during pregnancy can produce renal toxicity, fetal toxicity, and teratogenicity.

STOT-Single Exposure: No data available.

STOT-Repeated Exposure: No data available.

Carcinogenicity/Other Information

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

ACGIH A4 - Not Classifiable as a Human Carcinogen.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	n.a.	n.a.	n.a.	n.a.
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	n.a.	3	A4	n.a.
3. Acetone {2-Propanone}	67-64-1	n.a.	n.a.	A4	n.a.
4. Light aliphatic solvent naphtha (petroleum)	64742-89-8	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information

No information available for this product as a whole. Information below will be for individual ingredients:

Toxicity:

Toluene: LC50 FOR BLUEGILL WAS 17 MG/L/24 HR & 13 MG/L/96 HR

Acetone: LC50 Pimephales promelas (Fathead minnow, age 33 days, length 22.6 mm, weight 0.159 g) 8,120 mg/L/96 h (95% confidence limit: 7,530-8,760 mg/L); flow through, 25.0 deg C, dissolved oxygen 6.7 mg/L, hardness 48.5 mg/L CaCO₃, alkalinity 45.8 mg/L CaCO₃, pH 7.58 /99% pure/

Persistence and Degradability:

Toluene is readily degradable.

Acetone: Based on a vapor pressure of 231 mm Hg at 25 deg C, acetone is expected to exist solely as a vapor in

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 7
Printed: 07/11/2012
Revision: 04/15/2011
Supersedes Revision: 02/17/2011

the ambient atmosphere. Vapor-phase acetone is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals with an estimated atmospheric half-life of about 79 days. Acetone also undergoes photodecomposition by sunlight with an estimated half-life of about 80 days.

Bioaccumulative Potential:

Methanol is not expected to bioaccumulate in the environment.

Toluene: Bioaccumulation is low to moderate.

Acetone: Volatilization from moist soil surfaces is also expected based upon the measured Henry's Law constant of 3.97×10^{-5} atm-cu m/mol. This compound is expected to biodegrade under aerobic and anaerobic conditions based upon the results of numerous screening tests. If released into water, acetone is not expected to adsorb to suspended solids or sediment based upon its estimated Koc value. Methyl ethyl ketone may volatilize from dry soil surfaces based upon its vapor pressure.

Mobility in Soil:

Methanol is expected to have very high mobility in soil.

Toluene is expected to have high to moderate mobility in soil.

Acetone is expected to have very high mobility in soils.

Other Adverse Effects: No data available.

13. Disposal Considerations

Waste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations.

Keep out of sewers and bodies of water.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name	Paint Related Material
DOT Hazard Class:	3
DOT Hazard Label:	FLAMMABLE LIQUID
UN/NA Number:	UN1263
Packing Group:	II

LAND TRANSPORT (Canadian TDG)

UN Number:	1263
Hazard Class:	3 - FLAMMABLE LIQUID
Packing Group:	II

Additional Transport Information

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 8
Printed: 07/11/2012
Revision: 04/15/2011
Supercedes Revision: 02/17/2011

15. Regulatory Information

Canadian Chemical Lists

Hazardous Components (Chemical Name)	CAS #	Canadian NPRI	Canadian IDL
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	Yes	Yes
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	Yes	Yes
3. Acetone {2-Propanone}	67-64-1	No	Yes
4. Light aliphatic solvent naphtha (petroleum)	64742-89-8	Yes	No

Canadian WHMIS Classification

No data available.

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	No	Yes 5000 LB	Yes	No
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	No	Yes 1000 LB	Yes	Yes
3. Acetone {2-Propanone}	67-64-1	No	Yes 5000 LB	No	Yes
4. Light aliphatic solvent naphtha (petroleum)	64742-89-8	No	No	No	No

US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	HAP, ODC ()	No	Inventory	Yes
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	HAP, ODC ()	Yes	Inventory, 8A CAIR	Yes
3. Acetone {2-Propanone}	67-64-1	HAP, ODC ()	No	Inventory, 4 Test	No
4. Light aliphatic solvent naphtha (petroleum)	64742-89-8	HAP, ODC ()	No	Inventory	No

International Regulatory Lists

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

☒ Yes ☐ No Acute (immediate) Health Hazard

☒ Yes ☐ No Chronic (delayed) Health Hazard

☒ Yes ☐ No Fire Hazard

☐ Yes ☒ No Sudden Release of Pressure Hazard

☐ Yes ☒ No Reactive Hazard

Regulatory Information

This product has been classified according to the hazard criteria of the Controlled Products Regulations.

Concentrations reported in section 2 are weight/weight.

Ingredients disclosed in section 2 are on Canadian DSL.

Methanol WHMIS Classification: B2, D1B, D2A, D2B

Methanol WHMIS Health Effects Criteria Met by this Chemical:

D1B - TDG class 6.1 packing group unknown - toxic - immediate

D2A - Teratogenicity and embryotoxicity - very toxic - other

D2B - Eye irritation - toxic - other

Methanol WHMIS Ingredient Disclosure List: Included for disclosure at 1% or greater. Meets criteria for disclosure at 0.1%.

SAFETY DATA SHEET

General Purpose Automotive Lacquer Thinner

Page: 9
Printed: 07/11/2012
Revision: 04/15/2011
Supersedes Revision: 02/17/2011

Acetone WHMIS Classification: B2, D2B

Acetone WHMIS Health Effects Criteria Met by this Chemical:

D2B - Eye irritation - toxic - other

Acetone WHMIS Ingredient Disclosure List: Included for disclosure at 1% or greater.

Toluene WHMIS Classification: B2, D2A, D2B

Toluene WHMIS Health Effects Criteria Met by this Chemical:

D2A - Teratogenicity and embryotoxicity - very toxic - other

D2B - Skin irritation - toxic - other

Toluene WHMIS Ingredient Disclosure List: Included for disclosure at 1% or greater. Meets criteria for disclosure at 0.1% or greater.

16. Other Information

Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.