

PRODUCT CODE : AR 9100
 PRODUCT NAME : TMP SURFACE PREP
 TYPE OF PRODUCT : Aerosol Automotive Surface Prep
 DOT CLASS : CONSUMER COMMODITY,ORM-D

HMIS CODES: H F R P
 2* 3 0 J

===== SECTION I - MANUFACTURER'S IDENTIFICATION =====

MANUFACTURED BY : Wesmar Products, Inc.
 ADDRESS : 1440 NW 45th St. Seattle, WA 98107

24-HOUR EMERGENCY : CALL CHEMTREC 1-800-424-9300 (SPILL, LEAK, FIRE, ACCIDENT)

NAME OF PREPARER : RUDD COMPANY, INC.

DATE PREPARED/REVISED: 04/05/2001

DATE PRINTED: 04/10/01

REASON REVISED : Format Update

CAS NUMBER	HAZARDOUS COMPONENTS	WT. %	---OCCUPATION EXPOSURE LIMITS---			VAPOR PRESSURE	
			OSHA PEL**	ACGIH TLV	OTHER	mm HG @ Temp	
00074-98-6	PROPANE	15	Simple	Asphyxiant	1000 ppm	3619	70
00075-28-5	ISOBUTANE	5	Not Est.	800 ppm	(estimate)		
00100-41-4	ETHYL BENZENE	13.64	100 ppm	100 ppm	434 mg/m3	10	77
00106-97-8	N-BUTANE	10	Not Est	800 ppm	1900 mg/m3	>999	64
01330-20-7	XYLENE	56	100 ppm	100 ppm	434 mg/m3	25	77

**=PELS represent lowered 1989 limits and may not be enforceable by Federal OSHA.

===== SECTION IIB - OTHER REGULATORY INFORMATION =====

CAS NUMBER	DESCRIPTION	CARCINOGEN		SARA TITLE III		CALIFORNIA	
		NTP	IARC OSHA	302	313	P65	I II
00074-98-6	PROPANE						
00075-28-5	ISOBUTANE						
00100-41-4	ETHYL BENZENE		X		X		
00106-97-8	N-BUTANE						
01330-20-7	XYLENE				X	X	

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE : 279 to 279 deg F. WT/GAL: 7.25 (W/ PROP: 6.13)
 VAPOR DENSITY : HEAVIER THAN AIR SOLIDS BY % WEIGHT: 0.00
 EVAPORATION RATE : FAST compared to n-butyl acetate CALCULATED V.O.C. : 5.88 LB/GL
 SOLUBILITY IN WATER: NEGLIGIBLE 706 GR/LT

HAPS BY % WEIGHT : 100

APPEARANCE AND ODOR: CLEAR TRANSPARENT LIQUID, SWEET AROMATIC ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASS: Class IC Flammable

BULK PRODUCT FLASH POINT : 76 deg F. METHOD USED:

BULK PROPELLANT FLASH POINT : -156 deg F.

PACKAGED PRODUCT FLAME EXTENSION: **0 deg F

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.0% UPPER: 9.5%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all unnecessary personnel. Use full protective equipment, including self-contained breathing apparatus. Use water spray, preferably fog, to cool closed containers to prevent pressure build-up and possible explosion. Direct water stream is not recommended for oil base fires. Product may float and reignite on surface of water. Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams or waterways.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Explosive air-vapor mixtures may form which are dangerous when exposed to heat or flame. Vapors are heavier than air and may travel along the ground, or be moved by ventilation, and ignited by pilot lights, stoves, heaters, electric motors, sparks, flame, smoking, static discharge or other ignition sources even at locations distant from material handling site. Contents under pressure. Exposure to heat or prolonged exposure to sun may cause bursting.

===== SECTION V - REACTIVITY DATA =====

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Other Organic Compounds.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong Oxidizing agents.

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID:

High temperature and humidity, ignition source, vapor build-up.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, skin contact.

ACUTE EFFECTS FROM SHORT TERM EXPOSURE:

INHALATION: Vapors and mists irritate nose, throat and lungs (burning, stinging, coughing). May Cause headache, dizziness, nausea, weakness, shortness of breath and loss of coordination. Exposure to extremely high vapor concentrations may cause unconsciousness and asphyxiation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EYES: Contact with liquid or vapors causes severe irritation (redness, watering, itching, stinging, blurred vision).

SKIN: Contact causes severe irritation (dryness, itching, cracking, rash and swelling) and possible burns.

SKIN ABSORPTION: Unknown.

SWALLOWING: Causes nausea, vomiting and diarrhea.

CHRONIC EFFECTS FROM LONG TERM/REPEATED EXPOSURE: Long-term or repeated overexposure, without proper ventilation or personal protection, may cause damage to: kidneys, liver, heart, brain and nervous system, dermatitis or other skin disorders.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Respiratory tract irritation nausea eye disorders skin disorders sensitization to chemical substances.

===== SECTION VII - EMERGENCY AND FIRST AID PROCEDURES =====

SWALLOWING: In case of accidental ingestion call Poison Center, Emergency Room or Physician immediately.

INHALATION: Remove from exposure to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get medical attention immediately.

EYE: Immediately flush with plenty of water for 15 minutes, while lifting upper and lower eyelids. Get medical attention.

SKIN: Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash or clean thoroughly before reuse. Get medical attention if irritation persists.

OTHER: Have Material Safety Data Sheet available if possible when calling Poison Center, Emergency Room or Physician.

===== SECTION VIII - PERSONAL PROTECTION =====

RESPIRATORY PROTECTION: If affected by odors or vapors, wear a respirator (NIOSH/MSHA TC-23C or equivalent) during use. If product gives off spray mists, wear respirator with pre-filter or particle mask to avoid breathing spray mists.

VENTILATION: Open doors and windows to provide fresh air ventilation, in work and surrounding areas, during and after application until all vapors (fumes) are gone.

HAND PROTECTION: Wear gloves to avoid skin contact.

EYE PROTECTION: Wear safety glasses or goggles to protect eyes from splash and spray mists. Note: Contact lenses may contribute to the severity of an eye injury and should not be worn when working with chemical products.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing to avoid skin contact with liquid or mists.

WORK/HYGIENIC PRACTICES: Wash hands after using and before eating, drinking or using tobacco products. Thoroughly clean contaminated clothing and shoes before reuse.

===== SECTION IX - SPILL OR LEAK PROCEDURES =====

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Eliminate ignition sources and ventilate area. Evacuate all unnecessary personnel. Wear full protective equipment. Dike drains to prevent entering storm or sanitary sewers, rivers, streams or waterways. Contain spill and cover with inert absorbent material. Take up using non-sparking tools (aluminum, brass or copper) and place mixture into containers for disposal. Note: Some spills or releases may require special reporting to local, state or federal agencies.

WASTE DISPOSAL: Waste material and empty containers must be disposed of in accordance with all local, state and federal environmental control regulations. Use only approved waste management facilities.

DOT/CERCLA:

The DOT/CERCLA reportable quantity (RQ) for this product is 172 gallons based on XYLENE RQ 1000 pounds.

===== SECTION X - SPECIAL PRECAUTIONS =====

HANDLING PRECAUTIONS: Keep liquid spray and vapors away from heat, sparks and flame. Turn off or remove all sources of ignition. Use proper methods of ventilation to prevent vapor build-up. Avoid spraying hot surfaces. Avoid breathing vapors, spray mists and sanding or grinding dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate methods of ventilation, respiratory and personal protective equipment. Do not heat, puncture or incinerate containers. Contents are under pressure and may contain explosive vapors, even when empty. Do not remove or deface label.

SHIPPING AND STORAGE PRECAUTIONS: Contents under pressure. Do not store above 120oF or permit prolonged exposure to sunlight. Protect containers from damage. Store in buildings or areas designed and protected for storage of aerosols. Keep out of reach of children. Do not store where contact with incompatible material could occur, even during an accidental spill or release.

===== SECTION XI - DISCLAIMER =====

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.