

BS 0320-GS&R 1 gal

# MATERIAL HEALTH AND SAFETY BULLETIN



|                                                                                                       |  |
|-------------------------------------------------------------------------------------------------------|--|
| MANUFACTURER'S NAME<br>Wesmar Products, Inc<br>1440 NW 45th St<br>Seattle, WA 98107<br>(206) 787-8186 |  |
| STREET ADDRESS                                                                                        |  |
| CITY, STATE, AND ZIP CODE                                                                             |  |
| EMERGENCY TELEPHONE NO.<br>(818) 786-2251                                                             |  |

|                                                                                                                                                      |                                                                                                                                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT: G.S.&R. #320<br><br>GENERIC NAME: GLAZING/SEALANT & RESEALER<br>CHEMICAL FAMILY:<br>DOT PROPER SHIPPING NAME: POLISHING COMPOUND,<br>LIQUID | WARNING STATEMENT:<br><br>HARMFUL IF SWALLOWED - DO NOT INDUCE<br>VOMITING - CONTAINS PETROLEUM DISTIL-<br>LATES. IF EYE CONTACT, RINSE WELL WITH<br>WATER. KEEP OUT OF THE HANDS OF CHILD-<br>REN. |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Section I - INGREDIENTS

|                                                                                                 | TLV* |                                                                        | TLV* |
|-------------------------------------------------------------------------------------------------|------|------------------------------------------------------------------------|------|
| HYDRO-CARBON MIXTURE<br>ATTAPULGITE<br>CALCINED KAOLIN                                          | 200  | CAS #64742-47-8<br>CAS #8031-18-3<br>CAS #66402-68-4                   |      |
| HMIS HAZARD INDEX<br><br>4 - Severe<br>3 - Serious<br>2 - Moderate<br>1 - Slight<br>0 - Minimal |      | HMIS RATINGS<br><br>Health.....1<br>Flammability..0<br>Reactivity....0 |      |

\*Threshold Limit Value

A. OSHA ☒

B. ACGIH ☐

C. See Section III ☐

D. Other ☐

## Section II — EMERGENCY AND FIRST AID PROCEDURES

EMERGENCY: Have a physician call LOS ANGELES POISON CONTROL CENTER (24 hrs.) 213/664-2121

|              |                                                                                                                                                                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye Contact  | If this product comes in contact with the eyes flush with large quantities of water for at least 15 minutes and seek immediate medical attention.                                                                                                       |
| Skin Contact | If this product comes in contact with the skin wash with soap and large quantities of water. Seek medical attention if irritation from contact persists.                                                                                                |
| Inhalation   | If breathing difficulties, dizziness or lightheadedness occur when working in areas with high vapor concentrations, victim should seek fresh air free of vapors. If breathing stops, begin artificial respiration and seek immediate medical attention. |
| Ingestion    | If this product is swallowed DO NOT induce vomiting. Seek immediate medical advice and/or attention.                                                                                                                                                    |

## Section III — PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

|                  |                                                                                                                            |
|------------------|----------------------------------------------------------------------------------------------------------------------------|
| Eye Effects      | This product may be an eye irritant.                                                                                       |
| Skin Effects     | Prolonged or repeated skin contact may result in dermatitis.                                                               |
| Systemic Effects | Various studies have shown a possible association with exposure to this product and the following:<br>Nausea and vomiting. |

| Section IV — SPECIAL PROTECTION INFORMATION |                                                                                                                                                                                                                                                                                                                                                                                         |                |                                                                                                                                        |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Respiratory Protection<br>Specify Type      | The use of respiratory protection depends on vapor concentration above the time-weighted TLV; use a NIOSH approved cartridge respirator or a gas mask.                                                                                                                                                                                                                                  |                |                                                                                                                                        |
| Ventilation                                 | General mechanical ventilation may be sufficient to keep product vapor concentrations within specified time-weighted TLV ranges. If general ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required. Other special precautions such as respiratory masks or environmental containment devices may be required in extreme cases. |                |                                                                                                                                        |
| Protective Gloves                           | The use of impermeable gloves is advised to prevent skin irritation in sensitive individuals.                                                                                                                                                                                                                                                                                           | Eye protection | Safety glasses, chemical goggles and/or face shields are recommended to safeguard against potential eye contact, irritation or injury. |
| Other Protective Equipment                  | Impermeable aprons are advised when working with this product. The availability of eye washes and safety showers in work areas is recommended.                                                                                                                                                                                                                                          |                |                                                                                                                                        |

| Section V — REACTIVITY DATA                |                                                                                                           |   |                      |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------|---|----------------------|
| Stability                                  | Unstable                                                                                                  |   | Conditions to Avoid: |
|                                            | Stable                                                                                                    | X |                      |
| Incompatibility<br>(Materials<br>to Avoid) | This product is incompatible with:<br>Strong oxidizing agents, strong acids or bases,<br>selected amines. |   |                      |
| Hazardous<br>Decomposition<br>Products     | Thermal decomposition in the presence of air may yield carbon<br>monoxide and/or carbon dioxide.          |   |                      |
| Hazardous<br>Polymerization                | May Occur                                                                                                 |   | Conditions to Avoid: |
|                                            | Will Not Occur                                                                                            | X |                      |

| Section IV — SPILL OR LEAK PROCEDURES                |                                                                                                                                                                                                                                                              |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HIGHWAY OR RAILWAY SPILLS—CALL CHEMTREC 800/424-9300 |                                                                                                                                                                                                                                                              |
| Precautions<br>In Case Of<br>Release or<br>Spill     | Keep sources of ignition and hot metal surfaces isolated from the spill. Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts of spilled material may be absorbed into an appropriate absorbant. |
| Reportable<br>Quantity                               | Notify Coast Guard National Response Center; Phone No. 800-424-8802, If Spill Is Greater Than ____ lbs. [Kilograms]                                                                                                                                          |
| Waste<br>Disposal<br>Method                          | Dispose of product in accordance with applicable local, county, state and federal regulations.                                                                                                                                                               |

**Section VII — STORAGE AND SPECIAL PRECAUTIONS**

|                                  |                                                                                                                                                                                                                                                     |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Handling and Storing Precautions | Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation (see Section IV).                                                                                                         |
| Other Precautions                | Personnel should avoid inhalation of vapors (see Sections I, II, III, V, VI). Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected areas with water (see Sections II, IV, VI). |

**Section VIII — FIRE AND EXPLOSION HAZARD DATA**

|                                    |                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                   |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOT Flammability Classification    | NON-FLAMMABLE                                                                                                                                                                                                                                         | Flash Point Range: <input type="checkbox"/> Below 20° F <input type="checkbox"/> 20° F - 100° F <input type="checkbox"/> 100° F - 200° F <input checked="" type="checkbox"/> Over 200° F <input type="checkbox"/> None to boiling |
| Extinguishing Media                | Use foam, CO <sub>2</sub> or dry chemical fire fighting apparatus.                                                                                                                                                                                    |                                                                                                                                                                                                                                   |
| Unusual Fire and Explosion Hazards | Keep work areas free of hot metal surfaces and other sources of ignition.                                                                                                                                                                             |                                                                                                                                                                                                                                   |
| Fire Fighting Procedures           | The use of self-contained breathing apparatus is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keep adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes. |                                                                                                                                                                                                                                   |

**Section IX — PHYSICAL DATA**

|                                                                                                           |                                 |                                                                                                      |
|-----------------------------------------------------------------------------------------------------------|---------------------------------|------------------------------------------------------------------------------------------------------|
| Approximate Boiling Range, ° F                                                                            | 212° - 480°F                    | Vapor Density: <input checked="" type="checkbox"/> Heavier Than Air <input type="checkbox"/> Lighter |
| Evaporation Rate: <input type="checkbox"/> Faster Than Ether <input checked="" type="checkbox"/> Slower   | Percent Volatile: LESS THAN 30% | Solubility in Water: YES                                                                             |
| Specific Gravity: <input checked="" type="checkbox"/> Lighter Than Water <input type="checkbox"/> Heavier | Weight per Gallon. 8.70         |                                                                                                      |
| Appearance and Odor: TAN IN COLOR WITH A CHARACTERISTIC ODOR.                                             |                                 |                                                                                                      |

**Section X — DOCUMENTARY INFORMATION**

|                              |                  |                          |
|------------------------------|------------------|--------------------------|
| Product Code No. #320 & #520 | Issue Date 06/06 | Prepared By D. KLINGEMAN |
|------------------------------|------------------|--------------------------|

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.