

CA 1315  
**ASHLAND**  
**SAFETY DATA SHEET**

Page: 1  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Wesmar Products, Inc  
1440 NW 45th ST  
Seattle, WA 98107  
(206) 782-8186

Emergency telephone number

1-800-ASHLAND  
(1-800-274-5263)

|                         |                                          |
|-------------------------|------------------------------------------|
| Product name            | CAR BRITE® CB TROPICAL GLOSS AEROSOL WAX |
| Product code            | CBOOA069-18                              |
| Product Use Description | No data                                  |

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: aerosol

DANGER! Moderate skin irritant, Moderate eye irritant.

**Potential Health Effects**

**Routes of Exposure**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye Contact**

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

**Skin Contact**

Can cause severe skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: skin blistering. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

**Inhalation**

# ASHLAND

## SAFETY DATA SHEET

Page: 2  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity.

### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidney. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, low blood pressure, mild, temporary changes in the liver, effects on heart rate, respiratory depression (slowing of the breathing rate), loss of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), lung edema (fluid buildup in the lung tissue), kidney damage, convulsions, coma, and death.

### Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects.

### Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

### Reproductive Hazard

# ASHLAND

## SAFETY DATA SHEET

Page: 3  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

### Other Information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin. Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components                                      | CAS-No.    | Concentration |
|-------------------------------------------------|------------|---------------|
| NAPHTHA (PETROLEUM), HEAVY<br>ALKYLATE          | 64741-65-7 | >=10-<15%     |
| DISTILLATES (PETROLEUM), ACID-<br>TREATED LIGHT | 64742-14-9 | >=1.5-<5%     |
| MORPHOLINE                                      | 110-91-8   | >=1-<1.5%     |

### 4. FIRST AID MEASURES

#### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

#### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

# ASHLAND

## SAFETY DATA SHEET

Page: 4  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

### Notes to Physician

**Hazards:** Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

**Treatment:** No information available.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO<sub>2</sub>), dry chemical

### Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

### Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

# ASHLAND

## SAFETY DATA SHEET

Page: 5  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

### Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

### Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Handling equipment must be properly grounded.

### Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

| MORPHOLINE |                            | 110-91-8  |
|------------|----------------------------|-----------|
| ACGIH      | time weighted average      | 20 ppm    |
| NIOSH      | Recommended exposure limit | 20 ppm    |
|            | (REL):                     |           |
| NIOSH      | Recommended exposure limit | 70 mg/m3  |
|            | (REL):                     |           |
| NIOSH      | Short term exposure limit  | 30 ppm    |
| NIOSH      | Short term exposure limit  | 105 mg/m3 |
| OSHA Z1    | Permissible exposure limit | 20 ppm    |
| OSHA Z1    | Permissible exposure limit | 70 mg/m3  |

### General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

# ASHLAND

## SAFETY DATA SHEET

Page: 6  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

### Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

### Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

### Skin and Body Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

### Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                           |         |
|---------------------------|---------|
| Physical state            | aerosol |
| Form                      | No data |
| Colour                    | No data |
| Odour                     | No data |
| Boiling point/range       | No data |
| pH                        | No data |
| Flash point               | No data |
| Evaporation rate          | No data |
| Explosion limits          | No data |
| Vapour pressure           | No data |
| Vapour density            | No data |
| Density                   | No data |
| Solubility                | No data |
| Partition coefficient (n- | No data |

# ASHLAND

## SAFETY DATA SHEET

Page: 7  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

octanol/water)

Autoignition temperature

No data

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to Avoid

#### Incompatible Products

Avoid contact with: acetaldehyde, acids, chlorine, ethylene oxide, isocyanates, peroxides, strong oxidizing agents, Do not use with aluminum equipment at temperatures above 120 degrees F.

#### Hazardous Decomposition Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

#### Hazardous Reactions

Product will not undergo hazardous polymerization.

#### Thermal Decomposition

No data

### 11. TOXICOLOGICAL INFORMATION

#### Acute Oral Toxicity

NAPHTHA (PETROLEUM), HEAVY  
ALKYLATE LD 50 Rat: 8,000 mg/kg

MORPHOLINE LD 50 Rat: 1,050 mg/kg

#### Acute Inhalation Toxicity

NAPHTHA (PETROLEUM), HEAVY  
ALKYLATE LD 50 Rat: 5,900 mg/m3, 4 h

# ASHLAND

## SAFETY DATA SHEET

Page: 8  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

MORPHOLINE

LC 50 Rat: 8000 ppm, 8 h

### Acute Dermal Toxicity

NAPHTHA (PETROLEUM), HEAVY  
ALKYLATE

LD 50 Rabbit: 4,000 mg/kg

MORPHOLINE

LD 50 Rabbit: 500 mg/kg

## 12. ECOLOGICAL INFORMATION

### Aquatic Toxicity

#### Acute and Prolonged Toxicity to Fish

No data

#### Acute Toxicity to Aquatic Invertebrates

No data

### Environmental Fate and Pathways

No data

## 13. DISPOSAL CONSIDERATIONS

### Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

## 14. TRANSPORT INFORMATION

### IMDG:

UN1950, AEROSOLS 2.1,



# ASHLAND

## SAFETY DATA SHEET

Page: 9  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

**IATA\_P:**

UN1950, Aerosols, flammable 2.1,

**IATA\_C:**

UN1950, Aerosols, flammable 2.1,

**CFR\_ROAD:**

UN1950, Aerosols 2.1,

**CFR\_RAIL:**

UN1950, Aerosols 2.1,

**CFR\_INWTR:**

UN1950, Aerosols 2.1,

**IMDG\_INWTR:**

UN1950, AEROSOLS 2.1,

**IMDG\_ROAD:**

UN1950, AEROSOLS 2.1,

**IMDG\_RAIL:**

UN1950, AEROSOLS 2.1,

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

### 15. REGULATORY INFORMATION

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

**SARA Hazard Classification** Acute Health Hazard

**SARA 313 Component(s)**

**OSHA Hazards**

Moderate skin irritant  
Moderate eye irritant

|      | Health | Flammability | Reactivity | Other |
|------|--------|--------------|------------|-------|
| HMIS | 2      | 0            | 0          |       |
| NFPA | 1      | 4            | 0          |       |

### 16. OTHER INFORMATION

**ASHLAND**  
**SAFETY DATA SHEET**

CAR BRITE® CB TROPICAL GLOSS  
AEROSOL WAX CBOOA069-18

Page: 10  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0408144  
Version: 1.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).