

CA 1320
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
--

Wesmar Products
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number 1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® AEROSOL INSIDE OUT DETAILER
Product code	CBOOG008C22
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: aerosol

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF INHALED OR SWALLOWED. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin Contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), central nervous system, male reproductive system

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

Target Organs

Prolonged and repeated exposure to n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of the arms and legs) and result in muscular weakness and loss of sensation. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, nasal damage, testis damage, lung damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: central nervous system effects, visual impairment

Carcinogenicity

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

This material (or a component) has been shown to cause birth defects in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

Other Information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
N-HEXANE	110-54-3	>=20-<30%
METHYL-2-PENTANE	107-83-5	>=15-<20%
METHYL-3-PENTANE	96-14-0	>=15-<20%
CYCLOHEXANE	110-82-7	>=5-<10%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water mist, carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides

Precautions for Fire-Fighting

No data

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).

Environmental Precautions

No data

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Prevent from entering drains, sewers, streams and other bodies of water. Dam and dike to prevent spreading. If runoff occurs, notify authorities. Transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil, and other materials to containers for disposal.

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22**7. HANDLING AND STORAGE****Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Handling equipment must be properly grounded.

Storage

Do not store exposed to direct light. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines**

N-HEXANE		110-54-3
ACGIH	time weighted average	50 ppm
NIOSH	Recommended exposure limit (REL):	50 ppm
NIOSH	Recommended exposure limit (REL):	180 mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	1,800 mg/m3
METHYL-2-PENTANE		107-83-5
ACGIH	time weighted average	500 ppm
ACGIH	Short term exposure limit	1,000 ppm
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3
NIOSH	Ceiling Limit Value and Time Period (if specified):	510 ppm
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1A	time weighted average	500 ppm
OSHA Z1A	time weighted average	1,800 mg/m3
OSHA Z1A	Short term exposure limit	1,000 ppm
OSHA Z1A	Short term exposure limit	3,600 mg/m3
US CA OEL	Time Weighted Average (TWA)	500 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	1,800 mg/m3
	Permissible Exposure Limit (PEL):	
US CA OEL	Short term exposure limit	1,000 ppm

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

US CA OEL	Short term exposure limit	3,600 mg/m3
METHYL-3-PENTANE		96-14-0
ACGIH	time weighted average	500 ppm
ACGIH	Short term exposure limit	1,000 ppm
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3
NIOSH	Ceiling Limit Value and Time Period (if specified):	510 ppm
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1A	time weighted average	500 ppm
OSHA Z1A	time weighted average	1,800 mg/m3
OSHA Z1A	Short term exposure limit	1,000 ppm
OSHA Z1A	Short term exposure limit	3,600 mg/m3
US CA OEL	Time Weighted Average (TWA)	500 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	1,800 mg/m3
	Permissible Exposure Limit (PEL):	
US CA OEL	Short term exposure limit	1,000 ppm
US CA OEL	Short term exposure limit	3,600 mg/m3
BUTANE NORMAL		106-97-8
NIOSH	Recommended exposure limit (REL):	800 ppm
NIOSH	Recommended exposure limit (REL):	1,900 mg/m3
OSHA Z1A	time weighted average	800 ppm
OSHA Z1A	time weighted average	1,900 mg/m3
US CA OEL	Time Weighted Average (TWA)	800 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	1,900 mg/m3
	Permissible Exposure Limit (PEL):	
PROPANE		74-98-6
NIOSH	Recommended exposure limit (REL):	1,000 ppm
NIOSH	Recommended exposure limit (REL):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	1,000 ppm
OSHA Z1	Permissible exposure limit	1,800 mg/m3
OSHA Z1A	time weighted average	1,000 ppm
OSHA Z1A	time weighted average	1,800 mg/m3
US CA OEL	Time Weighted Average (TWA)	1,000 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	1,800 mg/m3
	Permissible Exposure Limit (PEL):	
ACGIH	time weighted average	1,000 ppm
CYCLOHEXANE		110-82-7

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

ACGIH	time weighted average	100 ppm
OSHA Z1	Permissible exposure limit	300 ppm
OSHA Z1	Permissible exposure limit	1,050 mg/m3
NIOSH	Recommended exposure limit	300 ppm
	(REL):	
NIOSH	Recommended exposure limit	1,050 mg/m3
	(REL):	

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	aerosol
Form	No data

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

Colour	No data
Odour	No data
Boiling point/range	No data
pH	No data
Flash point	No data
Evaporation rate	No data
Explosion limits	1.9 %(V) 9.5 %(V)
Vapour pressure	No data
Vapour density	No data
Density	0.636 g/cm3 @ 59.9 °F / 15.5 °C
	No data
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

Acute Oral Toxicity

N-HEXANE	LD 50 Rat: 25 g/kg
CYCLOHEXANE	LD 50 Mouse: 1,300 mg/kg LD 50 Rat: 29,820 mg/kg

Acute Inhalation Toxicity

N-HEXANE	LC 50 Rat: 48000 ppm, 4 h
METHYL-2-PENTANE	LC 50 Rat: 3125 ppm, 4 h
CYCLOHEXANE	LC 50 Rat: 4044 ppm,

Acute Dermal Toxicity

N-HEXANE	LD 50 Rabbit: 1.3 g/kg
CYCLOHEXANE	LD 50 Rabbit: 2.0 g/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

Waste Disposal Methods For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1950, AEROSOLS 2.1,

IATA-P:

UN1950, Aerosols, flammable 2.1,

IATA-C:

UN1950, Aerosols, flammable 2.1,

CFR-ROAD:

UN1950, Aerosols 2.1,

CFR-RAIL:

UN1950, Aerosols 2.1,

CFR-INWTR:

UN1950, Aerosols 2.1,

IMDG-INWTR:

UN1950, AEROSOLS 2.1,

IMDG-ROAD:

UN1950, AEROSOLS 2.1,

IMDG-RAIL:

UN1950, AEROSOLS 2.1,

Dangerous goods descriptions (if indicated above) may not reflect package size, quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

N-HEXANE	110-54-3	20%
CYCLOHEXANE	110-82-7	5%

ASHLAND
SAFETY DATA SHEET

Page: 11
Revision Date: 07/30/2007
Print Date: 8/16/2007
MSDS Number: R0408147
Version: 1.1

CAR BRITE® AEROSOL INSIDE
OUT DETAILER CBOOG008C22

OSHA Hazards

Moderate skin irritant
Moderate eye irritant

	Health	Flammability	Reactivity	Other
HMIS				No data
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).