

CG 1000 - CQ 1000

WORKOUT

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 06/19/06

Date Printed: 07/31/06

MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: WORKOUT COMPOUND 12/32OZ

SAP Material No: CBOOB090-02

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

Wesmar Products Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
KEROSINE, STRAIGHT RUN, KEROSENE	8008-20-6	11.0- 21.0
SILICA		7.0- 17.0
ALIPHATIC HYDROCARBONS (STODDARD TYPE)	8052-41-3	2.2- 12.0
QUARTZ	14808-60-7	2.2- 12.0
MICROCRYSTALLINE SILICA	1317-95-9	2.2- 12.0
SILICA	61790-53-2	1.0- 10.0
ALIPHATIC PETROLEUM DISTILLATES	8042-47-5	1.0- 9.0
GLYCERINE	56-81-5	1.0- 9.0
TALL OIL FATTY ACID	61790-12-3	1.0- 7.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation.

Skin

Can cause skin irritation. Prolonged or repeated contact may dry and crack the skin. Additional symptoms of skin contact may include: skin blistering, Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of dust, vapor, and/or fume is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Prolonged or repeated breathing of this material may result in chronic bronchitis (inflammation of the airways of the lungs). Symptoms include coughing and shortness of breath. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8). Prolonged or repeated breathing of dust may result in progressive and irreversible lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 06/19/06

Date Printed: 07/31/06

MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, loss of coordination, confusion, difficult breathing, irregular heartbeat, narcosis (dazed or sluggish feeling), convulsions, coma, and death. Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

Target Organ Effects

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Chronic feeding studies with white oils (greater than 0.5% in the diet) have resulted in increased organ weights (liver, kidney, spleen), and in microscopic areas of oil accumulation in the liver and the lymph nodes of the gut in experimental animals. These changes have occasionally been associated with cell damage. In humans, cell damage resulting from accumulation of these oil droplets has only occurred following prolonged ingestion of mineral oil. These effects are not expected to occur as a result of occupational exposure to white oils. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: mild, reversible liver effects, mild, reversible kidney effects. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these organs: chronic bronchitis, emphysema, kidney damage.

Developmental Information

Tall oil fatty acids did not cause harm to the fetus when given in the diet of laboratory animals.

Cancer Information

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. The International Agency for Research on Cancer (IARC) and the National Toxicology Program have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke. White mineral oil was not carcinogenic in laboratory animals by any route of exposure other than by injection into the abdomen. Results of abdominal injection are not relevant to possible human exposure to this material.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 06/19/06

Date Printed: 07/31/06

MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

Other Health Effects

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease.

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse. If skin contact with molten material occurs, flush exposed area with cool water. Do not forcibly remove material adhering to the skin. Seek immediate medical attention.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidneys. Individuals with pre-existing heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material. Silicosis predisposes the individual to the development of tuberculosis. This is most likely to occur after the age of 50 and in association with moderate to severe silicosis.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 06/19/06

Date Printed: 07/31/06

MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

5. FIRE FIGHTING MEASURES

Flash Point

154.0 F (67.7 C)

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Not determined

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred. Precautions during use:

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 06/19/06
Date Printed: 07/31/06
MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

KEROSENE, STRAIGHT RUN, KEROSENE (8008-20-6)
ACGIH TLV 200.000 mg/m³ - TWA ((Skin))

SILICA

No exposure limits established

ALIPHATIC HYDROCARBONS (STODDARD TYPE) (8052-41-3)

OSHA VPCL 100.000 ppm - TWA
ACGIH TLV 100.000 ppm - TWA

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 06/19/06
Date Printed: 07/31/06
MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

QUARTZ (14808-60-7)
OSHA VPEL 0.100 mg/m3 - TWA respirable dust
ACGIH TLV 0.025 mg/m3 - TWA

MICROCRYSTALLINE SILICA (1317-95-9)
OSHA VPEL 0.100 mg/m3 - TWA respirable dust (as quartz)

SILICA (61790-53-2)
OSHA VPEL 6.000 mg/m3 - TWA
ACGIH TLV 3.000 mg/m3 - TWA respirable particulate
ACGIH TLV 10.000 mg/m3 - TWA inhalable particulate

ALIPHATIC PETROLEUM DISTILLATES (8042-47-5)
OSHA VPEL 5.000 mg/m3 - TWA as Oil Mist - CASRN 8012-95-1
ACGIH TLV 5.000 mg/m3 - TWA as Oil Mist - CASRN 8012-95-1
ACGIH TLV 5.000 mg/m3 - TWA for mineral oil mist
ACGIH TLV 10.000 mg/m3 - STEL as Oil Mist - CASRN 8012-95-1
ACGIH TLV 10.000 mg/m3 - STEL for mineral oil mist

GLYCERINE (56-81-5)
OSHA VPEL 5.000 mg/m3 - TWA respirable fraction
OSHA VPEL 10.000 mg/m3 - TWA total dust
ACGIH TLV 10.000 mg/m3 - TWA

TALL OIL FATTY ACID (61790-12-3)
No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
(for product) > 150.0 F (65.5 C) @ 760.00 mmHg

Vapor Pressure
(for component) < 1.000 mmHg

Specific Vapor Density
No data

Specific Gravity
1.146 @ 60.00 F

Liquid Density
9.560 lbs/gal @ 60.00 F
9.560 lbs/gal @ 60.00 F

Percent Volatiles (Including Water)
No data

Evaporation Rate
No data

Appearance
No data

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007
Date Prepared: 06/19/06
Date Printed: 07/31/06
MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

State

LIQUID

Physical Form

No data

Color

BEIGE

Odor

SOLVENT

pH

8.5

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008
Date Prepared: 06/19/06
Date Printed: 07/31/06
MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
FLAMMABLE LIQUIDS, N.O.S.,3,UN1993,II

Container/Mode:
CASES/SURFACE - NO EXCEPTIONS

NOS Component:
PETROLEUM DISTILLATES

RQ (Reportable Quantity) - 49 CFR 172.101
Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4
None

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate(X) Delayed(X) Fire(X) Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65
None

International Regulations

Inventory Status
Not determined

State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.

QUARTZ
MICROCRYSTALLINE SILICA

New Jersey RTK Label Information

KEROSENE	8008-20-6
STODDARD SOLVENT	8052-41-3
SILICA, QUARTZ	14808-60-7
SILICA, TRIPOLI	1317-95-9

Pennsylvania RTK Label Information

KEROSINE (PETROLEUM)	8008-20-6
STODDARD SOLVENT	8052-41-3
QUARTZ (SiO2)	14808-60-7
TRIPOLI	1317-95-9
1,2,3-PROPANETRIOL	56-81-5

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 009
Date Prepared: 06/19/06
Date Printed: 07/31/06
MSDS No: 525.0405367-002.001

WORKOUT COMPOUND 12/32OZ

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.