

CG 1090

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 10/07/05

Date Printed: 12/28/05

MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: BLUE MAX 5 GAL

SAP Material No: CBOOE004-05

Wesmar Products, Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)	
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	1.0-	9.0
DODECYLBENZENESULFONIC ACID	27176-87-0	1.0-	8.0
SODIUM TRIPOLYPHOSPHATE	7758-29-4	1.0-	8.0
NONIONIC SURFACTANT	68439-46-3	1.0-	7.0
TRISODIUM PHOSPHATE	7601-54-9	1.0-	7.0
SODIUM XYLENE SULFONATE	1300-72-7	1.0-	6.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Material is corrosive to eyes. May cause burns.

Skin

Can cause skin burns and other permanent skin damage. Passage of this material through the skin may be harmful.

Swallowing

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation, burns and tissue damage. Shock may occur. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury. Exposure causes severe irritation of the gastrointestinal tract.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful or fatal. May cause severe irritation and burns to the nose, throat, and respiratory tract. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), low blood pressure, pain in the abdomen, effects on heart rate, difficult breathing, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), blood in the urine, blood abnormalities (breakage of red blood cells), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, coma, and death.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 10/07/05
Date Printed: 12/28/05
MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

Target Organ Effects

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes.

Swallowing

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 10/07/05

Date Printed: 12/28/05

MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Excessive levels of phosphorus can cause low blood calcium, with tetany and convulsions. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidneys, blood-forming system. Exposure to this material may aggravate any pre-existing condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, phosphorous oxides, sodium oxide various hydrocarbons.

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

alcohol foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Not determined

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 10/07/05

Date Printed: 12/28/05

MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Under oxidation conditions, peroxides may be formed. If they become concentrated, these peroxides may present an explosion hazard. Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 10/07/05
Date Printed: 12/28/05
MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

Exposure Guidelines

Component

ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2)
OSHA VPEL 25.000 ppm - TWA ((Skin))
ACGIH TLV 20.000 ppm - TWA

DODECYLBENZENESULFONIC ACID (27176-87-0)
No exposure limits established

SODIUM TRIPOLYPHOSPHATE (7758-29-4)
No exposure limits established

NONIONIC SURFACTANT (68439-46-3)
No exposure limits established

TRISODIUM PHOSPHATE (7601-54-9)
No exposure limits established

SODIUM XYLENE SULFONATE (1300-72-7)
No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for product) .0 (-17.7 C)

Vapor Pressure

(for product) .000

Specific Vapor Density

No data

Specific Gravity

1.055 @ 60.00 F

Liquid Density

8.800 lbs/gal @ 60.00 F

8.800 lbs/gal @ 60.00 F

Percent Volatiles (Including Water)

No data

Evaporation Rate

No data

Appearance

No data

State

LIQUID

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 10/07/05

Date Printed: 12/28/05

MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

Physical Form

No data

Color

BLUE

Odor

CHEMICAL

pH

> 13.0

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, phosphorous oxides, sodium oxide various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: aluminum, magnesium, strong mineral acids, strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007
Date Prepared: 10/07/05
Date Printed: 12/28/05
MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
CAUSTIC ALKALI LIQUIDS, NOS,8,UN1719

Container/Mode:
CASES/SURFACE - NO EXCEPTIONS

NOS Component:
POTASSIUM HYDROXIDE
SODIUM METASILICATE

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

36902 DODECYLBENZENESULFONIC ACID

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component	Component
DODECYLBENZENESULFONIC ACID	1000
PENTASODIUM TRIPHOSPHATE	5000
TRISODIUM PHOSPHATE	5000

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate(X) Delayed(X) Fire(X) Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2

International Regulations

Inventory Status
Not determined

State and Local Regulations

California Proposition 65
None

New Jersey RTK Label Information

2-BUTOXY ETHANOL	111-76-2
DODECYLBENZENE SULFONIC ACID	27176-87-0
SODIUM PHOSPHATE, TRIBASIC	7758-29-4
SODIUM PHOSPHATE, TRIBASIC	7601-54-9

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008
Date Prepared: 10/07/05
Date Printed: 12/28/05
MSDS No: 525.0405872-001.002

BLUE MAX 5 GAL

Pennsylvania RTK Label Information

ETHANOL, 2-BUTOXY-	111-76-2
BENZENESULFONIC ACID, DODECYL-	27176-87-0
TRIPHOSPHORIC ACID, PENTASODIUM SALT	7758-29-4
PHOSPHORIC ACID, TRISODIUM SALT	7601-54-9

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.