

CG 1117-A-B
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Emergency telephone number 1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® SURFACE CLARIFIER Water Spot Remover
Product code	CBOOE111-05-S5
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, colourless

DANGER! POISON! Toxic by inhalation, Toxic by ingestion, Toxic by skin absorption, Corrosive to skin, Corrosive to eyes, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Causes eye burns.

Skin Contact

Both the liquid and vapor can cause severe burns which may not be immediately painful or visible. Pain may become gradually more severe, possibly taking 1-24 hours to become noticeable. These burns can be very deep, possibly causing bone damage, and are very slow to heal. Even solutions containing 2% or less hydrogen fluoride or other inorganic fluoride compounds can cause burns and tissue damage. Passage of this material into the body through the skin is possible, and skin contact may be harmful or fatal.

Ingestion

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER Water Spot Remover CBOOE111-05-S5

vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury.

Inhalation

Breathing of vapor or mist is possible. Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, nervous system, blood-forming system, bone. Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: irritation (nose, throat, airways), cough, sneezing, headache, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficult breathing, irregular heartbeat, blood in the urine, blood abnormalities (breakage of red blood cells), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, coma, and death.

Target Organs

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Repeated, prolonged overexposure to inorganic fluoride compounds may result in gastrointestinal disturbances, loss of weight, anemia (reduced number of red blood cells), diseases of the teeth, and skeletal fluorosis. Skeletal fluorosis is characterized by bone and joint pain, limited motion in the joints or spine, increased bone density which can cause the bones to become brittle, and hardening of ligaments. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: nervous system effects, blood abnormalities, liver abnormalities, kidney damage.

Carcinogenicity

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER Water Spot Remover CBOOE111-05-S5

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Reproductive Hazard

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Other Information

Hydrofluoric acid has been shown to cause permanent changes in the DNA of insect germ cells. Changes in these cells can be passed to the next generation. The relevance of this finding to human health is uncertain.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
PHOSPHORIC ACID	7664-38-2	>=30-<40%
SURFACTANT	NJTS# 254504001- 5149	>=1.5-<5%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush contaminated skin with large quantities of cool running water for 5 minutes. Remove contaminated clothing while flushing contaminated skin. Immediately after washing, apply 2.5% calcium gluconate gel to all affected skin areas. (Note: If gel is not prepared within 5 minutes, continue flushing until gel is prepared.) The gel should be massaged into the affected skin by personnel wearing gloves to prevent skin contamination during first aid. Gel should be applied every 15 minutes and

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER Water Spot Remover CBOOE111-05-S5

massaged continuously. Instead of calcium gluconate treatment, the affected areas may be soaked in iced 0.13% benzalkonium chloride solution (Zephiran chloride). Use ice cubes rather than shaved ice to prevent frostbite. If it is not practical to immerse affected area, towels should be soaked with iced 0.13% benzalkonium chloride solution and used as compresses for the burned area. Compresses should be changed every 2-3 minutes and continued until pain is relieved or victim is seen by a physician. If neither calcium gluconate nor benzalkonium chloride is available, use an iced saturated water solution of magnesium sulfate (Epsom salts), or if that is not available, iced 70% alcohol or ice water. Local anesthetics should be avoided since relief of pain indicates success of the treatment. ***Get medical attention as soon as possible.*** ::::NOTE::::Calcium gluconate gel can be prepared by mixing a 10 milliliter ampule of calcium gluconate with a 2-ounce tube of K-Y jelly (Johnson & Johnson). After a jar of this mixture has been opened and used, it should be discarded to prevent bacterial or chemical contamination.

Ingestion

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This product contains hydrofluoric acid (HF). Acute local effects from HF exposure are concentration-dependent. If untreated or exposure is prolonged, even dilute solutions of HF can cause delayed toxicity following penetration to subcutaneous tissue. Acute systemic toxicity is largely dependent upon the total amount of fluoride ion absorbed. Thus ingestion, skin contact or significant inhalation can cause severe systemic effects including electrolyte (calcium, magnesium, potassium) and acid-base abnormalities with resulting cardiovascular effects. Exposure of >5% of the body surface area with any concentration of HF may predispose the patient to development of hypocalcemia. Chronic exposure to less than acutely toxic amounts of HF is a low toxicity hazard. Repeated exposure and absorption of 10-80 mg of fluoride per day may produce systemic fluorosis.

Treatment: No information available.

ASHLAND

SAFETY DATA SHEET

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: acid vapors, carbon dioxide and carbon monoxide

Precautions for Fire-Fighting

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

No data

Environmental Precautions

No data

Methods for Cleaning Up

Cover the contaminated surface with sodium bicarbonate or a soda ash/flaked lime mixture (50-50). Mix and add water if necessary to form a slurry. Scoop up slurry and wash site with soda ash solution. Proper mixing procedures are essential. Trained personnel should conduct this procedure. Untrained personnel should be removed from the spill area. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing protective equipment should be excluded from area of spill until clean-up is completed. Stop spill at source. Dike to prevent spreading. Pump to salvage tank.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Under oxidation conditions, peroxides may be formed. If they become concentrated, these peroxides may present an explosion hazard.

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

Storage

Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

PHOSPHORIC ACID

7664-38-2

ACGIH	time weighted average	1 mg/m3
ACGIH	Short term exposure limit	3 mg/m3
NIOSH	Recommended exposure limit	1 mg/m3
	(REL):	
NIOSH	Short term exposure limit	3 mg/m3
OSHA Z1	Permissible exposure limit	1 mg/m3

ETHYLENE GLYCOL MONOBUTYL ETHER

111-76-2

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit	5 ppm
	(REL):	
NIOSH	Recommended exposure limit	24 mg/m3
	(REL):	
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	240 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourless
Odour	No data
Boiling point/range	212 °F / 100 °C @ 1,013.333333 hPa
pH	1
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	23.3333333 hPa @ 68 °F / 20 °C
Vapour density	No data
Density	1.20 g/cm ³ 10.01 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

Avoid contact with:, organic materials, strong alkalis, strong oxidizing agents,
strong reducing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

PHOSPHORIC ACID	LD 50 Rat: 1,530 mg/kg
SURFACTANT	LD 50 Rat: 1.4 g/kg
ETHYLENE GLYCOL MONOBUTYL ETHER	LD 50 Rat: 470 mg/kg

Acute Inhalation Toxicity

ETHYLENE GLYCOL MONOBUTYL ETHER	LC 50 Rat: 450 ppm, 4 h
------------------------------------	-------------------------

Acute Dermal Toxicity

PHOSPHORIC ACID	LD 50 Rabbit: 2,740 mg/kg
SURFACTANT	LD 50 Rabbit: 5 g/kg
ETHYLENE GLYCOL MONOBUTYL ETHER	LD 50 Rabbit: 220 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN2922, CORROSIVE LIQUID, TOXIC, N.O.S. (PHOSPHORIC ACID, HYDROFLUORIC ACID) 8 (6.1), II

IATA_P:

UN2922, Corrosive liquid, toxic, n.o.s. (PHOSPHORIC ACID, HYDROFLUORIC ACID) 8 (6.1), II

IATA_C:

UN2922, Corrosive liquid, toxic, n.o.s. (PHOSPHORIC ACID, HYDROFLUORIC ACID) 8 (6.1), II

CFR_ROAD:

UN2922, Corrosive liquids, toxic, n.o.s. (PHOSPHORIC ACID, HYDROFLUORIC ACID) 8 (6.1), II

CFR_RAIL:

UN2922, Corrosive liquids, toxic, n.o.s. (PHOSPHORIC ACID, HYDROFLUORIC ACID) 8 (6.1), II

CFR_INWTR:

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

UN2922, Corrosive liquids, toxic, n.o.s. (PHOSPHORIC ACID,
HYDROFLUORIC ACID) 8 (6.1), II

IMDG_INWTR:

UN2922, CORROSIVE LIQUID, TOXIC, N.O.S. 8 (6.1), II

IMDG_ROAD:

UN2922, CORROSIVE LIQUID, TOXIC, N.O.S. 8 (6.1), II

IMDG_RAIL:

UN2922, CORROSIVE LIQUID, TOXIC, N.O.S. 8 (6.1), II

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ARSENIC

LEAD

NICKEL

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

MERCURY

LEAD

SARA Hazard Classification Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards

- Toxic by inhalation
- Toxic by ingestion
- Toxic by skin absorption
- Corrosive to skin
- Corrosive to eyes
- Carcinogen

HMIS	Health	Flammability	Reactivity	Other
	3	0		

ASHLAND
SAFETY DATA SHEET

Page: 11
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406087
Version: 1.

CAR BRITE® SURFACE CLARIFIER
Water Spot Remover CBOOE111-05-S5

NFPA

No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).