

CG 1615-A-B
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name

CAR BRITE® BODY BRITE Transit Coating Remover

Product code

CBOOF001F05-S5

Product Use Description

No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, fruity, colourless

DANGER! Toxic by skin absorption, Corrosive to skin, Corrosive to eyes.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Causes eye burns.

Skin Contact

Can cause permanent skin damage. Symptoms may include redness, burning, and swelling of skin, burns, and other skin damage. Additional symptoms of skin contact may include: allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects) Passage of this material into the body through the skin is possible, and skin contact may be harmful.

Ingestion

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

Inhalation

Breathing of vapor or mist is possible. Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), shortness of breath, difficult breathing, lung edema (fluid buildup in the lung tissue), liver damage, kidney damage, lung damage

Target Organs

Frequent ingestion of silicates over long periods of time is associated with the formation of stones in the kidney and urinary tract in humans. Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: kidney damage, liver damage

Carcinogenicity

There is no information available. The chance of this material causing cancer is unknown. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

Monoethanolamine caused harm to the fetus in a laboratory animal study in which high doses of the material were placed in the stomachs of the mothers through a feeding tube. However, in others studies monoethanolamine was not harmful to unborn rats or rabbits when the chemical was given to the mothers by skin contact. Contact with monoethanolamine in the workplace at levels which are not harmful to the mother should have no effect on the unborn baby.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
MONOETHANOLAMINE	141-43-5	>=10-<15%
SURFACTANT	NJTS# 254504001- 5325	>=5-<10%
SODIUM XYLENE SULFONATE	1300-72-7	>=1.5-<5%
INORGANIC SALT	NJTS# 254504001- 5179	>=1-<1.5%
ETHYLENEDIAMINETETRAACETIC ACID	60-00-4	>=1-<1.5%

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes.

Ingestion

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

No data

Notes to Physician

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

given in the data sheet must be observed. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

MONOETHANOLAMINE

141-43-5

ACGIH	time weighted average	3 ppm
ACGIH	Short term exposure limit	6 ppm
NIOSH	Recommended exposure limit	3 ppm
	(REL):	
NIOSH	Recommended exposure limit	8 mg/m3
	(REL):	
NIOSH	Short term exposure limit	6 ppm
NIOSH	Short term exposure limit	15 mg/m3
OSHA Z1	Permissible exposure limit	3 ppm
OSHA Z1	Permissible exposure limit	6 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourless
Odour	fruity
Boiling point/range	No data
pH	11.5
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	1.03 g/cm ³ 8.61 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with: acids, aldehydes, aluminum, ammonium salts, ketones, lead, organic anhydrides, organic halides, strong acids, strong alkalis, strong oxidizing agents, tin, water, zinc

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

Hazardous Decomposition Products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization., Can react with chemically reactive metals, such as aluminum, zinc, magnesium, copper, etc., to release hydrogen gas which can form explosive mixtures with air.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

MONOETHANOLAMINE	LD 50 Rat: 1,720 mg/kg
SURFACTANT	LD 50 Rat: 2,780 mg/kg
SODIUM XYLENE SULFONATE	LD 50 Rat: 4,000 mg/kg
INORGANIC SALT	LD 50 Rat: 1,153 mg/kg

Acute Inhalation Toxicity

Acute Dermal Toxicity

MONOETHANOLAMINE	LD 50 Rabbit: 1,000 mg/kg
------------------	---------------------------

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

1,4-DIOXANE

NICKEL

COBALT

ETHYLENE OXIDE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

ETHYLENE OXIDE

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406149
Version: 1.

CAR BRITE® BODY BRITE Transit
Coating Remover CBOOF001F05-S5

OSHA Hazards

Toxic by skin absorption
Corrosive to skin
Corrosive to eyes

	Health	Flammability	Reactivity	Other
HMIS	3	0	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).