

CG 3070
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE
COMPANY/UNDERTAKING**

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® LEATHER & PLASTIC CLEANER Ready-To-Use, VOC Compliant
Product code	CBOOE021-03
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, fruity, colourless

DANGER! Toxic by inhalation, Toxic by ingestion, Toxic by skin absorption, Corrosive to skin, Corrosive to eyes, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Causes eye burns.

Skin Contact

Can cause permanent skin damage. Symptoms may include redness, burning, and swelling of skin, burns, and other skin damage. Passage of this material into the body through the skin is possible, and skin contact may be harmful.

Ingestion

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. This material can get into the lungs during swallowing or vomiting.

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

This results in lung inflammation and other lung injury. Exposure causes severe irritation of the gastrointestinal tract.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, blood-forming system. Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), low blood pressure, pain in the abdomen, effects on heart rate, difficult breathing, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), blood in the urine, blood abnormalities (breakage of red blood cells), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, coma, and death

Target Organs

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Ethylene glycol monobutyl

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Reproductive Hazard

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
SODIUM XYLENE SULFONATE	1300-72-7	>=1.5-<5%
INORGANIC SALT	NJTS# 254504001- 5035	>=1.5-<5%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	>=1.5-<5%
BENZENESULFONIC ACID, C10-16- ALKYL DERIVS.	68584-22-5	>=1.5-<5%
TRISODIUM PHOSPHATE	7601-54-9	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes.

Ingestion

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Excessive levels of phosphorus can cause low blood calcium, with tetany and convulsions.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, phosphorous oxides, sodium oxide, various hydrocarbons

Precautions for Fire-Fighting

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

ETHYLENE GLYCOL MONOBUTYL 111-76-2 ETHER

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	5 ppm
NIOSH	Recommended exposure limit (REL):	24 mg/m3
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	240 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourless
Odour	fruity
Boiling point/range	No data
pH	13
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	1.06 g/cm ³ 8.85 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

Partition coefficient (n-octanol/water) No data
Autoignition temperature No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, aluminum, magnesium, strong mineral acids, strong oxidizing agents, strong reducing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, phosphorous oxides, sodium oxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

SODIUM XYLENE SULFONATE	LD 50 Rat: 4,000 mg/kg
INORGANIC SALT	LD 50 Rat: 3,120 mg/kg
ETHYLENE GLYCOL MONOBUTYL ETHER	LD 50 Rat: 470 mg/kg
TRISODIUM PHOSPHATE	LD 50 Rat: 4,150 mg/kg

Acute Inhalation Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

ETHYLENE GLYCOL MONOBUTYL
ETHER LC 50 Rat: 450 ppm, 4 h

Acute Dermal Toxicity

INORGANIC SALT LD 50 Rabbit: 4,640 mg/kg

ETHYLENE GLYCOL MONOBUTYL
ETHER LD 50 Rabbit: 220 mg/kg

TRISODIUM PHOSPHATE LD 50 Rabbit: 7,940 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

14. TRANSPORT INFORMATION

IMDG:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM METASILICATE,) 8, III

IATA_P:

UN1719, Caustic alkali liquid, n.o.s. (SODIUM METASILICATE,) 8, III

IATA_C:

UN1719, Caustic alkali liquid, n.o.s. (SODIUM METASILICATE,) 8, III

CFR_ROAD:

UN1719, Caustic alkali liquids, n.o.s. (SODIUM METASILICATE,) 8, III

CFR_RAIL:

UN1719, Caustic alkali liquids, n.o.s. (SODIUM METASILICATE,) 8, III

CFR_INWTR:

UN1719, Caustic alkali liquids, n.o.s. (SODIUM METASILICATE,) 8, III

IMDG_INWTR:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. 8, III

IMDG_ROAD:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. 8, III

IMDG_RAIL:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. 8, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

SULFURIC ACID

ARSENIC

SARA Hazard Classification

Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405799
Version: 1.

CAR BRITE® LEATHER & PLASTIC
CLEANER Ready-To-Use, VOC
Compliant CBOOE021-03

OSHA Hazards

Toxic by inhalation
Toxic by ingestion
Toxic by skin absorption
Corrosive to skin
Corrosive to eyes
Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	3	0	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).