

5200 Underbody Protection Bitumen 1000ml**1 Identification of the substance/preparation and of the company/undertaking**

- **Product details**
- **Trade name:** 5200
- **Article number:** 6.5200.1000
- **Application of the substance / the preparation** Surface protection
- **Manufacturer/Supplier:**
Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of bitumen, solvents, fillers and additives

• **Dangerous components:**

CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, N; R 10-37-51/53-65-66-67	10-25%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrosulfurized heavy Xn, N; R 10-51/53-65-66-67	10-25%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification• **Hazard description:**

Xi Irritant
N Dangerous for the environment

• **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

R 10 Flammable.

R 37 Irritating to respiratory system.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

• **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

GB

Material Safety Data Sheet

According to 91/155 EEC

5 Fire-fighting measures

- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter A/P2
- **Protection of hands:**



Protective gloves

Material Safety Data Sheet

According to 91/155 EEC

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Body protection: Use protective suit.

9 Physical and chemical properties

General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 142°C

Flash point: 39°C

Ignition temperature: 450.0°C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.6 Vol %

Upper: 7.5 Vol %

Vapour pressure at 20°C: 5.0 hPa

Density at 20°C: 1.040 g/cm³

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Solvent content:

Organic solvents: 44.0 %

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Dangerous reactions: No dangerous reactions known.

GB

Material Safety Data Sheet
According to 91/155 EEC

· **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**

· **ADR/RID class:** 3 Flammable liquids.

· **Danger code (Kemler):** 30

· **UN-Number:** 1139

· **Packaging group:** III

· **Hazard label** 3

· **Description of goods:** 1139 COATING SOLUTION, special provision 640E

· **Maritime transport IMDG:**

· **IMDG Class:** 3

· **UN Number:** 1139

· **Label** 3

· **Packaging group:** III

Material Safety Data Sheet

According to 91/155 EEC

- EMS Number: F-E,S-E
- Marine pollutant: Yes
- Proper shipping name: COATING SOLUTION

- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 3
- UN/ID Number: 1139
- Label: 3
- Packaging group: III
- Proper shipping name: COATING SOLUTION

15 Regulatory information

- Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- Code letter and hazard designation of product:



Xi Irritant
N Dangerous for the environment

- Risk phrases:

10 Flammable.
37 Irritating to respiratory system.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

- Safety phrases:

2 Keep out of the reach of children.
23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
24 Avoid contact with skin.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.

- National regulations:

- Technical instructions (air):

Class	Share in %
NK	25-50

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC-CH 44.00 %
- VOC-EU 457.6 g/l

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant R-phrases

10 Flammable.
37 Irritating to respiratory system.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.

GB

Material Safety Data Sheet
According to 91/155 EEC

- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development

GB