

ER 1001
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
~~E15010602~~

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name

EAGLE ONE® E1 20/20 GLASS CLEANER GLASS
CLEANER

Product code

~~E15010602~~

Product Use Description

No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, colourless

CAUTION! Combustible Liquid, Moderate skin irritant, Moderate eye irritant.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin Contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include: skin blistering. Passage of this material into the body through the skin is possible, and may add to toxic effects from breathing or swallowing.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, eye. Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), pain in the abdomen and lower back, shortness of breath, loss of coordination, confusion, difficult breathing, irregular heartbeat, narcosis (dazed or sluggish feeling), kidney damage, liver damage, convulsions, coma, and death

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, eye damage

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

Reproductive Hazard

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Other Information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ALIPHATIC HYDROCARBON	NJTS# 254504001- 5164	>=70-<80%
DIPROPYLENE GLYCOL MONOPROPYL ETHER	29911-27-1	>=1-<1.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a

ASHLAND

SAFETY DATA SHEET

Page: 4

Revision Date: 04/16/2007

Print Date: 5/25/2007

MSDS Number: R0390302

Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water mist, carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides

Precautions for Fire-Fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Flammability Class for Flammable Liquids

Combustible Liquid Class IIIA

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

equipment should be excluded from area of spill until clean-up has been completed.
Scoop into containers.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or repeated contact. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Provide adequate ventilation to control formaldehyde

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourless
Odour	No data
Boiling point/range	No data
pH	No data
Flash point	187.00 °F / 86.11 °C Pensky Martens closed cup
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	0.825 g/cm ³ @ 70.00 °F / 21.11 °C 6.87 lb/gal @ 70.00 °F / 21.11 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Avoid contact with:, heat

Incompatible Products

Avoid contact with:, acids, strong bases, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicates, silicon oxides, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

ALIPHATIC HYDROCARBON	LD 50 Rat: 8,000 mg/kg
-----------------------	------------------------

Acute Inhalation Toxicity

ALIPHATIC HYDROCARBON	LD 50 Rat: 2500 ppm, 4 h
-----------------------	--------------------------

Acute Dermal Toxicity

ALIPHATIC HYDROCARBON	LD 50 Rabbit: 4,000 mg/kg
-----------------------	---------------------------

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/16/2007
Print Date: 5/25/2007
MSDS Number: R0390302
Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

SARA Hazard Classification

Fire Hazard
Acute Health Hazard

SARA 313 Component(s)

OSHA Hazards

Combustible Liquid
Moderate skin irritant
Moderate eye irritant

ASHLAND

SAFETY DATA SHEET

Page: 9

Revision Date: 04/16/2007

Print Date: 5/25/2007

MSDS Number: R0390302

Version: 1.2

EAGLE ONE® E1 20/20 GLASS
CLEANER GLASS CLEANER
E15010602

	Health	Flammability	Reactivity	Other
HMIS	1	2	0	
NFPA	1	2	0	

16. OTHER INFORMATION

Valvoline slop oil is the excess material from packaging of motor oils and related products. It is virtually impossible to provide definitive physical, chemical or health hazard data for this material. The warnings and information presented are generalized from similar petroleum products. The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).