

00
Section 1 —
Product Identification

Material Safety Data Sheet



Wesmar Products, Inc.
1440 NW 45th St
Seattle, Wa 98107
(206) 782-8186

Emergency telephone numbers (216) 566-2917 United States
Information telephone number (800) 251-2486
©2000, The Sherwin-Williams Co.

SPARVAR® Products - 1

SPVR1/KRI

CAS No.	Section 2 — Hazardous Ingredients (percent by weight)	ACGIH TLV	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)	S100 Glossy White	S101 Flat White	S102 Antique White	S110 Glossy Black	S111 Ultra Flat Black	S112 Shadow Gray	S113 Dove Gray	S117 Semi-Flat Black	PERCENT BY WEIGHT	
74-98-6	Propane	2500	1000	PPM	760.0	14	14	14	14	14	14	14	14	14	14
106-97-8	Butane	800	800	PPM	760.0	6	6	6	6	6	6	6	6	6	6
108-88-3	Toluene.	50	100	PPM (Skin)	22.0					33					
100-41-4	Ethylbenzene	100	100	PPM	7.1	1	2	1	1		2	2	2	2	2
1330-20-7	Xylene.	100	100	PPM	5.9	7	11	7	8		9	10	9	9	9
71-36-3	1-Butanol	C 50	C 50	PPM (Skin)	5.5	2	2	1	1						
67-64-1	Acetone.	500	1000	PPM	180.0	35	34	36	35	32	36	37	39	39	39
78-93-3	Methyl Ethyl Ketone.	200	200	PPM	70.0	10	4	7	12		8	8	12	12	12
108-10-1	Methyl Isobutyl Ketone.	50	50	PPM	16.0			2			2	1			
108-65-6	1-Methoxy-2-Propanol Acetate	Not Established			1.8	6	7	7	10		7	7	7	7	7
112926-00-8	Amorphous Precipitated Silica	10	6	Mg/M3 as Dust			2			2					
7727-43-7	Barium Sulfate.	10	10[5]	Mg/M3 as Dust [Resp. Fraction]				1			1	2			
13463-67-7	Titanium Dioxide.	10	10[5]	Mg/M3 as Dust [Resp. Fraction]		7	7	6			2	2			
1333-86-4	Carbon Black.	3.5	3.5	Mg/M3					0.5	2	0.2		1		
[% Barium]								[0.7]			[0.7]	[1.0]			
Weight per Gallon (lbs.)						6.67	6.76	6.70	6.39	6.50	6.53	6.53	6.37		
VOC Less Water & Federally Exempt Solvents (percent by weight)						46.9	46.4	46.7	52.7	53.4	48.6	48.2	50.0		
Flash Point (°F)						<0	<0	<0	<0	<0	<0	<0	<0		
HMS (NFPA) Rating (health - flammability - reactivity)						2 - 4 - 0	2 - 4 - 0	2 - 4 - 0	2 - 4 - 0	2 - 4 - 0	2 - 4 - 0	2 - 4 - 0	2 - 4 - 0		

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

Section 3 — Physical Data

PRODUCT WEIGHT	See TABLE	EVAPORATION RATE	Faster than Ether
SPECIFIC GRAVITY	0.72-0.82	VAPOR DENSITY	Heavier than Air
BOILING RANGE	-60 - 415 °F	MELTING POINT	H.A.
SOLUBILITY	>85 %	SOLUBILITY IN WATER	H.A.

Section 4 — Fire And Explosion Hazard Data

FLASH POINT*	125	0.3	UEL	11.1
EXTINGUISHING MEDIA	Carbon Dioxide, Dry Chemical, Foam			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.			
SPECIAL FIRE FIGHTING PROCEDURES	Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.			

Section 5 — Health Hazard Data

ROUTES OF EXPOSURE	Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.
ACUTE Health Hazards	Effects of OVEREXPOSURE Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.
SIGNS AND SYMPTOMS OF OVEREXPOSURE	Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE	
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None generally recognized

EMERGENCY AND FIRST AID PROCEDURES	If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet. Wash affected area thoroughly with soap and water.
If ON SKIN:	Remove contaminated clothing and launder before re-use.
If IN EYES:	Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED:	Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.

CHRONIC Health Hazards	Carbon black is classified by IARC as possibly carcinogenic to humans (Group 2B) based on experimental animal data, however, there is inadequate evidence in humans for its carcinogenicity.
Prolonged overexposure to solvent ingredients in the following products may cause adverse effects to organ systems:	
*S500	liver, urinary, reproductive
*S111, S120, S121, S124, S203, S204, S205	liver, urinary, cardiovascular, & reproductive
*S100, S101, S102, S103, S110, S112, S113	
*S117, S118, S130, S140, S151, S153, S159	liver, urinary, blood forming, & reproductive
S160, S164S180, S181	
Methyl Ethyl Ketone may increase the nervous system effects of other solvents.	
Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.	
Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.	

Section 6 — Reactivity Data

STABILITY — Stable	
CONDITIONS TO AVOID — None known.	
INCOMPATIBILITY — None known.	
HAZARDOUS DECOMPOSITION PRODUCTS	By fire: Carbon Dioxide, Carbon Monoxide
HAZARDOUS POLYMERIZATION — Will Not Occur	

Section 7 — Spill Or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Remove all sources of ignition. Ventilate and remove with inert absorbent.
WASTE DISPOSAL METHOD	Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Waste from products containing Methyl Ethyl Ketone may also require extractability testing.
	Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and local regulations regarding pollution.

Section 8 — Protection Information

PRECAUTIONS TO BE TAKEN IN USE	Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
	These products may contain materials classified as nuisance particulates (listed "as dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), 3 mg./m3 (respirable fraction), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).
VENTILATION	Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.
RESPIRATORY PROTECTION	If personal exposure cannot be controlled below applicable limits by ventilation, wear a fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.
	When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.
PROTECTIVE GLOVES	None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.
EYE PROTECTION	Wear safety spectacles with unperforated side shields.

Section 9 — Precautions

DOL STRONG ADHESIVE - 1A	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE	Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.
	During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.
	Consult NFPA Code. Use approved Bonding and Grounding procedures.
	Contents under pressure. Do not puncture. Incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.
OTHER PRECAUTIONS	Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 10 — Other Regulatory Information

CALIFORNIA PROPOSITION 65	WARNING: These products contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.
TSCA CERTIFICATION	All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.