

PW 2010, 2015

Water based undercoating black

MATERIAL SAFETY DATA SHEET
WATERBORNE BLACK UNDERCOATER

Page: 1

DATE PRINTED: 04/17/2001

REVISION DATE: 04/17/01

PRODUCT NAME: WATERBORNE BLACK UNDERCOATER
PRODUCT CODE: 05-365-28

HMIS: HEALTH: 1, FIRE: 0, REACTIVITY: 0, PERSONAL PROTECTION:

4 = EXTREME, 3 = HIGH, 2 = MODERATE, 1 = SLIGHT, 0 = INSIGNIFICANT, * = CHRONIC

SECTION I - MANUFACTURER IDENTIFICATION: Wesmar Products, Inc.
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

MANUFACTURER'S NAME:
ADDRESS:

24 HOUR EMERGENCY PHONE NO: 800-424-9300
INFORMATION PHONE NO: 509-535-6311

NAME OF PREPARER: JEFF WEAR

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	EXPOSURE LIMITS (TLV, PEL)	CAS NUMBER	WEIGHT PERCENT	VAPOR PRESSURE mm Hg @ TEMP (F)
Calcium Carbonate (Calcite)	ACGIH: 10 mg/m3 TWA OSHA: 5 mg/m3 TWA	1317-65-3	2.84	NA NA
Carbon Black	ACGIH, OSHA: 3.5 mg/m3 TWA	1333-86-4	1.36	NA NA

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Emergency and Community Right-to-Know Act of 1986 and of 40 CFR 372.

This product contains hazardous components which may become airborne and result in exposure when removed by abrasive blasting, sanding, or grinding. Ventilate and avoid breathing dust.

This product contains materials listed as hazardous air pollutants.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE (F): 212 - 471
SPECIFIC GRAVITY (H2O=1): 1.04
% VOLATILE BY WT: 75.05%
VAPOR DENSITY: Lighter than air.
EVAPORATION RATE: NA
V.O.C. (lb/gal): 0.47 lb/gal
SOLUBILITY IN WATER: Dilutable in water.
APPEARANCE: Black liquid.

POUNDS PER GALLON: 8.69 lb/gl
% VOLATILE BY VOL: 78.36%
V.O.C. (g/l): 56 g/l
ODOR: Ammonia odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASS:
OSHA Class IIIB (flash point >=200 F).

FLASH POINT (F): >200 METHOD USED: SET

M A T E R I A L S A F E T Y D A T A S H E E T
WATERBORNE BLACK UNDERCOATER

Page: 2

DATE PRINTED: 04/17/2001

=====

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .62 UPPER: 4.24

EXTINGUISHING MEDIA: Foam. CO2. Dry chemical. Water fog.

SPECIAL FIREFIGHTING PROCEDURES

Evacuate hazard area of unprotected personnel.

Full protective equipment is recommended including self contained breathing apparatus, to protect firefighters from hazardous combustion products.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Materials will not sustain combustion unless water has evaporated. Closed containers may explode from steam pressure when exposed to extreme heat.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable.

CONDITIONS TO AVOID

Excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID)

None reasonably foreseeable.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

The dry paint film can burn and produce one or more of the following: Carbon dioxide. Carbon monoxide. Oxides of nitrogen. Acrolein.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF EXPOSURE: Dermal: X Inhalation: X Ingestion:

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Excess inhalation of vapors and/or volatilized ammonia may produce headache, nausea, and irritation to the respiratory tract.

No chronic effects known at this time.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin contact may produce irritation due to slight alkalinity.

Liquid, vapor, and mist may produce eye irritation.

Presence of volatilized ammonia may irritate the eyes.

No chronic skin effects known at this time.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No acute effects known at this time.

No chronic effects known at this time.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No acute effects known at this time.

No chronic effects known at this time.

DATE PRINTED: 04/17/2001

=====

OTHER HEALTH HAZARDS (ACUTE AND CHRONIC)

No other acute effects known at this time.

No other chronic effects known at this time.

CARCINOGENICITY: CONTAINS CARCINOGENS: None known.

OSHA REGULATED: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

None known at this time.

EMERGENCY AND FIRST AID PROCEDURES

If splashed into the eyes, flush eyes with clear water for 15 minutes or until irritation subsides; consult a physician as required.

For irritation due to inhalation, remove to fresh air.

If irritation persists, consult a physician.

For skin contact, remove with soap and water.

If ingested, drink 1 to 2 glasses of water to dilute. Do NOT induce vomiting.

Consult a physician or poison control center immediately.

===== SECTION VII - SPILL OR LEAK PROCEDURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wearing protective gloves, wipe up liquid with absorbent cloth.

WASTE DISPOSAL METHOD

Dispose in accordance with local, state, and federal regulations.

===== SECTION VIII - SAFE HANDLING AND USE INFORMATION =====

RESPIRATORY PROTECTION

In restricted ventilation areas, use approved NIOSH/MSHA chemical/mechanical filters designed to remove a combination of particulates and vapor.

Use ventilation to keep levels below exposure guidelines (see Section II.) User

should test and monitor exposure levels to insure all personnel exposure is

below guidelines. If not sure or if not able to monitor levels, use a

NIOSH/MSHA approved air purifying respirator.

VENTILATION

Provide air movement to remove excess vapors.

Ventilation and respiratory protection must be adequate to prevent the TLV's of hazardous ingredients from being exceeded.

All application areas should be ventilated in accordance with OSHA regulations.

PROTECTIVE GLOVES

Natural rubber or latex gloves required for prolonged or repeated contact.

EYE PROTECTION

Safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

None reasonably foreseeable.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom. Smoke in smoking areas only. Wash clothes before reuse.

===== SECTION IX - SPECIAL PRECAUTIONS =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

M A T E R I A L S A F E T Y D A T A S H E E T
WATERBORNE BLACK UNDERCOATER

Page: 4

DATE PRINTED: 04/17/2001

=====

Do not store in excessive heat (above 120 deg F.) Use with adequate ventilation.

OTHER PRECAUTIONS

Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapors.

===== SECTION X - DISCLAIMER =====

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date of this material data sheet, Columbia Paint & Coatings makes no representations as to the completeness and accuracy thereof. Information is supplied upon the condition that persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Columbia Paint & Coatings be responsible for damages of any nature whatsoever resulting from the use of, misuse or reliance upon information. No representations, guarantees, or warranties (either expressed or implied), merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to information or the material to which information refers. Regulatory requirements are subject to change and may differ from one location to another. It is the user's sole responsibility to ensure its activities comply with federal, state or provincial, and local laws and regulations. This information must be included with all MSDS's that are copied and distributed for this material.