

RO 1401, 1411

MATERIAL SAFETY DATA SHEET

Page 1 of 4

Revised date:07/20/02

Product: **ECO- & HIDRO COATINGS**MSDS-505/CAN&USA

1. PRODUCT AND COMPANY IDENTIFICATION**1.1 Product specifications**

Name: HIDROTEX

Colors: White, Gray, Black

Use: One component multi-purpose waterborne protective coatings.

1.2 Manufacturer's details

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

1.3 Emergency telephone number

CAN: CANUTEC 613-996-6666

USA: CHEMTREC 800-424-9300

2. INFORMATION/COMPOSITION - PRODUCT COMPONENTS

These substances represent a risk for health according to the European Union Directives for Dangerous Substances - 92/32/CEE.

INGREDIENTS	CAS Nr	INTERVAL OF CONC %	SYMBOL*	PHRASES*	VAPOR PRESSURE (20°C/(MMHg)	SARA 313 REPORT	EXPOSURE LIMITS			
							OSHA/ NIOSH	ACGIH	STEL	CEILING
1. 2-Butoxyethanol	111-76-2	c<5	Xn	R-20/21/22-37	0.6	No	50 ppm skin	25 ppm skin	--	--

*According to EU Directives

3. PRODUCT RISKS IDENTIFICATIONThis product is not classified by the 88/379/EEC as a dangerous product.

4. FIRST AID**4.1 General**

If symptoms persist seek medical advice.

4.2 InhalationIf the damaged person has headache place him somewhere outdoors.

4.3 Eye contact

Wash eyes with plenty of water for approximately 10 minutes turning up the eyelids, seek medical attention immediately.

4.4 Skin contact

Remove contaminated clothing. Wash skin vigorously with soap and water or a proper skin wash. Never use solvents or thinners.

4.5 Ingestion

In case of ingestion, seek medical attention immediately. Keep the patient relaxed. Do not induce vomiting.

5. FIRE PROCEDURE

This is a water based product that is not combustible.

6. ACCIDENT PREVENTION MEASURES

Use safety measures mentioned in sections 7 and 8. Contain spills with non-combustible absorbents and dispose of in accordance to the requirements of local legislation (see section 13). Keep product spills, absorbent and decontaminant out of storm or sewer systems. Clean with detergent. Do not use solvents. If the product contaminates lakes, rivers, storm or sewer systems, report to the proper authorities according to local legislation.

7. HANDLING AND STORAGE

7.1 Handling

Keep out of eye and skin contact. Avoid vapour inhalation and dust produced during spray application. For personal safety/protection, please refer to paragraph 8. Do not eat, drink or smoke in application zones. Follow regulations on hygiene and safety at work.

7.2 Storage

Store according to local regulations and in a well ventilated area away from heat, frost and direct sunlight. Avoid temperatures between +5°C and +35°C. Keep the product in packages made with the same material than the original ones. Firmly replace lid after each usage and store in an upright position.

8. EXPOSITION/PERSONAL PROTECTION MEASURES

8.1 Technical measures

Provide proper ventilation, which can be obtained through good local extraction and good general extraction systems. Wear NIOSH approved respiratory equipment when handling open containers, pouring and mixing, as well as when applying and sanding.

8.2 Exposure limits

For exposure limits during work see section 2.

8.3 Personal protection

Breathing protection

Wear NIOSH approved respiratory equipment when handling open containers, pouring and mixing, as well as when applying and sanding. This will most likely be a fresh air supply or an active carbon particulate filter.

Hand protection

For prolonged or repeated contact use polyvinyl alcohol gloves or nitril rubber gloves. Barrier creams could aid in protecting skin areas that may become exposed (e.g. wrist area). NEVER use barrier creams once exposure has already occurred.

Eye protection

Wear protection designed to protect eyes against spray and splashes.

Skin protection

Cover all parts of the body, including neck and head. Exposed parts should be washed after product application.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical estate:	Viscous liquid	
Flash point:	---	UNE- EN 456
Viscosity:	200.10 ³ cps at 20°C	BROOKFIELD
Density:	1.2 grs/cc at 20°C	UNE-48098
Vapour pressure:	0.8 hPa at 20°C (2-Butoxyethanol)	
Flammable limits:	min: 1.1% vol - max: 10.6% vol (2-Butoxyethanol)	
Water solubility:	Insoluble but can be mixed in any proportion.	
Wt % Solids:	97 to 59	
Vol. % Solids:	90 to 45	
OSHA Storage:	II	
Coating VOC:	0.2 to 42 lbs./gallon	
Solvent Density:	0.01 lbs./gallon	

10. STABILITY AND REACTIVITY

Product is stable under recommended handling and storage conditions (see section 7).

11. TOXICOLOGICAL INFORMATION

There is no data available on this on this product from tested samples. Inhalation of vapour concentrations above the limit of exposure causes respiratory irritation. There are no known negative or harmful effects if handled correctly.

12. ECOLOGICAL INFORMATION

The dispersion of the product it is not classified as dangerous for the environment. Penetration into waterways, storm and sewer systems should be avoided.

13. DISPOSAL CONSIDERATIONS

Do not dispose of material or any by-products thereof into waterways, storm and sewer systems. Empty containers or residual materials should be treated according to local regulations.

14. TRANSPORT INFORMATION

Product not dangerous for its transport according to ADR/TPC (road) regulations, RID/TPF (rail) regulations, IMDG (sea) regulations and ICAO/IATA (air) regulations.

15. TRANSPORTATION:

See section 2 for further information.

HEALTH	0
FLAMMABILITY	0
REACTIVITY	0
